

Qualified Combination Ovens

V-07-2025

Qualifying electric combination oven/steamer models must have a tested steam mode cooking energy efficiency of $\geq 55\%$ and convection mode cooking energy efficiency of $\geq 78\%$ utilizing ASTM F2861, and meet the idle rate requirements in Table 1.

NOTE: Program criteria are subject to change.

Company	Model Number	Size (Steam Pans)	Fuel Type	Preheat Energy (kWh)	Convection Mode				Steam Mode			
					Idle Rate (kW)	Energy Efficiency (%)	Production Capacity (lb/h)	Cooking Water Use (gph)	Idle Rate (kW)	Energy Efficiency (%)	Production Capacity (lb/h)	Cooking Water Use (gph)
Alto-Shaam	10-20E PRO	22	Electric	1.32	2.01	85%	201	5.1	3.27	62%	276	3.3
Alto-Shaam	20-20E PRO	40	Electric	2.79	3.43	87%	370	10.8	3.45	74%	712	4.8
Alto-Shaam	CTP10-20E	22	Electric	1.32	2.01	85%	201	5.1	3.27	62%	276	3.3
Alto-Shaam	CTP20-20E	40	Electric	2.79	3.43	87%	370	10.8	3.45	74%	712	4.8
Alto-Shaam	CTP7-20E	14	Electric	1.26	1.51	80%	140	0.8	1.18	59%	171	1.5
Angelo Po	FX122E3**	24	Electric	0.98	2.12	82%	227	1.6	3.10	68%	290	3.4
Angelo Po	FX202E3**	40	Electric	3.75	3.34	82%	431	1.2	5.43	67%	524	5.3
Angelo Po	FX82E3**	16	Electric	1.32	1.69	80%	149	1.2	2.57	66%	186	2.8
Blodgett	BCT-102E	20	Electric	1.49	1.28	81%	188	0.0	3.20	67%	216	5.5
Blodgett	BCT-62E	12	Electric	1.18	1.05	79%	114	0.0	1.35	58%	99	3.2
Blodgett	BLCT-102E	20	Electric	0.83	1.26	83%	189	0.4	1.99	57%	97	4.2
Blodgett	BLCT-10E	6	Electric	0.54	0.74	78%	62	0.0	1.59	66%	100	4.5
Convotherm	C4e* 10.10ES	10	Electric	0.97	1.19	78%	104	0.0	0.71	72%	101	0.5
Convotherm	C4e* 10.10ES-N	11	Electric	1.03	1.09	80%	108	0.0	0.88	72%	158	0.5
Convotherm	C4e* 10.20EB	22	Electric	1.53	1.74	81%	216	0.0	2.52	64%	348	10.6
Convotherm	C4e* 10.20ES	22	Electric	1.49	1.68	83%	232	0.1	1.56	76%	337	2.7
Convotherm	C4e* 6.20EB	14	Electric	1.46	1.42	80%	145	0.0	1.85	61%	213	8.1
Convotherm	C4e* 6.20ES	14	Electric	1.05	1.36	81%	139	0.0	1.44	70%	183	0.2
Convotherm	Cmn 10.10 pro	8	Electric	0.67	0.72	80%	80	2.9	0.89	70%	104	2.7
Convotherm	Cmn 6.10 pro	5	Electric	0.51	0.61	79%	54	1.1	0.56	70%	81	1.9
Convotherm	OES-6.10 Mini	4	Electric	0.44	0.61	81%	44	0.0	0.89	69%	61	0.4
Eloma	Compact PRO 6-11	6	Electric	0.47	0.61	80%	59	0.0	1.15	63%	62	0.9
Eloma	GENIUS MT 12-21E	24	Electric	2.61	2.01	78%	203	0.0	3.55	67%	313	6.5
Giorik	SEHE102W	20	Electric	1.43	1.69	81%	200	0.0	1.81	68%	220	12.9
Giorik	SEHE102WH	20	Electric	1.43	1.69	81%	200	0.0	1.81	68%	220	12.9
Giorik	SETE102W	20	Electric	1.68	1.86	80%	193	0.0	1.44	70%	263	7.5
Giorik	SETE202W	40	Electric	2.40	3.36	85%	366	0.0	3.18	64%	431	13.9
Giorik	SETE202WH	40	Electric	2.40	3.36	85%	366	0.0	3.18	64%	431	13.9
Henny Penny	FSEN610	6	Electric	0.60	0.59	78%	57	0.0	1.35	63%	78	5.1
Lainox	NAEB071	7	Electric	0.79	1.03	78%	84	0.0	1.46	62%	107	3.0
Lainox	NAEB101	10	Electric	1.13	1.21	82%	110	3.3	1.63	63%	175	4.9
Lainox	NAEB102	20	Electric	1.56	1.88	83%	194	0.0	2.34	65%	366	17.2
Lainox	NAEV071	7	Electric	0.79	1.03	78%	84	0.0	1.42	66%	92	0.2
Lainox	NAEV072	14	Electric	1.56	1.27	81%	138	14.1	1.13	70%	128	3.4
Lainox	NAEV101	10	Electric	1.13	1.21	82%	110	3.3	1.22	66%	98	1.3
Lainox	NAEV102	20	Electric	1.56	1.76	84%	196	8.8	1.93	72%	186	2.1
RATIONAL	ICC 6-FULL E (LM200CE) CC2ERRA.*****	12	Electric	0.45	1.06	82%	144	0.0	0.86	64%	282	6.1
RATIONAL	ICC 6-HALF E (LM200BE) CB2ERRA.*****	6	Electric	0.80	0.70	78%	71	0.0	0.68	61%	122	6.4
RATIONAL	ICP 10-FULL E (LM100EE) CE1ERRA.*****	20	Electric	1.44	1.22	82%	206	0.1	1.19	64%	383	7.8
RATIONAL	ICP 10-HALF E (LM100DE) CD1ERRA.*****	10	Electric	0.82	0.94	81%	107	0.0	0.91	63%	188	3.5
RATIONAL	ICP 20-FULL E (LM100GE) CG1ERRA.*****	40	Electric	2.40	2.19	87%	430	0.0	3.70	68%	880	23.8
RATIONAL	ICP 20-HALF E (LM100FE) CF1ERRA.*****	20	Electric	1.86	1.71	79%	210	0.0	1.89	61%	375	10.6
RATIONAL	ICP 6-FULL E (LM100CE) CC1ERRA.*****	12	Electric	1.00	0.95	81%	127	15.4	0.87	59%	236	16.8
RATIONAL	ICP 6-HALF E (LM100BE) CB1ERRA.*****	6	Electric	0.54	0.71	80%	66	0.0	0.82	59%	103	3.1
Retigo	B621i	12	Electric	1.00	1.10	80%	118	0.0	1.25	68%	170	3.9
Retigo	H14-0801-DB	12	Electric	1.00	1.10	80%	118	0.0	1.25	68%	170	3.9
UNOX	XAVC-06FS-EP*	12	Electric	0.95	1.13	78%	117	0.2	1.33	64%	179	6.8

Qualified Combination Ovens

V-07-2025

Qualifying electric combination oven/steamer models must have a tested steam mode cooking energy efficiency of ≥ 55% and convection mode cooking energy efficiency of ≥ 78% utilizing ASTM F2861, and meet the idle rate requirements in Table 1.

NOTE: Program criteria are subject to change.

Company	Model Number	Size (Steam Pans)	Fuel Type	Preheat Energy (kWh)	Convection Mode				Steam Mode			
					Idle Rate (kW)	Energy Efficiency (%)	Production Capacity (lb/h)	Cooking Water Use (gph)	Idle Rate (kW)	Energy Efficiency (%)	Production Capacity (lb/h)	Cooking Water Use (gph)
Alto-Shaam	10-20E PRO	22	Electric	1.32	2.01	85%	201	5.1	3.27	62%	276	3.3
UNOX	XAVC-10FS-EP*	20	Electric	1.54	1.57	83%	192	0.0	1.65	63%	287	13.0
Vulcan	CHEF-62E-***	12	Electric	1.08	1.23	79%	126	2.0	1.79	60%	245	8.0
Vulcan	TCM-102E-*****	20	Electric	1.15	1.56	83%	198	0.0	1.89	66%	321	8.1

Table 1. Idle Rate Requirements for Commercial Combination Oven/Steamers

Combi Oven Type	Steam Mode Idle Rate	Convection Mode Idle Rate
Electric Combi <15 pan capacity*	≤ 2.635 kW	≤ 1.595 kW
Electric Combi 15-28 pan capacity*	≤ 4.364 kW	≤ 2.674 kW
Electric Combi >28 pan capacity*	≤ 5.96 kW	≤ 3.67 kW

*Combination oven/steamer pan capacity based on the maximum capacity of standard 2 ½-inch deep hotel pans. This must be consistent with the number of pans used to meet the energy-efficiency qualifications utilizing ASTM F2861.

Qualified Convection Ovens

V-07-2025

Qualifying models must be listed in the California Energy Commission database. Qualifying full-size (≥ 5 pans) electric convection ovens must have a cooking energy efficiency of ≥ 76% and an idle energy rate ≤ 1.4 kW utilizing ASTM Standard F1496. Full-size (< 5 pans) electric convection ovens must have a cooking energy efficiency of ≥ 76% and an idle rate of ≤ 1.0 kW. Half-size electric convection ovens must have a cooking energy efficiency of ≥ 71% and an idle energy rate ≤ 1.0 kW. Multiple oven configurations are paid per qualifying oven.

NOTE: Program criteria are subject to change.

Company	Model Number	Oven Size	Number of Cavities	Test Pan Capacity	Fuel Type	Energy Input Rate (kW)	Preheat Energy (kWh)	Idle Energy Rate (kW)	Energy Efficiency (%)	Production Capacity (lb/h)
Belshaw Adamatic	BX3 Eco Touch	Full	1	3	Electric	7.5	0.75	1.00	76%	59
Belshaw Adamatic	BX4 Eco Touch	Full	1	4	Electric	7.5	0.85	1.00	82%	74
Belshaw Adamatic	FG189T-UZ8*	Full	1	3	Electric	7.5	0.75	1.00	76%	59
Belshaw Adamatic	FG189T-UZ9*	Full	1	4	Electric	7.5	0.85	1.00	82%	74
Blodgett	BDO-100-E	Full	1	5	Electric	11.0	1.39	1.21	78%	99
Blodgett	BDO-100-E DBL	Full	2	5	Electric	11.0	1.39	1.21	78%	99
Blodgett	CTB	Half	1	5	Electric	5.6	0.92	1.00	74%	50
Blodgett	CTB DBL	Half	2	5	Electric	5.6	0.92	1.00	74%	50
Blodgett	CTBR	Half	1	5	Electric	5.6	0.92	1.00	74%	50
Blodgett	CTBR DBL	Half	2	5	Electric	5.6	0.92	1.00	74%	50
Blodgett	HV100E	Full	1	5	Electric	15.0	1.49	1.31	76%	114
Blodgett	HV100E DBL	Full	2	5	Electric	15.0	1.49	1.31	76%	114
Blodgett	HVH-100E	Full	1	5	Electric	15.0	1.49	1.31	76%	114
Blodgett	HVH-100E DBL	Full	2	5	Electric	15.0	1.49	1.31	76%	114
Blodgett	Mark V-100	Full	1	5	Electric	11.0	1.39	1.21	78%	99
Blodgett	Mark V-100 DBL	Full	2	5	Electric	11.0	1.39	1.21	78%	99
Blodgett	Mark V-100-K12	Full	1	5	Electric	11.0	1.39	1.21	78%	99
Blodgett	Mark V-100-K12 DBL	Full	2	5	Electric	11.0	1.39	1.21	78%	99
Blodgett	Mark V-200	Full	1	5	Electric	11.0	1.54	1.17	78%	106
Blodgett	Mark V-200 DBL	Full	2	5	Electric	11.0	1.54	1.17	78%	106
Blodgett	Mark V-200-K12	Full	1	5	Electric	11.0	1.54	1.17	78%	106
Blodgett	Mark V-200-K12 DBL	Full	2	5	Electric	11.0	1.54	1.17	78%	106
Blodgett	SHO-100-E	Full	1	5	Electric	11.0	1.39	1.21	78%	99
Blodgett	SHO-100-E DBL	Full	2	5	Electric	11.0	1.39	1.21	78%	99
Blodgett	Zephaire-100-E	Full	1	5	Electric	11.0	1.39	1.21	78%	99
Blodgett	Zephaire-100-E DBL	Full	2	5	Electric	11.0	1.39	1.21	78%	99
Blodgett	Zephaire-200-E	Full	1	5	Electric	11.0	1.54	1.17	78%	106
Blodgett	Zephaire-200-E DBL	Full	2	5	Electric	11.0	1.54	1.17	78%	106
Blue Seal	E32D5	Full	1	5	Electric	6.5	0.67	1.00	80%	82
Cadco	OV-013**	Half	1	3	Electric	1.4	0.20	0.48	72%	14
Cadco	XAFT-03HS-**	Half	1	3	Electric	2.6	0.32	0.67	74%	27
Cadco	XAFT-04HS-**	Half	1	4	Electric	2.9	0.37	0.79	73%	30
Doyon	DCOT5	Half	1	5	Electric	4.0	0.55	0.71	78%	51
Equipex	FC60	Half	1	4	Electric	2.7	0.29	0.66	74%	23
Lang	ECOH	Half	1	5	Electric	7.8	0.68	0.83	74%	48
Moffat	E22M3	Half	1	3	Electric	1.5	0.31	0.55	76%	22
Moffat	E23D3	Half	1	3	Electric	2.7	0.33	0.62	71%	27
Moffat	E23M3	Half	1	3	Electric	2.7	0.33	0.62	71%	27
Moffat	E32D4	Full	1	4	Electric	6.5	0.67	0.98	77%	73
Moffat	E32D4/2	Full	2	4	Electric	6.5	0.67	0.98	77%	73
Moffat	E32D5	Full	1	5	Electric	5.8	0.67	1.00	80%	82
Moffat	E32D5/2	Full	2	5	Electric	5.8	0.67	1.00	80%	82
Moffat	E32MS	Full	1	5	Electric	6.0	0.58	0.80	82%	77
Moffat	E32MS/2	Full	2	5	Electric	6.0	0.58	0.80	82%	77
Moffat	E33D5	Half	1	5	Electric	6.0	0.50	0.66	75%	48
Moffat	E33T5	Half	1	5	Electric	6.0	0.50	0.66	75%	48
Mono Equipment	BX3 Eco Touch	Full	1	3	Electric	7.5	0.75	1.00	76%	59
Mono Equipment	BX4 Eco Touch	Full	1	4	Electric	7.5	0.85	1.00	82%	74
Nu-Vu	NCOT5	Half	1	5	Electric	4.0	0.55	0.71	78%	51
Nu-Vu	X5	Full	1	5	Electric	6.2	0.63	1.35	76%	104
Revent	ONE39E	Full	1	8	Electric	15.2	3.35	1.35	85%	117
Royal	RECO-1	Full	1	6	Electric	9.0	1.40	1.39	76%	103
Royal	RECO-2	Full	2	6	Electric	9.0	1.40	1.39	76%	103
Southbend	BES/17CCH	Full	1	5	Electric	8.5	1.53	1.34	76%	92
Southbend	BES/17SC	Full	1	5	Electric	8.5	1.53	1.34	76%	92

Qualified Convection Ovens

V-07-2025

Qualifying models must be listed in the California Energy Commission database. Qualifying full-size (≥ 5 pans) electric convection ovens must have a cooking energy efficiency of ≥ 76% and an idle energy rate ≤ 1.4 kW utilizing ASTM Standard F1496. Full-size (< 5 pans) electric convection ovens must have a cooking energy efficiency of ≥ 76% and an idle rate of ≤ 1.0 kW. Half-size electric convection ovens must have a cooking energy efficiency of ≥ 71% and an idle energy rate ≤ 1.0 kW. Multiple oven configurations are paid per qualifying oven.

NOTE: Program criteria are subject to change.

Company	Model Number	Oven Size	Number of Cavities	Test Pan Capacity	Fuel Type	Energy Input Rate (kW)	Preheat Energy (kWh)	Idle Energy Rate (kW)	Energy Efficiency (%)	Production Capacity (lb/h)
Belshaw Adamatic	BX3 Eco Touch	Full	1	3	Electric	7.5	0.75	1.00	76%	59
Belshaw Adamatic	BX4 Eco Touch	Full	1	4	Electric	7.5	0.85	1.00	82%	74
Belshaw Adamatic	FG189T-UZ8*	Full	1	3	Electric	7.5	0.75	1.00	76%	59
Southbend	BES/17TC	Full	1	5	Electric	8.5	1.53	1.34	76%	92
Southbend	BES/27CCH	Full	2	5	Electric	8.5	1.53	1.34	76%	92
Southbend	BES/27SC	Full	2	5	Electric	8.5	1.53	1.34	76%	92
Southbend	BES/27TC	Full	2	5	Electric	8.5	1.53	1.34	76%	92
Southbend	ES/17CCH	Full	1	5	Electric	8.5	1.53	1.34	76%	92
Southbend	ES/17SC	Full	1	5	Electric	8.5	1.53	1.34	76%	92
Southbend	ES/17TC	Full	1	5	Electric	8.5	1.53	1.34	76%	92
Southbend	ES/27CCH	Full	2	5	Electric	8.5	1.53	1.34	76%	92
Southbend	ES/27SC	Full	2	5	Electric	8.5	1.53	1.34	76%	92
Southbend	ES/27TC	Full	2	5	Electric	8.5	1.53	1.34	76%	92
Southbend	KES/17CCH	Full	1	5	Electric	8.5	1.53	1.34	76%	92
Southbend	KES/17SC	Full	1	5	Electric	8.5	1.53	1.34	76%	92
Southbend	KES/17TC	Full	1	5	Electric	8.5	1.53	1.34	76%	92
Southbend	KES/27CCH	Full	2	5	Electric	8.5	1.53	1.34	76%	92
Southbend	KES/27SC	Full	2	5	Electric	8.5	1.53	1.34	76%	92
Southbend	KES/27TC	Full	2	5	Electric	8.5	1.53	1.34	76%	92
Southbend	KLES/17CCH	Full	1	5	Electric	8.5	1.53	1.34	76%	92
Southbend	KLES/17SC	Full	1	5	Electric	8.5	1.53	1.34	76%	92
Southbend	KLES/17TC	Full	1	5	Electric	8.5	1.53	1.34	76%	92
Southbend	KLES/27CCH	Full	2	5	Electric	8.5	1.53	1.34	76%	92
Southbend	KLES/27SC	Full	2	5	Electric	8.5	1.53	1.34	76%	92
Southbend	KLES/27TC	Full	2	5	Electric	8.5	1.53	1.34	76%	92
Southbend	KS/17CCH	Full	1	5	Electric	8.5	1.53	1.34	76%	92
Southbend	KS/17SC	Full	1	5	Electric	8.5	1.53	1.34	76%	92
Southbend	KS/17TC	Full	1	5	Electric	8.5	1.53	1.34	76%	92
Southbend	KS/27CCH	Full	2	5	Electric	8.5	1.53	1.34	76%	92
Southbend	KS/27SC	Full	2	5	Electric	8.5	1.53	1.34	76%	92
Southbend	KS/27TC	Full	2	5	Electric	8.5	1.53	1.34	76%	92
Southbend	PCE15S/S*	Full	2	5	Electric	8.5	1.53	1.34	76%	92
Southbend	PCE15S/T*	Full	2	5	Electric	8.5	1.53	1.34	76%	92
Southbend	PCE75S/S*	Full	1	5	Electric	8.5	1.53	1.34	76%	92
Southbend	PCE75S/T*	Full	1	5	Electric	8.5	1.53	1.34	76%	92
Southbend	SLES/17CCH	Full	1	5	Electric	8.5	1.53	1.34	76%	92
Southbend	SLES/17SC	Full	1	5	Electric	8.5	1.53	1.34	76%	92
Southbend	SLES/17TC	Full	1	5	Electric	8.5	1.53	1.34	76%	92
Southbend	SLES/27CCH	Full	2	5	Electric	8.5	1.53	1.34	76%	92
Southbend	SLES/27SC	Full	2	5	Electric	8.5	1.53	1.34	76%	92
Southbend	SLES/27TC	Full	2	5	Electric	8.5	1.53	1.34	76%	92
UNOX	OV-013**	Half	1	3	Electric	1.4	0.20	0.48	72%	14
UNOX	XAFT-03HS-**	Half	1	3	Electric	2.6	0.32	0.67	74%	27
UNOX	XAFT-04HS-**	Half	1	4	Electric	2.9	0.37	0.79	73%	30
Vulcan	VC44E*	Full	2	5	Electric	12.5	1.24	1.40	76%	94
Vulcan	VC4E*	Full	1	5	Electric	12.5	1.24	1.40	76%	94
Vulcan	VC55E*	Full	2	5	Electric	12.5	1.24	1.40	76%	94
Vulcan	VC5E*	Full	1	5	Electric	12.5	1.24	1.40	76%	94
Wells	M4200	Half	1	5	Electric	8.4	0.67	0.75	77%	51

Qualified Convection Ovens

V-07-2025

Qualifying models must be listed in the California Energy Commission database. Qualifying full-size (≥ 5 pans) electric convection ovens must have a cooking energy efficiency of ≥ 76% and an idle energy rate ≤ 1.4 kW utilizing ASTM Standard F1496. Full-size (< 5 pans) electric convection ovens must have a cooking energy efficiency of ≥ 76% and an idle rate of ≤ 1.0 kW. Half-size electric convection ovens must have a cooking energy efficiency of ≥ 71% and an idle energy rate ≤ 1.0 kW. Multiple oven configurations are paid per qualifying oven.

NOTE: Program criteria are subject to change.

Company	Model Number	Oven Size	Number of Cavities	Test Pan Capacity	Fuel Type	Energy Input Rate (kW)	Preheat Energy (kWh)	Idle Energy Rate (kW)	Energy Efficiency (%)	Production Capacity (lb/h)
Belshaw Adamatic	BX3 Eco Touch	Full	1	3	Electric	7.5	0.75	1.00	76%	59
Belshaw Adamatic	BX4 Eco Touch	Full	1	4	Electric	7.5	0.85	1.00	82%	74
Belshaw Adamatic	FG189T-UZ8*	Full	1	3	Electric	7.5	0.75	1.00	76%	59

Qualified Deck Ovens

Qualifying electric deck ovens must have a tested heavy load cooking energy efficiency of ≥ 60% and an idle energy rate less than or equal to 1,300 W, utilizing ASTM Standard F1965.

Multiple deck oven configurations are paid per qualifying oven deck.

NOTE: Program criteria are subject to change.

V-07-2025

Company	Model Number	Size	Fuel Type	Preheat Energy (kWh)	Idle Energy Rate (kW)	Energy Efficiency (%)	Production Capacity (lb/h)
Cuppone	Donatello DN635L/*CD	Full	Electric	2.3	1.1	66%	61
Cuppone	Donatello DN935/*CD	Full	Electric	5.5	1.2	82%	95
Cuppone	Evolution	Full	Electric	3.6	1.3	75%	110
Cuppone	MAX635L/*DG	Full	Electric	2.1	1.2	75%	46
Cuppone	MAX935/*DG	Full	Electric	2.8	1.1	82%	68
Cuppone	Michelangelo ML-635L/*	Full	Electric	2.3	1.1	92%	60
Cuppone	Michelangelo ML-935/*	Full	Electric	3.5	1.2	74%	84
Cuppone	Tiziano TZ430	Full	Electric	1.5	0.9	70%	45
Doyon	2T	Full	Electric	2.5	1.3	60%	35
Pizza Master	PM 72*	Full	Electric	1.6	0.7	93%	25
Pizza Master	PM 73*	Full	Electric	3.1	1.0	63%	37
Pizza Master	PM 74*	Full	Electric	1.6	1.1	67%	46
Pizza Master	PM 83*	Full	Electric	1.8	1.2	68%	48
Pizza Master	PM 91*	Full	Electric	3.1	1.0	68%	37
Pizza Master	PM 92*	Full	Electric	2.8	0.9	80%	54
Pizza Master	PM 93*	Full	Electric	1.5	1.2	67%	128
Revent	US * deck 1 pan	Full	Electric	3.1	1.0	68%	37
Revent	US * deck 2 pan	Full	Electric	3.5	1.1	63%	37
Revent	US * deck 3 pan	Full	Electric	1.5	1.2	67%	128



Qualified Deck Ovens

Qualifying electric deck ovens must have a tested heavy load cooking energy efficiency of ≥ 60% and an idle energy rate less than or equal to 1,300 W, utilizing ASTM Standard F1965.

Multiple deck oven configurations are paid per qualifying oven deck.

NOTE: Program criteria are subject to change.

V-07-2025

Company	Model Number	Size	Fuel Type	Preheat Energy (kWh)	Idle Energy Rate (kW)	Energy Efficiency (%)	Production Capacity (lb/h)
Cuppone	Donatello DN635L/*CD	Full	Electric	2.3	1.1	66%	61
Cuppone	Donatello DN935/*CD	Full	Electric	5.5	1.2	82%	95
Cuppone	Evolution	Full	Electric	3.6	1.3	75%	110
Cuppone	MAX635L/*DG	Full	Electric	2.1	1.2	75%	46

Qualified Fryers

V-07-2025

Qualifying electric fryer models (vat width < 18-inches) must meet ENERGY STAR specifications and have a tested heavy load cooking energy efficiency of ≥ 83% and an idle energy rate ≤ 800 W utilizing ASTM Standard F1361. Qualifying electric fryer models (vat width ≥ 18-inches) must meet ENERGY STAR specifications and have a tested heavy load cooking energy efficiency of ≥ 80% and an idle energy rate ≤ 1,100 W utilizing ASTM Standard F2144.

Multiple vat configurations are paid per qualifying vat.

NOTE: Program criteria are subject to change.

Company	Model Number	Number of Vats	Vat Width	Shortening Capacity (lb)	Fuel Type	Preheat Energy (kWh)	Idle Energy Rate (kW)	Energy Efficiency (%)	Production Capacity (lb/h)
BKI	ALF-FC	1	14	50	Electric	1.74	0.80	86%	45
Frymaster	1FQE60U***	1	18	63	Electric	2.68	0.88	91%	84
Frymaster	1FQE80U***	1	18	80	Electric	2.15	1.09	90%	84
Frymaster	2FQE30U***	2	13	30	Electric	1.64	0.61	87%	61
Frymaster	2FQE60U***	2	18	63	Electric	2.68	0.88	91%	84
Frymaster	2FQE80U***	2	18	80	Electric	2.15	1.09	90%	84
Frymaster	3FQE30U***	3	13	30	Electric	1.64	0.61	87%	61
Frymaster	3FQE60U***	3	18	63	Electric	2.68	0.88	91%	84
Frymaster	3FQE80U***	3	18	80	Electric	2.15	1.09	90%	84
Frymaster	4FQE30U***	4	13	30	Electric	1.64	0.61	87%	61
Frymaster	BIELA214***	2	13	30	Electric	1.64	0.61	87%	61
Frymaster	BIELA314***	3	13	30	Electric	1.64	0.61	87%	61
Frymaster	BIELA414***	4	13	30	Electric	1.64	0.61	87%	61
Frymaster	BIELA514***	5	13	30	Electric	1.64	0.61	87%	61
Frymaster	FPEL14	1	14	35	Electric	1.47	0.62	87%	58
Frymaster	FPEL214	2	14	35	Electric	1.47	0.62	87%	58
Frymaster	FPEL314	3	14	35	Electric	1.47	0.62	87%	58
Frymaster	FPEL414	4	14	35	Electric	1.47	0.62	87%	58
Frymaster	FPEL514	5	14	35	Electric	1.47	0.62	87%	58
Frymaster	FPRE180**	1	18	80	Electric	2.05	1.09	89%	62
Frymaster	FPRE280**	2	18	80	Electric	2.05	1.09	89%	62
Frymaster	FPRE380**	3	18	80	Electric	2.05	1.09	89%	62
Frymaster	FPRE480**	4	18	80	Electric	2.05	1.09	89%	62
Frymaster	H17TC	1	14	50	Electric	1.70	0.77	84%	72
Frymaster	RE14***	1	14	50	Electric	1.52	0.62	87%	61
Frymaster	RE180**	1	18	80	Electric	2.05	1.09	89%	62
Frymaster	RE22***	1	14	50	Electric	1.65	0.52	89%	69
Giles Enterprises, Inc.	EOF-24	1	24	175	Electric	4.84	0.95	83%	150
Giles Enterprises, Inc.	GEF-400	1	13	45	Electric	1.32	0.70	86%	53
Giles Enterprises, Inc.	GEF-560	1	18.5	60	Electric	1.52	0.83	89%	77
Giles Enterprises, Inc.	GEF-720	1	18.5	75	Electric	3.17	0.93	85%	96
Henny Penny	EEE-141	1	12	30	Electric	1.49	0.72	85%	59
Henny Penny	EEE-141 Split Vat	1	14	30	Electric	1.59	0.76	86%	61
Henny Penny	EEE-142	2	12	30	Electric	1.49	0.72	85%	59
Henny Penny	EEE-142 Split Vat	2	14	30	Electric	1.59	0.76	86%	61
Henny Penny	EEE-143	3	12	30	Electric	1.49	0.72	85%	59
Henny Penny	EEE-143 Split Vat	3	14	30	Electric	1.59	0.76	86%	61
Henny Penny	EEE-144	4	12	30	Electric	1.49	0.72	85%	59
Henny Penny	EEE-144 Split Vat	4	14	30	Electric	1.59	0.76	86%	61
Henny Penny	LVE-201	1	12	30	Electric	1.42	0.73	86%	62
Henny Penny	LVE-201 Split Vat	1	12	30	Electric	1.52	0.79	85%	57
Henny Penny	LVE-202	2	12	30	Electric	1.42	0.73	86%	62
Henny Penny	LVE-202 Split Vat	2	12	30	Electric	1.52	0.79	85%	57
Henny Penny	LVE-203	3	12	30	Electric	1.42	0.73	86%	62
Henny Penny	LVE-203 Split Vat	3	12	30	Electric	1.52	0.79	85%	57
Henny Penny	LVE-204	4	12	30	Electric	1.42	0.73	86%	62
Henny Penny	LVE-204 Split Vat	4	12	30	Electric	1.52	0.79	85%	57
Henny Penny	LVE-302	2	14	30	Electric	1.37	0.50	86%	47
Henny Penny	LVE-303	3	14	30	Electric	1.37	0.50	86%	47
Henny Penny	LVE-304	4	14	30	Electric	1.37	0.50	86%	47
Henny Penny	OEA-321 (22kW)	1	14	65	Electric	2.58	0.75	83%	69
Henny Penny	OEA-322 (22kW)	2	14	65	Electric	2.58	0.75	83%	69
Henny Penny	OEA-323 (22kW)	3	14	65	Electric	2.58	0.75	83%	69
Henny Penny	OFE-321 (22kW)	1	14	65	Electric	2.58	0.75	83%	69
Henny Penny	OFE-322 (22kW)	2	14	65	Electric	2.58	0.75	83%	69
Henny Penny	OFE-323 (22kW)	3	14	65	Electric	2.58	0.75	83%	69
Hobart	HF50	1	14	50	Electric	1.76	0.63	85%	72
Motion Technology, Inc.	MTI-10X	1	N/A	15	Electric	1.07	0.67	86%	28
Perfect Fry Company	PFA720	1	N/A	15	Electric	0.98	0.59	86%	35

Qualified Fryers

V-07-2025

Qualifying electric fryer models (vat width < 18-inches) must meet ENERGY STAR specifications and have a tested heavy load cooking energy efficiency of ≥ 83% and an idle energy rate ≤ 800 W utilizing ASTM Standard F1361. Qualifying electric fryer models (vat width ≥ 18-inches) must meet ENERGY STAR specifications and have a tested heavy load cooking energy efficiency of ≥ 80% and an idle energy rate ≤ 1,100 W utilizing ASTM Standard F2144.

Multiple vat configurations are paid per qualifying vat.

NOTE: Program criteria are subject to change.

Company	Model Number	Number of Vats	Vat Width	Shortening Capacity (lb)	Fuel Type	Preheat Energy (kWh)	Idle Energy Rate (kW)	Energy Efficiency (%)	Production Capacity (lb/h)
BKI	ALF-FC	1	14	50	Electric	1.74	0.80	86%	45
Frymaster	1FQE60U***	1	18	63	Electric	2.68	0.88	91%	84
Frymaster	1FQE80U***	1	18	80	Electric	2.15	1.09	90%	84
Resfab	MB-85***	1	20	85	Electric	3.66	1.10	84%	69
Sapidus	UE1100	1	14	60	Electric	1.72	0.79	84%	54
Sapidus	UE1100-3	1	21	70	Electric	2.51	1.09	86%	69
Ultrafryer Systems	B-E20-18-2-***	2	18	100	Electric	2.34	1.08	83%	93
Ultrafryer Systems	B-E20-18-3-***	3	18	100	Electric	2.34	1.08	83%	93
Ultrafryer Systems	B-E20-18-4-***	4	18	100	Electric	2.34	1.08	83%	93
Ultrafryer Systems	B-E20-18-5-***	5	18	100	Electric	2.34	1.08	83%	93
Ultrafryer Systems	B-E20-18-6-***	6	18	100	Electric	2.34	1.08	83%	93
Ultrafryer Systems	F-E20-18	1	18	100	Electric	2.34	1.08	83%	93
Vulcan	1ER50**	1	14	50	Electric	1.75	0.74	86%	58
Vulcan	1ER85**	1	18	85	Electric	2.78	1.08	88%	105
Vulcan	1VEF50	1	14	50	Electric	1.86	0.77	87%	66
Vulcan	2ER50**	2	14	50	Electric	1.75	0.74	86%	58
Vulcan	2ER85**	2	18	85	Electric	2.78	1.08	88%	105
Vulcan	3ER50**	3	14	50	Electric	1.75	0.74	86%	58
Vulcan	3ER85**	3	18	85	Electric	2.78	1.08	88%	105
Vulcan	4ER50**	4	14	50	Electric	1.75	0.74	86%	58
Vulcan	4ER85**	4	18	85	Electric	2.78	1.08	88%	105
Vulcan	CEF40	1	14	45	Electric	1.88	0.70	85%	70

Qualified Fryers

V-07-2025

Qualifying electric fryer models (vat width < 18-inches) must meet ENERGY STAR specifications and have a tested heavy load cooking energy efficiency of ≥ 83% and an idle energy rate ≤ 800 W utilizing ASTM Standard F1361. Qualifying electric fryer models (vat width ≥ 18-inches) must meet ENERGY STAR specifications and have a tested heavy load cooking energy efficiency of ≥ 80% and an idle energy rate ≤ 1,100 W utilizing ASTM Standard F2144.

Multiple vat configurations are paid per qualifying vat.

NOTE: Program criteria are subject to change.

Company	Model Number	Number of Vats	Vat Width	Shortening Capacity (lb)	Fuel Type	Preheat Energy (kWh)	Idle Energy Rate (kW)	Energy Efficiency (%)	Production Capacity (lb/h)
BKI	ALF-FC	1	14	50	Electric	1.74	0.80	86%	45
Frymaster	1FQE60U***	1	18	63	Electric	2.68	0.88	91%	84
Frymaster	1FQE80U***	1	18	80	Electric	2.15	1.09	90%	84

Qualified Griddles

V-07-2025

Qualifying electric griddle models must have a tested heavy-load cooking energy efficiency of ≥ 70% and an idle energy rate of ≤ 355 Watts per ft² of cooking surface, utilizing ASTM Standard F1275 for single-sided griddles and F1605 for double-sided griddles.

NOTE: Program criteria are subject to change.

Company	Model Number	Single or Double Sided	Fuel Type	Nominal Width (ft)	Surface Area (ft²)	Preheat Energy (Wh/ft²)	Idle Energy Rate (W/ft²)	Energy Efficiency (%)	Production Capacity (lb/h/ft²)
AccuTemp	EAN2083E1800	Single	Electric	2	4.80	263	279	87%	4.7
AccuTemp	EGD****B3600	Single	Electric	3	5.55	576	271	86%	9.8
AccuTemp	EGD****B4800	Single	Electric	4	7.13	576	271	86%	9.8
AccuTemp	EGF****A2450	Single	Electric	2	5.00	566	274	86%	10.6
AccuTemp	EGF****A3650	Single	Electric	3	7.50	576	271	86%	9.8
AccuTemp	EGF****A4850	Single	Electric	4	9.43	576	271	86%	9.8
AccuTemp	EGF****B2450	Single	Electric	2	3.88	566	274	86%	10.6
AccuTemp	EGF****B3650	Single	Electric	3	5.82	576	271	86%	9.8
AccuTemp	EGF****B4850	Single	Electric	4	7.77	576	271	86%	9.8
AccuTemp	EGF****C2201	Single	Electric	2	4.75	576	271	86%	9.8
Garland	MWE-2W	Double	Electric	3	6.00	575	300	76%	8.3
Garland	MWE2S	Double	Electric	3	6.00	575	300	76%	8.3
Garland	MWE3W-1	Double	Electric	3	6.00	662	307	78%	11.4
Garland	XE24	Double	Electric	2	4.00	878	255	75%	17.6
Garland	XPE36	Double	Electric	3	5.50	776	329	82%	17.1
Imperial	ITG-24-E	Single	Electric	2	4.00	285	210	77%	5.0
Imperial	ITG-36-E	Single	Electric	3	6.00	285	210	77%	5.0
Imperial	ITG-48-E	Single	Electric	4	8.00	285	210	77%	5.0
Imperial	ITG-60-E	Single	Electric	5	10.00	285	210	77%	5.0
Imperial	ITG-72-E	Single	Electric	6	12.00	285	210	77%	5.0
Keating	24X30FT-E	Single	Electric	2	4.00	438	247	72%	5.1
Keating	27X30-E	Single	Electric	2	4.00	438	247	72%	5.1
Keating	27X30FT-E	Single	Electric	2	4.50	438	247	72%	5.1
Keating	30X30-E	Single	Electric	3	4.50	438	247	72%	5.1
Keating	30X30FT-E	Single	Electric	3	5.00	438	247	72%	5.1
Keating	36X30-E	Single	Electric	3	5.50	438	247	72%	5.1
Keating	36X30FT-E	Single	Electric	3	6.00	438	247	72%	5.1
Keating	36X36FT-E	Single	Electric	3	7.50	438	247	72%	5.1
Keating	42X30-E	Single	Electric	4	6.50	438	247	72%	5.1
Keating	42X30FT-E	Single	Electric	4	7.00	438	247	72%	5.1
Keating	48X30-E	Single	Electric	4	7.50	438	247	72%	5.1
Keating	48X30FT-E	Single	Electric	4	8.00	438	247	72%	5.1
Keating	48X36FT-E	Single	Electric	4	10.00	438	247	72%	5.1
Keating	60X30-E	Single	Electric	5	9.50	438	247	72%	5.1
Keating	60X30FT-E	Single	Electric	5	10.00	438	247	72%	5.1
Keating	60X36FT-E	Single	Electric	5	12.50	438	247	72%	5.1
Keating	72X30-E	Single	Electric	6	11.50	438	247	72%	5.1
Keating	72X30FT-E	Single	Electric	6	12.00	438	247	72%	5.1
Keating	72X36FT-E	Single	Electric	6	15.00	438	247	72%	5.1
Lang	124TC	Single	Electric	2	3.83	577	268	75%	6.8
Lang	136TC	Single	Electric	3	6.00	577	268	75%	6.8
Lang	148TC	Single	Electric	4	7.67	577	268	75%	6.8
Lang	160TC	Single	Electric	5	9.58	577	268	75%	6.8
Lang	172TC	Single	Electric	6	11.50	577	268	75%	6.8
Taylor Company	C810-**	Double	Electric	3	6.00	637	320	77%	11.2
Taylor Company	C812-**	Double	Electric	3	6.00	637	320	77%	11.2
Taylor Company	C832-**	Double	Electric	3	6.00	637	307	76%	8.6
Taylor Company	C842-**	Double	Electric	3	6.00	637	320	77%	11.2
Taylor Company	L810-**	Double	Electric	3	6.00	728	318	87%	17.1
Taylor Company	L812-**	Double	Electric	3	6.00	728	318	87%	17.1
Taylor Company	L820-**	Double	Electric	2	4.05	640	294	87%	17.7
Vulcan	HEG24E	Single	Electric	2	3.00	305	330	77%	6.8
Vulcan	HEG36E	Single	Electric	3	6.00	305	330	77%	6.8
Vulcan	HEG48E	Single	Electric	4	8.00	305	330	77%	6.8
Vulcan	HEG60E	Single	Electric	5	10.00	305	330	77%	6.8
Vulcan	HEG72E	Single	Electric	6	12.00	305	330	77%	6.8
Vulcan	RRE24E	Single	Electric	2	4.00	315	322	76%	7.4
Vulcan	RRE36E	Single	Electric	3	6.00	315	322	76%	7.4

Qualified Griddles

V-07-2025

Qualifying electric griddle models must have a tested heavy-load cooking energy efficiency of ≥ 70% and an idle energy rate of ≤ 355 Watts per ft² of cooking surface, utilizing ASTM Standard F1275 for single-sided griddles and F1605 for double-sided griddles.

NOTE: Program criteria are subject to change.

Company	Model Number	Single or Double Sided	Fuel Type	Nominal Width (ft)	Surface Area (ft²)	Preheat Energy (Wh/ft²)	Idle Energy Rate (W/ft²)	Energy Efficiency (%)	Production Capacity (lb/h/ft²)
AccuTemp	EAN2083E1800	Single	Electric	2	4.80	263	279	87%	4.7
AccuTemp	EGD****B3600	Single	Electric	3	5.55	576	271	86%	9.8
Vulcan	RRE48E	Single	Electric	4	8.00	315	322	76%	7.4
Wells	G-13	Single	Electric	2	2.75	420	242	75%	5.2
Wells	G-19	Single	Electric	3	4.36	420	242	75%	5.2
Wells	G-23	Single	Electric	3	6.00	420	242	75%	5.2
Wells	G-24	Single	Electric	4	7.91	420	242	75%	5.2
Wells	G-60	Single	Electric	6	11.29	420	242	75%	5.2
Wolf	WEG24E	Single	Electric	2	4.00	305	330	77%	6.8
Wolf	WEG36E	Single	Electric	3	6.00	305	330	77%	6.8
Wolf	WEG48E	Single	Electric	4	8.00	305	330	77%	6.8
Wolf	WEG60E	Single	Electric	5	10.00	305	330	77%	6.8
Wolf	WEG72E	Single	Electric	6	12.00	305	330	77%	6.8

Qualified Griddles

V-07-2025

Qualifying electric griddle models must have a tested heavy-load cooking energy efficiency of ≥ 70% and an idle energy rate of ≤ 355 Watts per ft² of cooking surface, utilizing ASTM Standard F1275 for single-sided griddles and F1605 for double-sided griddles.

NOTE: Program criteria are subject to change.

Company	Model Number	Single or Double Sided	Fuel Type	Nominal Width (ft)	Surface Area (ft²)	Preheat Energy (Wh/ft²)	Idle Energy Rate (W/ft²)	Energy Efficiency (%)	Production Capacity (lb/h/ft²)
AccuTemp	EAN2083E1800	Single	Electric	2	4.80	263	279	87%	4.7
AccuTemp	EGD****B3600	Single	Electric	3	5.55	576	271	86%	9.8

Qualified Steam Cookers

V-07-2025

Qualifying electric steam cooker models must have a tested heavy load potato cooking energy efficiency of ≥ 50% and meet the idle rate requirements in Table 2 utilizing ASTM Standard F1484.
NOTE: Program criteria are subject to change.

Company	Model Number	Steamer Type	Number of Cavities	Pan Capacity	Fuel Type	Preheat Energy (kWh)	Idle Energy Rate (kW)	Energy Efficiency (%)	Production Capacity (lb/h)	Water Use (gph)
AccuTemp	E3*****	Boilerless	1	3 pan	Electric	1.20	0.20	51%	81	1.5
AccuTemp	E3***** DBL	Boilerless	2	6 pan	Electric	1.20	0.20	51%	81	1.5
AccuTemp	E3***** TPL	Boilerless	3	9 pan	Electric	1.20	0.20	51%	81	1.5
AccuTemp	E6*****	Boilerless	1	6 pan	Electric	1.31	0.15	70%	164	4.2
AccuTemp	E6***** DBL	Boilerless	2	12 pan	Electric	1.31	0.15	70%	164	4.2
AccuTemp	S3*****	Boilerless	1	3 pan	Electric	1.60	0.20	60%	71	< 1.5
AccuTemp	S3***** DBL	Boilerless	2	6 pan	Electric	1.60	0.20	60%	71	< 1.5
AccuTemp	S6*****	Boilerless	1	6 pan	Electric	1.70	0.30	69%	97	< 1.5
AccuTemp	S6***** DBL	Boilerless	2	12 pan	Electric	1.70	0.30	69%	97	< 1.5
Cleveland	(2) 22CET33.1	Boilerless	2	6 pan	Electric	1.20	0.18	67%	56	2.3
Cleveland	(2) 22CET66.1	Boilerless	2	12 pan	Electric	1.33	0.49	62%	94	1.5
Cleveland	1SCE	Boilerless	1	5 pan	Electric	1.54	0.33	71%	84	< 2.5
Cleveland	22CCT6	Boilerless	1	6 pan	Electric	1.82	0.67	70%	112	3.6
Cleveland	22CET3.1	Boilerless	1	3 pan	Electric	1.20	0.18	67%	56	2.3
Cleveland	22CET6.1	Boilerless	1	6 pan	Electric	1.33	0.49	62%	94	1.5
Crown Food Service	EPX-3	Boilerless	1	3 pan	Electric	1.16	0.13	63%	66	< 3.0
Crown Food Service	EPX-5	Boilerless	1	5 pan	Electric	1.65	0.22	68%	97	< 3.0
Groen	(2)GSSP-BLE-3E*	Boilerless	2	8 pan	Electric	1.14	0.35	59%	57	1
Groen	(2)GSSP-BLE-5E*	Boilerless	2	12 pan	Electric	1.43	0.70	52%	96	16.5
Groen	(2)GSSP-CL-3E	Boilerless	2	6 pan	Electric	1.57	0.20	57%	57	0.7
Groen	(2)GSSP-CL-5E	Boilerless	2	10 pan	Electric	1.82	0.29	60%	85	0.8
Groen	GSSP-BLE-3E*	Boilerless	1	4 pan	Electric	1.14	0.35	59%	57	1
Groen	GSSP-BLE-5E*	Boilerless	1	6 pan	Electric	1.43	0.70	52%	96	16.5
Groen	GSSP-CL-3E	Boilerless	1	3 pan	Electric	1.57	0.20	57%	57	0.7
Groen	GSSP-CL-5E	Boilerless	1	5 pan	Electric	1.82	0.29	60%	85	0.8
Groen	VRC-3E	Boilerless	1	3 pan	Electric	2.42	0.11	68%	60	< 2.5
Groen	VRC-6E	Boilerless	1	6 pan	Electric	2.20	0.20	71%	98	< 2.5
Groen	XS-***.*	Boilerless	1	6 pan	Electric	1.60	0.16	74%	110	< 1.5
Hobart	HC24EO5	Boilerless	1	5 pan	Electric	2.18	0.38	65%	92	1.3
Market Forge	Altair II-10	Boilerless	2	10 pan	Electric	3.25	0.73	64%	175	1.6
Market Forge	Altair II-12	Boilerless	2	12 pan	Electric	3.54	0.80	62%	209	2.1
Market Forge	Altair II-4	Boilerless	1	4 pan	Electric	1.48	0.33	67%	71	0.6
Market Forge	Altair II-6	Boilerless	1	6 pan	Electric	1.77	0.40	62%	104	1
Market Forge	Altair II-8	Boilerless	2	8 pan	Electric	2.95	0.66	67%	142	1.2
Market Forge	ETP-10E	Steam Generator	2	10 pan	Electric	1.83	0.43	67%	159	5.9
Southbend	EZ18-3	Boilerless	1	3 pan	Electric	1.04	0.12	61%	65	0.6
Southbend	EZ18-5	Boilerless	1	5 pan	Electric	1.19	0.19	70%	117	1.1
Southbend	EZ24-3	Boilerless	1	3 pan	Electric	1.16	0.13	63%	66	< 3.0
Southbend	EZ24-5	Boilerless	1	5 pan	Electric	1.65	0.22	68%	97	< 3.0
Sterling	QCG E10-36-ES***	Steam Generator	2	10 pan	Electric	2.81	0.17	60%	245	5.2
Sterling	SP208-14-3-AF	Boilerless	1	6 pan	Electric	1.66	0.29	79%	132	0.9
Sterling	SP208-14-3-AF DBL	Boilerless	2	12 pan	Electric	1.66	0.29	79%	132	0.9
Sterling	SP208-14-3-MF	Boilerless	1	6 pan	Electric	1.66	0.29	79%	132	0.9
Sterling	SP208-14-3-MF DBL	Boilerless	2	12 pan	Electric	1.66	0.29	79%	132	0.9
Sterling	SP240-14-3-AF	Boilerless	1	6 pan	Electric	1.66	0.29	79%	132	0.9
Sterling	SP240-14-3-AF DBL	Boilerless	2	12 pan	Electric	1.66	0.29	79%	132	0.9
Sterling	SP240-14-3-MF	Boilerless	1	6 pan	Electric	1.66	0.29	79%	132	0.9
Sterling	SP240-14-3-MF DBL	Boilerless	2	12 pan	Electric	1.66	0.29	79%	132	0.9
Superior	C24EO5	Boilerless	1	5 pan	Electric	2.18	0.38	65%	92	1.3
Vulcan	C24EA3-LWE	Steam Generator	1	3 pan	Electric	0.99	0.14	62%	72	4.9
Vulcan	C24EA5-LWE	Steam Generator	1	5 pan	Electric	1.10	0.17	63%	112	6
Vulcan	C24EO3AF	Boilerless	1	3 pan	Electric	1.08	0.23	60%	65	1.6
Vulcan	C24EO5	Boilerless	1	5 pan	Electric	2.18	0.38	65%	92	1.3
Vulcan	C24EO5AF	Boilerless	1	5 pan	Electric	1.22	0.31	69%	106	1.2
Vulcan	C24ET10-LWE	Steam Generator	2	10 pan	Electric	2.07	0.31	67%	236	7.6
Vulcan	C24ET6-LWE	Steam Generator	2	6 pan	Electric	1.97	0.30	59%	142	4.7

Qualified Steam Cookers

V-07-2025

Qualifying electric steam cooker models must have a tested heavy load potato cooking energy efficiency of ≥ 50% and meet the idle rate requirements in Table 2 utilizing ASTM Standard F1484.
NOTE: Program criteria are subject to change.

Company	Model Number	Steamer Type	Number of Cavities	Pan Capacity	Fuel Type	Preheat Energy (kWh)	Idle Energy Rate (kW)	Energy Efficiency (%)	Production Capacity (lb/h)	Water Use (gph)
---------	--------------	--------------	--------------------	--------------	-----------	----------------------	-----------------------	-----------------------	----------------------------	-----------------

Table 1. Idle Rate Requirements for Commercial Steam Cookers

Steam Cooker Type	Pan Capacity	Idle Energy Rate
Electric	3-pan	≤ 0.4 kW
	4-pan	≤ 0.53 kW
	5-pan	≤ 0.67 kW
	6-pan and greater	≤ 0.8 kW

Qualified Hot Food Holding Cabinets

V-07-2025

Qualifying models must be listed in the California Energy Commission database. Qualifying full-size cabinets must have an idle energy rate ≤ 25 W/cu.ft. and qualifying half-size cabinets must have an idle energy rate ≤ 35 W/cu.ft. in accordance with ASTM F2140.

NOTE: Program criteria are subject to change.

Company	Model Number	Size	Cabinet Volume (cu. ft.)	Idle Energy Rate (Watts/cu. ft.)
Alto-Shaam	1000-BQ2/128	Full Size	28.2	13.5
Alto-Shaam	1000-BQ2/192	Full Size	44.0	11.9
Alto-Shaam	1000-BQ2/96	Full Size	22.0	15.1
Alto-Shaam	1000-S	1/2 Size	7.8	18.7
Alto-Shaam	1000-S/SR	1/2 Size	7.8	18.7
Alto-Shaam	1000-UP	Full Size	15.6	17.5
Alto-Shaam	1000-UP/P	Full Size	15.6	17.5
Alto-Shaam	1000-UP/SR	Full Size	15.6	17.5
Alto-Shaam	12.20*W	Full Size	19.4	10.9
Alto-Shaam	1200-S	1/2 Size	9.4	18.4
Alto-Shaam	1200-S/SR	1/2 Size	9.4	18.4
Alto-Shaam	1200-UP	Full Size	18.8	15.2
Alto-Shaam	1200-UP/SR	Full Size	18.8	15.2
Alto-Shaam	500-PH***	1/2 Size	4.9	30.3
Alto-Shaam	500-S***	1/2 Size	3.6	30.6
Alto-Shaam	750-S	1/2 Size	6.7	21.5
Alto-Shaam	750-S/SR	1/2 Size	6.7	21.5
Avantco	177HPESC1836	Full Size	18.0	15.6
Avantco	177HPESDC1836	Full Size	18.0	15.6
Avantco	177HPESDS1836	Full Size	18.0	14.5
Avantco	177HPESS1836	Full Size	18.0	14.5
Avantco	177HTESC1836	Full Size	18.0	15.6
Avantco	177HTESDC1836	Full Size	18.0	15.6
Avantco	177HTESDS1836	Full Size	18.0	14.3
Avantco	177HTESS1836	Full Size	18.0	14.3
Beverage-Air	PH1-1BHG-PT*****	Full Size	21.5	15.0
Beverage-Air	PH1-1HS*****	Full Size	20.2	13.2
Beverage-Air	PH1-1S*****	Full Size	20.2	13.2
Beverage-Air	PH2-1*****	Full Size	43.2	6.9
Beverage-Air	PH2-1BG*****	Full Size	46.5	7.6
Beverage-Air	PH2-1BG-PT*****	Full Size	46.5	10.5
Beverage-Air	PH11-1BG*****	Full Size	33.6	9.1
Cambro Manufacturing Co.	CMBH1826***	Full Size	17.3	12.3
Cambro Manufacturing Co.	CMBH1826L	1/2 Size	7.7	10.3
Cambro Manufacturing Co.	CMBH1826LC	1/2 Size	7.7	10.3
Cambro Manufacturing Co.	CMBH1826LF	1/2 Size	7.7	10.3
Cambro Manufacturing Co.	CMBH1826LTR	1/2 Size	7.7	10.3
Cambro Manufacturing Co.	PCU1000HC	1/2 Size	8.7	11.2
Cambro Manufacturing Co.	PCU1000HC3	1/2 Size	8.7	11.2
Cambro Manufacturing Co.	PCU1000HC3SP	1/2 Size	8.7	11.2
Cambro Manufacturing Co.	PCU1000HCSP	1/2 Size	8.7	11.2
Cambro Manufacturing Co.	PCU1000HH	1/2 Size	8.7	11.2
Cambro Manufacturing Co.	PCU1000HH3	1/2 Size	8.7	11.2

Qualified Hot Food Holding Cabinets

V-07-2025

Qualifying models must be listed in the California Energy Commission database. Qualifying full-size cabinets must have an idle energy rate ≤ 25 W/cu.ft. and qualifying half-size cabinets must have an idle energy rate ≤ 35 W/cu.ft. in accordance with ASTM F2140.

NOTE: Program criteria are subject to change.

Company	Model Number	Size	Cabinet Volume (cu. ft.)	Idle Energy Rate (Watts/cu. ft.)
Cambro Manufacturing Co.	PCU1000HH3SP	1/2 Size	8.7	11.2
Cambro Manufacturing Co.	PCU1000HHSP	1/2 Size	8.7	11.2
Cambro Manufacturing Co.	PCU1000HP	1/2 Size	8.7	11.2
Cambro Manufacturing Co.	PCU1000HP3	1/2 Size	8.7	11.2
Cambro Manufacturing Co.	PCU1000HP3SP	1/2 Size	8.7	11.2
Cambro Manufacturing Co.	PCU1000HPSP	1/2 Size	8.7	11.2
Cambro Manufacturing Co.	PCU2000HC	Full Size	16.4	8.0
Cambro Manufacturing Co.	PCU2000HC3	Full Size	16.4	8.0
Cambro Manufacturing Co.	PCU2000HC3SP	Full Size	16.4	8.0
Cambro Manufacturing Co.	PCU2000HCSP	Full Size	16.4	8.0
Cambro Manufacturing Co.	PCU2000HH	Full Size	16.4	8.0
Cambro Manufacturing Co.	PCU2000HH3	Full Size	16.4	8.0
Cambro Manufacturing Co.	PCU2000HH3SP	Full Size	16.4	8.0
Cambro Manufacturing Co.	PCU2000HHSP	Full Size	16.4	8.0
Cambro Manufacturing Co.	PCU2000HP	Full Size	16.4	8.0
Cambro Manufacturing Co.	PCU2000HP3	Full Size	16.4	8.0
Cambro Manufacturing Co.	PCU2000HP3SP	Full Size	16.4	8.0
Cambro Manufacturing Co.	PCU2000HPSP	Full Size	16.4	8.0
Cambro Manufacturing Co.	PCU800HC	1/2 Size	3.7	26.5
Cambro Manufacturing Co.	PCU800HC3	1/2 Size	3.7	26.5
Cambro Manufacturing Co.	PCU800HC3SP	1/2 Size	3.7	26.5
Cambro Manufacturing Co.	PCU800HCSP	1/2 Size	3.7	26.5
Cambro Manufacturing Co.	PCU800HH	1/2 Size	7.1	13.6
Cambro Manufacturing Co.	PCU800HH3	1/2 Size	7.1	13.6
Cambro Manufacturing Co.	PCU800HH3SP	1/2 Size	7.1	13.6
Cambro Manufacturing Co.	PCU800HHSP	1/2 Size	7.1	13.6
Cambro Manufacturing Co.	PCU800HP	1/2 Size	3.7	26.5

Qualified Hot Food Holding Cabinets

V-07-2025

Qualifying models must be listed in the California Energy Commission database. Qualifying full-size cabinets must have an idle energy rate ≤ 25 W/cu.ft. and qualifying half-size cabinets must have an idle energy rate ≤ 35 W/cu.ft. in accordance with ASTM F2140.

NOTE: Program criteria are subject to change.

Company	Model Number	Size	Cabinet Volume (cu. ft.)	Idle Energy Rate (Watts/cu. ft.)
Cambro Manufacturing Co.	PCU800HP3	1/2 Size	3.7	26.5
Cambro Manufacturing Co.	PCU800HP3SP	1/2 Size	3.7	26.5
Cambro Manufacturing Co.	PCU800HPSP	1/2 Size	3.7	26.5
Cambro Manufacturing Co.	PCUHH615	Full Size	18.9	10.7
Cambro Manufacturing Co.	PCUHP615	1/2 Size	9.3	11.5
Cambro Manufacturing Co.	PCUPH615	1/2 Size	9.3	11.5
Cambro Manufacturing Co.	UPCH1600	1/2 Size	12.1	8.5
Cambro Manufacturing Co.	UPCH400	1/2 Size	3.2	14.3
Cambro Manufacturing Co.	UPCH800	1/2 Size	6.0	15.2
Cambro Manufacturing Co.	UPCHT1600	1/2 Size	6.0	17.1
Cambro Manufacturing Co.	UPCHT800	1/2 Size	3.2	28.6
Cambro Manufacturing Co.	UPCHW400	1/2 Size	3.2	14.3
Continental	DL1W	Full Size	18.1	10.2
Continental	DL1W-HD	Full Size	18.1	10.2
Continental	DL1W-PT	Full Size	18.1	10.2
Continental	DL1W-PT-HD	Full Size	18.1	10.2
Continental	DL1W-SA	Full Size	18.1	10.2
Continental	DL1W-SA-HD	Full Size	18.1	10.2
Continental	DL1W-SA-PT	Full Size	18.1	10.2
Continental	DL1W-SA-PT-HD	Full Size	18.1	10.2
Continental	DL1W-SS	Full Size	18.1	10.2
Continental	DL1W-SS-HD	Full Size	18.1	10.2
Continental	DL1W-SS-PT	Full Size	18.1	10.2
Continental	DL1W-SS-PT-HD	Full Size	18.1	10.2
Continental	DL1WE	Full Size	20.4	6.4
Continental	DL1WE-HD	Full Size	20.4	6.4
Continental	DL1WE-PT	Full Size	20.4	6.4
Continental	DL1WE-PT-HD	Full Size	20.4	6.4
Continental	DL1WE-SA	Full Size	20.4	6.4
Continental	DL1WE-SA-HD	Full Size	20.4	6.4
Continental	DL1WE-SA-PT	Full Size	20.4	6.4
Continental	DL1WE-SA-PT-HD	Full Size	20.4	6.4
Continental	DL1WE-SS	Full Size	20.4	6.4
Continental	DL1WE-SS-HD	Full Size	20.4	6.4
Continental	DL1WE-SS-PT	Full Size	20.4	6.4
Continental	DL1WE-SS-PT-HD	Full Size	20.4	6.4
Continental	DL1WI	Full Size	29.8	10.6
Continental	DL1WI-SA	Full Size	29.8	10.6
Continental	DL1WI-SS	Full Size	29.8	10.6
Continental	DL2W	Full Size	41.7	6.7
Continental	DL2W-HD	Full Size	41.7	6.7
Continental	DL2W-PT	Full Size	41.7	6.7

Qualified Hot Food Holding Cabinets

V-07-2025

Qualifying models must be listed in the California Energy Commission database. Qualifying full-size cabinets must have an idle energy rate ≤ 25 W/cu.ft. and qualifying half-size cabinets must have an idle energy rate ≤ 35 W/cu.ft. in accordance with ASTM F2140.

NOTE: Program criteria are subject to change.

Company	Model Number	Size	Cabinet Volume (cu. ft.)	Idle Energy Rate (Watts/cu. ft.)
Continental	DL2W-PT-HD	Full Size	41.7	6.7
Continental	DL2W-SA	Full Size	41.7	6.7
Continental	DL2W-SA-HD	Full Size	41.7	6.7
Continental	DL2W-SA-PT	Full Size	41.7	6.7
Continental	DL2W-SA-PT-HD	Full Size	41.7	6.7
Continental	DL2W-SS	Full Size	41.7	6.7
Continental	DL2W-SS-HD	Full Size	41.7	6.7
Continental	DL2W-SS-PT	Full Size	41.7	6.7
Continental	DL2W-SS-PT-HD	Full Size	41.7	6.7
Continental	DL2WE	Full Size	46.1	7.7
Continental	DL2WE-HD	Full Size	46.1	7.7
Continental	DL2WE-PT	Full Size	46.1	7.7
Continental	DL2WE-PT-HD	Full Size	46.1	7.7
Continental	DL2WE-SA	Full Size	46.1	7.7
Continental	DL2WE-SA-HD	Full Size	46.1	7.7
Continental	DL2WE-SA-PT	Full Size	46.1	7.7
Continental	DL2WE-SA-PT-HD	Full Size	46.1	7.7
Continental	DL2WE-SS	Full Size	46.1	7.7
Continental	DL2WE-SS-HD	Full Size	46.1	7.7
Continental	DL2WE-SS-PT	Full Size	46.1	7.7
Continental	DL2WE-SS-PT-HD	Full Size	46.1	7.7
Continental	DL2WI	Full Size	64.5	6.5
Continental	DL2WI-RT	Full Size	64.5	6.5
Continental	DL2WI-SA	Full Size	64.5	6.5
Continental	DL2WI-SA-RT	Full Size	64.5	6.5
Continental	DL2WI-SS	Full Size	64.5	6.5
Continental	DL2WI-SS-RT	Full Size	64.5	6.5
Cres Cor	1200HH*****	1/2 Size	10.2	29.3
Cres Cor	500HH*****	1/2 Size	3.8	26.5
Cres Cor	EB120****	Full Size	34.1	23.4
Cres Cor	EB150A****	Full Size	40.9	19.6
Cres Cor	H137PSUA12D****	Full Size	21.1	19.0
Cres Cor	H137PWSUA12D****	Full Size	21.1	23.7
Cres Cor	H137S27D****	Full Size	21.1	23.7
Cres Cor	H137S96BC*****	Full Size	33.3	15.0
Cres Cor	H137SUA12D*	Full Size	21.5	12.4
Cres Cor	H137SUA12DSD*	Full Size	21.5	12.4
Cres Cor	H137SUA6D*	1/2 Size	10.4	21.1
Cres Cor	H137SUA6DSD*	1/2 Size	10.4	21.1
Cres Cor	H137SUA9D*	Full Size	15.6	15.8
Cres Cor	H137SUA9DSD*	Full Size	15.6	15.8
Cres Cor	H137UA12D***	Full Size	21.1	23.7
Cres Cor	H137WSUA12D15A*	Full Size	21.5	12.4
Cres Cor	H137WSUA12D15A***	Full Size	21.1	23.7
Cres Cor	H1381834D*	Full Size	21.5	12.4
Cres Cor	H1381834D***	Full Size	21.1	23.7
Cres Cor	H138PS1834D****	Full Size	21.1	19.0
Cres Cor	H138PWS1834D****	Full Size	21.1	23.7
Cres Cor	H138S1834D*	Full Size	21.5	12.4
Cres Cor	H138WS1834D***	Full Size	21.1	21.3
Cres Cor	H138WS1834D15A*	Full Size	21.5	12.4
Cres Cor	H3391813C****	1/2 Size	6.9	29.1
Cres Cor	H339214C*	1/2 Size	13.8	14.8
Cres Cor	H339SS12188C*	1/2 Size	6.9	15.4

Qualified Hot Food Holding Cabinets

V-07-2025

Qualifying models must be listed in the California Energy Commission database. Qualifying full-size cabinets must have an idle energy rate ≤ 25 W/cu.ft. and qualifying half-size cabinets must have an idle energy rate ≤ 35 W/cu.ft. in accordance with ASTM F2140.

NOTE: Program criteria are subject to change.

Company	Model Number	Size	Cabinet Volume (cu. ft.)	Idle Energy Rate (Watts/cu. ft.)
Cres Cor	H339SS1813C*	1/2 Size	6.9	15.4
Cres Cor	H339SS188C*	1/2 Size	6.9	15.4
Cres Cor	H339SSUA8C*	1/2 Size	8.2	14.4
Cres Cor	HCUA11*	Full Size	15.4	14.7
Delfield	GAH2-G	Full Size	44.0	6.9
Delfield	GAH2-S	Full Size	44.0	5.6
Delfield	GAHPT1-G	Full Size	21.0	10.9
Delfield	GAHPT1-GH	Full Size	21.0	11.2
Delfield	GAHR12-S	Full Size	77.0	5.6
FWE	E-600	Full Size	16.5	2.0
FWE	E-600-***	Full Size	16.5	2.0
FWE	E-720	Full Size	23.2	1.6
FWE	E-720-***	Full Size	23.2	1.6
FWE	E-720-XL	Full Size	29.0	0.5
FWE	E-720-XL-***	Full Size	29.0	0.5
FWE	E-960	Full Size	31.1	1.0
FWE	E-960-***	Full Size	31.1	1.0
FWE	HLC-16	1/2 Size	4.5	18.2
FWE	HLC-16-CHP	1/2 Size	4.5	18.2
FWE	HLC-16P	1/2 Size	4.5	18.2
FWE	HLC-16S	1/2 Size	4.5	18.2
FWE	HLC-1826-4	1/2 Size	5.5	19.1
FWE	HLC-1826-4-CHP	1/2 Size	5.5	19.1
FWE	HLC-1826-4-UC	1/2 Size	5.5	19.1
FWE	HLC-5 (120v, 500W)	1/2 Size	3.0	5.3
FWE	HLC-5-*** (120v, 500W)	1/2 Size	3.0	5.3
FWE	HLC-5S (120v, 500W)	1/2 Size	3.0	5.3
FWE	HLC-5S-*** (120v, 500W)	1/2 Size	3.0	5.3
FWE	HLC-8	1/2 Size	4.5	18.2
FWE	HLC-8-CHP	1/2 Size	4.5	18.2
FWE	HLC-8H-24	1/2 Size	4.5	18.2
FWE	HLC-8S	1/2 Size	4.5	18.2
FWE	HLC-SL-1826-5 (120v, 1000W)	1/2 Size	7.0	2.6
FWE	HLC-SL-1826-5-*** (120v, 500W)	1/2 Size	7.0	2.6
FWE	HLC-SL-1826-8 (120v, 1000W)	1/2 Size	8.9	1.7
FWE	HLC-SL-1826-8-*** (120v, 1000W)	1/2 Size	8.9	1.7
FWE	MT-1826-18	Full Size	26.8	9.6
FWE	MT-1826-18D	Full Size	26.8	9.6
FWE	MT-1826-18P	Full Size	26.8	9.6
FWE	MTU-12	Full Size	22.1	14.0
FWE	MTU-12-***	Full Size	22.1	14.0
FWE	MTU-4	1/2 Size	9.1	4.0
FWE	MTU-4-***	1/2 Size	9.1	4.0
FWE	P-60	1/2 Size	14.3	1.8
FWE	P-60-***	1/2 Size	14.3	1.8
FWE	PHTT-10****	Full Size	17.9	1.5
FWE	PHTT-12****	Full Size	23.1	1.0
FWE	PHTT-12*****	Full Size	23.1	1.0
FWE	PHTT-4	1/2 Size	8.3	4.0
FWE	PHTT-4-***	1/2 Size	8.3	4.0

Qualified Hot Food Holding Cabinets

V-07-2025

Qualifying models must be listed in the California Energy Commission database. Qualifying full-size cabinets must have an idle energy rate ≤ 25 W/cu.ft. and qualifying half-size cabinets must have an idle energy rate ≤ 35 W/cu.ft. in accordance with ASTM F2140.

NOTE: Program criteria are subject to change.

Company	Model Number	Size	Cabinet Volume (cu. ft.)	Idle Energy Rate (Watts/cu. ft.)
FWE	PHTT-4S	1/2 Size	8.3	4.0
FWE	PHTT-4S-***	1/2 Size	8.3	4.0
FWE	PHTT-6	1/2 Size	12.2	34.4
FWE	PHTT-6*****	1/2 Size	12.2	34.4
FWE	PHTT-6*****	1/2 Size	12.2	34.4
FWE	PHTT-6-***	1/2 Size	12.2	34.4
FWE	PHTT-6S	1/2 Size	12.2	34.4
FWE	PHTT-6S-***	1/2 Size	12.2	34.4
FWE	PHU-12	Full Size	23.1	11.4
FWE	PHU-12D	Full Size	21.1	10.3
FWE	PHU-12P	Full Size	21.1	10.3
FWE	PHU-4	1/2 Size	9.1	4.0
FWE	PHU-4-***	1/2 Size	9.1	4.0
FWE	PST-10	1/2 Size	6.6	3.6
FWE	PST-10-***	1/2 Size	6.6	3.6
FWE	TS-1633-36	Full Size	23.5	0.9
FWE	TS-1633-36-***	Full Size	23.5	0.9
FWE	TS-1826-18	Full Size	26.8	9.6
FWE	TS-1826-18D	Full Size	26.8	9.6
FWE	TS-1826-18P	Full Size	26.8	9.6
FWE	UHS-10	Full Size	19.2	0.8
FWE	UHS-10-***	Full Size	19.2	0.8
FWE	UHS-12	Full Size	19.9	14.9
FWE	UHS-12-***	Full Size	19.9	14.9
FWE	UHS-12-BE	Full Size	23.1	12.8
FWE	UHS-12-FUSD	Full Size	23.1	12.8
FWE	UHS-12-HRT	Full Size	23.1	12.8
FWE	UHS-4	1/2 Size	9.0	3.3
FWE	UHS-4-***	1/2 Size	9.0	3.3
FWE	UHST-13	Full Size	24.5	0.8
FWE	UHST-13-***	Full Size	24.5	0.8
FWE	UHST-GN-6480-BQ	Full Size	24.0	11.3
Hatco	FSHC-17W1	Full Size	23.1	12.8
Hatco	FSHC-17W2	Full Size	21.1	10.4
Hatco	FSHC-17WD	Full Size	21.1	10.4
Hatco Corporation	FSHC-5W1-EE	1/2 Size	7.3	18.8
Hatco Corporation	FSHC-7W1-EE	1/2 Size	8.3	21.6
Hatco Corporation	FSHC-7W2-EE	1/2 Size	8.7	19.8
Hoshizaki	HC1A-FGE	Full Size	23.4	7.5
Hoshizaki	HC1A-FGE-FGE	Full Size	24.5	10.1
Hoshizaki	HC1A-FS	Full Size	23.4	6.1
Hoshizaki	HC1A-FS-FS	Full Size	24.5	6.6
Hoshizaki	HC1A-HGE	Full Size	23.4	7.5
Hoshizaki	HC1A-HGE-HGE	Full Size	24.5	10.1
Hoshizaki	HC1A-HS	Full Size	23.4	6.1
Hoshizaki	HC1A-HS-HS	Full Size	24.5	6.6
Hoshizaki	HC2A-FGE	Full Size	51.7	6.3
Hoshizaki	HC2A-FGE-FGE	Full Size	53.7	7.2
Hoshizaki	HC2A-FS	Full Size	51.7	4.6
Hoshizaki	HC2A-FS-FS	Full Size	53.7	5.7
Hoshizaki	HC2A-HGE	Full Size	51.7	6.3
Hoshizaki	HC2A-HGE-HGE	Full Size	53.7	7.2
Hoshizaki	HC2A-HS	Full Size	51.7	4.6
Hoshizaki	HC2A-HS-HS	Full Size	53.7	5.7

Qualified Hot Food Holding Cabinets

V-07-2025

Qualifying models must be listed in the California Energy Commission database. Qualifying full-size cabinets must have an idle energy rate ≤ 25 W/cu.ft. and qualifying half-size cabinets must have an idle energy rate ≤ 35 W/cu.ft. in accordance with ASTM F2140.

NOTE: Program criteria are subject to change.

Company	Model Number	Size	Cabinet Volume (cu. ft.)	Idle Energy Rate (Watts/cu. ft.)
Metro	C565-NFC-**	1/2 Size	12.0	29.0
Metro	C565-NFS-**	1/2 Size	12.0	29.0
Metro	C565-SF*.*****	1/2 Size	12.7	32.9
Metro	C565-SFC-**	1/2 Size	12.0	29.0
Metro	C565-SFS-**	1/2 Size	12.0	29.0
Metro	C565L-NFC-**	1/2 Size	12.0	29.0
Metro	C565L-NFS-**	1/2 Size	12.0	29.0
Metro	C565L-SF*.*****	1/2 Size	12.7	32.9
Metro	C565L-SFC-**	1/2 Size	12.0	29.0
Metro	C565L-SFS-**	1/2 Size	12.0	29.0
Metro	C567-NF*.*****	Full Size	20.3	22.6
Metro	C567-NFC-**	Full Size	19.2	18.1
Metro	C567-NFS-**	Full Size	19.2	18.1
Metro	C567-SF*.*****	Full Size	20.3	20.6
Metro	C567-SFC-**	Full Size	19.2	18.1
Metro	C567-SFS-**	Full Size	19.2	18.1
Metro	C567L-NF*.*****	Full Size	20.3	22.6
Metro	C567L-NFC-**	Full Size	19.2	18.1
Metro	C567L-NFS-**	Full Size	19.2	18.1
Metro	C567L-SF*.*****	Full Size	20.3	20.6
Metro	C567L-SFC-**	Full Size	19.2	18.1
Metro	C567L-SFS-**	Full Size	19.2	18.1
Metro	C569-N**.*****	Full Size	25.4	21.9
Metro	C569-NDC-**	Full Size	24.0	21.7
Metro	C569-NDS-**	Full Size	24.0	20.1
Metro	C569-NFC-**	Full Size	24.0	21.7
Metro	C569-NFS-**	Full Size	24.0	20.1
Metro	C569-S**.*****	Full Size	25.4	21.9
Metro	C569-SDC-**	Full Size	24.0	17.4
Metro	C569-SDS-**	Full Size	24.0	15.5
Metro	C569-SFC-**	Full Size	24.0	17.4
Metro	C569-SFS-**	Full Size	24.0	15.5
Metro	C569L-N**.*****	Full Size	25.4	21.9
Metro	C569L-NDC-**	Full Size	24.0	22.8
Metro	C569L-NDS-**	Full Size	24.0	22.3
Metro	C569L-NFC-**	Full Size	24.0	22.8
Metro	C569L-NFS-**	Full Size	24.0	22.3
Metro	C569L-S**.*****	Full Size	25.4	21.9
Metro	C569L-SDC-**	Full Size	24.0	14.8
Metro	C569L-SDS-**	Full Size	24.0	14.8
Metro	C569L-SFC-**	Full Size	24.0	14.8
Metro	C569L-SFS-**	Full Size	24.0	14.8
Metro	C585-NF*.*****	1/2 Size	12.7	33.8
Metro	C585-NFC-**	1/2 Size	12.0	32.9
Metro	C585-NFS-**	1/2 Size	12.0	32.9
Metro	C585-SF*.*****	1/2 Size	12.7	31.6
Metro	C585-SFC-**	1/2 Size	12.0	24.3
Metro	C585-SFS-**	1/2 Size	12.0	22.5
Metro	C585L-NF*.*****	1/2 Size	12.7	33.8
Metro	C585L-NFC-**	1/2 Size	12.0	32.9
Metro	C585L-NFS-**	1/2 Size	12.0	32.9
Metro	C585L-SF*.*****	1/2 Size	12.7	31.6
Metro	C585L-SFC-**	1/2 Size	12.0	24.3
Metro	C585L-SFS-**	1/2 Size	12.0	22.5

Qualified Hot Food Holding Cabinets

V-07-2025

Qualifying models must be listed in the California Energy Commission database. Qualifying full-size cabinets must have an idle energy rate ≤ 25 W/cu.ft. and qualifying half-size cabinets must have an idle energy rate ≤ 35 W/cu.ft. in accordance with ASTM F2140.

NOTE: Program criteria are subject to change.

Company	Model Number	Size	Cabinet Volume (cu. ft.)	Idle Energy Rate (Watts/cu. ft.)
Metro	C587-NF*.*****	Full Size	20.3	21.1
Metro	C587-NFC.**	Full Size	19.2	20.6
Metro	C587-NFS.**	Full Size	19.2	20.6
Metro	C587-SF*.*****	Full Size	20.3	19.8
Metro	C587-SFC.**	Full Size	19.2	15.2
Metro	C587-SFS.**	Full Size	19.2	14.1
Metro	C587L-NF*.*****	Full Size	20.3	21.1
Metro	C587L-NFC.**	Full Size	19.2	20.6
Metro	C587L-NFS.**	Full Size	19.2	20.6
Metro	C587L-SF*.*****	Full Size	20.3	19.8
Metro	C587L-SFC.**	Full Size	19.2	15.2
Metro	C587L-SFS.**	Full Size	19.2	14.1
Metro	C589-N**.*****	Full Size	25.4	24.8
Metro	C589-NDC.**	Full Size	24.0	23.9
Metro	C589-NDS.**	Full Size	24.0	22.0
Metro	C589-NFC.**	Full Size	24.0	23.9
Metro	C589-NFS.**	Full Size	24.0	22.0
Metro	C589-S**.*****	Full Size	25.4	22.8
Metro	C589-SDC.**	Full Size	24.0	18.3
Metro	C589-SDS.**	Full Size	24.0	16.2
Metro	C589-SFC.**	Full Size	24.0	18.3
Metro	C589-SFS.**	Full Size	24.0	16.2
Metro	C589L-N**.*****	Full Size	25.4	24.8
Metro	C589L-NDC.**	Full Size	24.0	23.9
Metro	C589L-NDS.**	Full Size	24.0	22.0
Metro	C589L-NFC.**	Full Size	24.0	23.9
Metro	C589L-NFS.**	Full Size	24.0	22.0
Metro	C589L-S**.*****	Full Size	25.4	21.7
Metro	C589L-SDC.**	Full Size	24.0	18.3
Metro	C589L-SDS.**	Full Size	24.0	16.2
Metro	C589L-SFC.**	Full Size	24.0	18.3
Metro	C589L-SFS.**	Full Size	24.0	16.2
Metro	C595-NF*.*****	1/2 Size	12.7	33.8
Metro	C595-NFC.**	1/2 Size	12.0	32.9
Metro	C595-NFS.**	1/2 Size	12.0	32.9
Metro	C595-SF*.*****	1/2 Size	12.7	31.6
Metro	C595-SFC.**	1/2 Size	12.0	24.3
Metro	C595-SFS.**	1/2 Size	12.0	22.5
Metro	C595L-NF*.*****	1/2 Size	12.7	33.8
Metro	C595L-NFC.**	1/2 Size	12.0	32.9
Metro	C595L-NFS.**	1/2 Size	12.0	32.9
Metro	C595L-SF*.*****	1/2 Size	12.7	31.6
Metro	C595L-SFC.**	1/2 Size	12.0	24.3
Metro	C595L-SFS.**	1/2 Size	12.0	22.5
Metro	C597-NF*.*****	Full Size	20.3	21.1
Metro	C597-NFC.**	Full Size	19.2	20.6
Metro	C597-NFS.**	Full Size	19.2	20.6
Metro	C597-SF*.*****	Full Size	20.3	19.8
Metro	C597-SFC.**	Full Size	19.2	15.2
Metro	C597-SFS.**	Full Size	19.2	14.1
Metro	C597L-NF*.*****	Full Size	20.3	21.1
Metro	C597L-NFC.**	Full Size	19.2	20.6
Metro	C597L-NFS.**	Full Size	19.2	20.6
Metro	C597L-SF*.*****	Full Size	20.3	19.8

Qualified Hot Food Holding Cabinets

V-07-2025

Qualifying models must be listed in the California Energy Commission database. Qualifying full-size cabinets must have an idle energy rate ≤ 25 W/cu.ft. and qualifying half-size cabinets must have an idle energy rate ≤ 35 W/cu.ft. in accordance with ASTM F2140.

NOTE: Program criteria are subject to change.

Company	Model Number	Size	Cabinet Volume (cu. ft.)	Idle Energy Rate (Watts/cu. ft.)
Metro	C597L-SFC-**	Full Size	19.2	15.2
Metro	C597L-SFS-**	Full Size	19.2	14.1
Metro	C599-N**-*****	Full Size	25.4	24.8
Metro	C599-NDC-**	Full Size	24.0	23.9
Metro	C599-NDS-**	Full Size	24.0	22.0
Metro	C599-NFC-**	Full Size	24.0	23.9
Metro	C599-NFS-**	Full Size	24.0	22.0
Metro	C599-S**-*****	Full Size	25.4	22.8
Metro	C599-SDC-**	Full Size	24.0	19.0
Metro	C599-SDS-**	Full Size	24.0	18.2
Metro	C599-SFC-**	Full Size	24.0	19.0
Metro	C599-SFS-**	Full Size	24.0	18.2
Metro	C599L-N**-*****	Full Size	25.4	24.8
Metro	C599L-NDC-**	Full Size	24.0	23.9
Metro	C599L-NDS-**	Full Size	24.0	22.0
Metro	C599L-NFC-**	Full Size	24.0	23.9
Metro	C599L-NFS-**	Full Size	24.0	22.0
Metro	C599L-S**-*****	Full Size	25.4	21.7
Metro	C599L-SDC-**	Full Size	24.0	19.0
Metro	C599L-SDS-**	Full Size	24.0	18.2
Metro	C599L-SFC-**	Full Size	24.0	19.0
Metro	C599L-SFS-**	Full Size	24.0	18.2
Metro	C5T5-AS**	1/2 Size	12.2	13.5
Metro	C5T5-DS**	1/2 Size	12.2	13.5
Metro	C5T8-AS**	Full Size	18.4	9.2
Metro	C5T8-DS**	Full Size	18.4	9.2
Metro	C5T9-AS**	Full Size	21.4	7.2
Metro	C5T9-DS**	Full Size	21.4	7.2
Metro	C5T9D-AS**	Full Size	21.4	7.2
Metro	C5T9D-DS**	Full Size	21.4	7.2
Metro	MBQ-120	Full Size	29.8	17.6
Metro	MBQ-120-QH	Full Size	29.8	17.6
Metro	MBQ-120D	Full Size	37.2	14.0
Metro	MBQ-120D-QH	Full Size	37.2	14.0
Metro	MBQ-144	Full Size	35.2	15.6
Metro	MBQ-144-QH	Full Size	35.2	15.6
Metro	MBQ-150D	Full Size	44.7	14.6
Metro	MBQ-150D-QH	Full Size	44.7	14.6
Metro	MBQ-180	Full Size	44.0	12.5
Metro	MBQ-180-QH	Full Size	44.0	12.5
Metro	MBQ-180D	Full Size	52.7	14.6
Metro	MBQ-180D-QH	Full Size	52.7	14.6
Metro	MBQ-200D	Full Size	57.6	13.8
Metro	MBQ-200D-QH	Full Size	57.6	13.8
Metro	MBQ-72	Full Size	18.6	20.2
Metro	MBQ-72-QH	Full Size	18.6	20.2
Metro	MBQ-90	Full Size	22.4	20.1
Metro	MBQ-90-QH	Full Size	22.4	20.1
Metro	TC90B	1/2 Size	8.6	22.6
Metro	TC90BB	1/2 Size	8.6	22.6
Moffat	H8D-FS-UC	1/2 Size	8.3	29.6
Royalton Foodservice Equipment Co.	SSRHHC-1000-C2	1/2 Size	8.3	28.1

Qualified Hot Food Holding Cabinets

V-07-2025

Qualifying models must be listed in the California Energy Commission database. Qualifying full-size cabinets must have an idle energy rate ≤ 25 W/cu.ft. and qualifying half-size cabinets must have an idle energy rate ≤ 35 W/cu.ft. in accordance with ASTM F2140.

NOTE: Program criteria are subject to change.

Company	Model Number	Size	Cabinet Volume (cu. ft.)	Idle Energy Rate (Watts/cu. ft.)
Royalton Foodservice Equipment Co.	SSRHHC-1000-C4	Full Size	19.3	18.7
Royalton Foodservice Equipment Co.	SSRHHC-2000-C4	Full Size	19.3	18.7
Royalton Foodservice Equipment Co.	SSRHHC-2000-C4US	Full Size	20.7	18.1
Royalton Foodservice Equipment Co.	SSRHHR-1000-C1R-SWH	1/2 Size	6.4	20.4
Royalton Foodservice Equipment Co.	SSRHHR-2000-C4R-SWH	Full Size	19.5	16.2
Royalton Foodservice Equipment Co.	SSRSH-1209	1/2 Size	4.8	28.4
Royalton Foodservice Equipment Co.	SSRSH-1209-SWH	1/2 Size	4.8	28.4
Royalton Foodservice Equipment Co.	SSRSH-1809	1/2 Size	7.9	19.4
Royalton Foodservice Equipment Co.	SSRSH-1809-SWH	1/2 Size	7.9	19.4
Royalton Foodservice Equipment Co.	SSRSH-2106	1/2 Size	10.2	18.2
Royalton Foodservice Equipment Co.	SSRSH-2106-SWH	1/2 Size	10.2	18.2
Traulsen	AHF132W-FHG	Full Size	24.0	12.6
Traulsen	AHF132W-FHS	Full Size	24.0	12.6
Traulsen	AHF132W-HHG	Full Size	24.0	12.6
Traulsen	AHF132W-HHS	Full Size	24.0	12.6
Traulsen	AHF132WP-FHS	Full Size	26.0	11.8
Traulsen	AHF132WP-HHS	Full Size	26.0	11.8
Traulsen	AHF232W-FHS	Full Size	52.0	7.7
Traulsen	AHF232W-HHS	Full Size	52.0	7.7
Traulsen	AHF232WP-FHS	Full Size	55.0	7.5
Traulsen	AHF232WP-HHS	Full Size	55.0	7.5
Traulsen	AIH132H-FHS	Full Size	38.0	9.2
Traulsen	AIH132L-FHS	Full Size	36.0	9.4
Traulsen	AIH132LP-FHS	Full Size	38.0	9.2
Traulsen	AIH232L-FHS	Full Size	74.0	6.5
Traulsen	AIH232LP-FHS	Full Size	80.0	6.3
Traulsen	G14300	Full Size	24.0	12.6
Traulsen	G14301	Full Size	24.0	12.6
Traulsen	G14302P	Full Size	26.0	11.8
Traulsen	G14303P	Full Size	26.0	11.8
Traulsen	G14304P	Full Size	26.0	11.8
Traulsen	G14305P	Full Size	26.0	11.8
Traulsen	G14310	Full Size	24.0	12.6
Traulsen	G14311	Full Size	24.0	12.6
Traulsen	G14312P	Full Size	26.0	11.8
Traulsen	G14313P	Full Size	26.0	11.8
Traulsen	G14314P	Full Size	26.0	11.8
Traulsen	G14315P	Full Size	26.0	11.8
Traulsen	G24300	Full Size	44.0	8.4
Traulsen	G24302	Full Size	44.0	8.4
Traulsen	G24303	Full Size	44.0	8.4
Traulsen	G24304P	Full Size	47.0	8.1
Traulsen	G24305P	Full Size	47.0	8.1

Qualified Hot Food Holding Cabinets

V-07-2025

Qualifying models must be listed in the California Energy Commission database. Qualifying full-size cabinets must have an idle energy rate ≤ 25 W/cu.ft. and qualifying half-size cabinets must have an idle energy rate ≤ 35 W/cu.ft. in accordance with ASTM F2140.

NOTE: Program criteria are subject to change.

Company	Model Number	Size	Cabinet Volume (cu. ft.)	Idle Energy Rate (Watts/cu. ft.)
Traulsen	G24306P	Full Size	47.0	8.1
Traulsen	G24307P	Full Size	47.0	8.1
Traulsen	G24310	Full Size	44.0	8.4
Traulsen	G24312	Full Size	44.0	8.4
Traulsen	G24312P	Full Size	47.0	8.1
Traulsen	G24313	Full Size	44.0	8.4
Traulsen	G24314P	Full Size	47.0	8.1
Traulsen	G24315P	Full Size	47.0	8.1
Traulsen	G24316P	Full Size	47.0	8.1
Traulsen	G24317	Full Size	44.0	8.4
Traulsen	G24317P	Full Size	47.0	8.1
Traulsen	RHF132W-FHG	Full Size	24.0	12.6
Traulsen	RHF132W-FHS	Full Size	24.0	12.6
Traulsen	RHF132W-HHG	Full Size	24.0	12.6
Traulsen	RHF132W-HHS	Full Size	24.0	12.6
Traulsen	RHF132WP-FHS	Full Size	26.0	11.8
Traulsen	RHF132WP-HHS	Full Size	26.0	11.8
Traulsen	RHF232W-FHS	Full Size	52.0	7.7
Traulsen	RHF232W-HHS	Full Size	52.0	7.7
Traulsen	RHF232WP-FHS	Full Size	55.0	7.5
Traulsen	RHF232WP-HHS	Full Size	55.0	7.5
Traulsen	RIH132H-FHS	Full Size	38.0	9.2
Traulsen	RIH132L-FHS	Full Size	36.0	9.4
Traulsen	RIH132LP-FHS	Full Size	38.0	9.2
Traulsen	RIH232L-FHS	Full Size	74.0	6.5
Traulsen	RIH232LP-FHS	Full Size	80.0	6.3
Victory	HIS-1D-1****C*****	Full Size	33.6	9.1
Victory	HISA-1D-1****C*****	Full Size	33.6	9.1
Victory	HS-1D-1*****	Full Size	20.2	13.2
Victory	HS-1D-1-PT***HD*G*****	Full Size	21.5	15.0
Victory	HS-2D-1-*****	Full Size	43.2	6.9
Victory	HS-2D-1-G*****	Full Size	46.5	7.6
Victory	HS-2D-1-PT****G*****	Full Size	46.5	10.5
Victory	HSA-1D-1*****	Full Size	20.2	13.2
Victory	HSA-1D-1-PT***HD*G*****	Full Size	21.5	15.0
Victory	HSA-2D-1-*****	Full Size	43.2	6.9
Victory	HSA-2D-1-G*****	Full Size	46.5	7.6
Victory	HSA-2D-1-PT****G*****	Full Size	46.5	10.5
Vulcan	VBP13**-****	Full Size	17.9	11.4
Vulcan	VBP15**-****	Full Size	20.0	13.1
Vulcan	VBP18**-****	Full Size	22.0	11.6
Vulcan	VBP5**-****	1/2 Size	7.3	20.4
Vulcan	VBP7**-****	1/2 Size	10.2	18.6
Vulcan	VHFA9-****	1/2 Size	12.7	34.1

Qualified Glass Door Refrigerators

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
ACCUCOLD	ACRT1151*	Reach-in	9.36	1.30
AHT	MALTA 185 NAM-R	Reach-in	27.46	1.47
AHT	MONTREAL XL EC PUSH 210 (U) NAM - R	Reach-in	42.73	2.37
AHT	PARIS 210 NAM-R	Reach-in	32.25	1.81
AHT	SYDNEY XL 210 NAM-R	Reach-in	40.98	2.11
AHT	SYDNEY XL 250 NAM-R	Reach-in	49.88	1.52
AHT	VENTO GD 250 L8 LAPS	Reach-in	119.42	6.20
AHT	VENTO GD 250 L8 LTG	Reach-in	119.42	6.20
AHT	VENTO GD 250 L8 LTG SLED	Reach-in	119.42	6.20
AHT	VENTO GD 375 L8 LAPS	Reach-in	179.09	13.04
AHT	VENTO GD 375 L8 LTG	Reach-in	179.09	13.04
AHT	VENTO GD 375 L8 LTG SLED	Reach-in	179.09	13.04
AHT	VENTO HYB GD 250 L8 LAPS	Reach-in	119.42	10.17
AHT	VENTO HYB GD 250 L8 LTG	Reach-in	119.42	10.17
AHT	VENTO HYB GD 250 L8 LTG SLED	Reach-in	119.42	10.17
AHT	VENTO HYB GD 375 L8 LAPS	Reach-in	179.09	17.64
AHT	VENTO HYB GD 375 L8 LTG	Reach-in	179.09	17.64
AHT	VENTO HYB GD 375 L8 LTG SLED	Reach-in	179.09	17.64
Avantco	178A49RGHC	Reach-in	41.30	3.35
Avantco	178GDC23LH*	Undercounter	23.00	2.20
Avantco	178Z1RGHC	Reach-in	21.26	2.09
Avantco	178Z2RGHC	Reach-in	42.59	3.17
Avanti	CBC113G0WG	Reach-in	11.30	1.38
Avanti	CF35T0WG-R	Reach-in	3.51	0.30
Avanti	CFC83Q0WG-R	Reach-in	9.48	0.50
AvaValley	342BDR84SZ	Milk or Beverage Cabinet	4.90	0.34
AvaValley	342BRC52SZ	Milk or Beverage Cabinet	2.20	0.26
AvaValley	342BRC78SZ	Milk or Beverage Cabinet	3.04	0.35
Beverage-Air	BB58HC-1-G*****	Other	21.86	1.99
Beverage-Air	CT96HC-1-*****	Reach-in	5.90	0.91
Beverage-Air	HBR12HC-1*G*****	Reach-in	12.06	1.47
Beverage-Air	HBR19HC-1*G*****	Reach-in	17.87	1.98
Beverage-Air	HBR23HC-1**G*****	Reach-in	23.10	2.04
Beverage-Air	HBR27HC-1**G*****	Reach-in	25.88	2.06
Beverage-Air	HBR35HC-1*G*****	Reach-in	35.40	2.60
Beverage-Air	HBR49HC-1**G****	Reach-in	46.15	3.21
Beverage-Air	HBR49HC-1**G*****	Reach-in	46.15	3.21
Beverage-Air	HBR72HC-1**G*****	Reach-in	68.93	3.92
Beverage-Air	HR1HC-1G*****	Reach-in	21.66	2.15
Beverage-Air	HR1HC-1HG*****	Reach-in	21.66	2.15
Beverage-Air	HRIWHC-1G*****	Reach-in	30.76	2.33
Beverage-Air	HRIWHC-1HG*****	Reach-in	30.76	2.33
Beverage-Air	HR2HC-1G*****	Reach-in	46.88	3.38
Beverage-Air	HR2HC-1HG*****	Reach-in	46.88	3.38
Beverage-Air	HR3HC-1G*****	Reach-in	71.52	3.77
Beverage-Air	HR3HC-1HG*****	Reach-in	71.52	3.77
Beverage-Air	HRP1HC-1G*****	Reach-in	21.66	2.15
Beverage-Air	HRP1HC-1HG*****	Reach-in	21.66	2.15
Beverage-Air	HRP1WHC-1G*****	Reach-in	30.76	2.33

Qualified Glass Door Refrigerators

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
Beverage-Air	HRP1WHC-1HG*****	Reach-in	30.76	2.33
Beverage-Air	HRP2HC-1G*****	Reach-in	46.88	3.38
Beverage-Air	HRP2HC-1HG*****	Reach-in	46.88	3.38
Beverage-Air	HRP3HC-1G*****	Reach-in	71.52	3.77
Beverage-Air	HRP3HC-1HG*****	Reach-in	71.52	3.77
Beverage-Air	HRPS1HC-1G*****	Reach-in	21.66	2.15
Beverage-Air	HRPS1HC-1HG*****	Reach-in	21.66	2.15
Beverage-Air	HRPS1WHC-1G*****	Reach-in	30.76	2.33
Beverage-Air	HRPS1WHC-1HG*****	Reach-in	30.76	2.33
Beverage-Air	HRPS2HC-1G*****	Reach-in	46.88	3.38
Beverage-Air	HRPS2HC-1HG*****	Reach-in	46.88	3.38
Beverage-Air	HRPS3HC-1G*****	Reach-in	71.52	3.77
Beverage-Air	HRPS3HC-1HG*****	Reach-in	71.52	3.77
Beverage-Air	HRS1HC-1G*****	Reach-in	21.66	2.15
Beverage-Air	HRS1HC-1HG*****	Reach-in	21.66	2.15
Beverage-Air	HRS2HC-1G*****	Reach-in	46.88	3.38
Beverage-Air	HRS2HC-1HG*****	Reach-in	46.88	3.38
Beverage-Air	HRS3HC-1G*****	Reach-in	71.52	3.77
Beverage-Air	HRS3HC-1HG*****	Reach-in	71.52	3.77
Beverage-Air	LV10HC-1-*****	Reach-in	9.60	1.31
Beverage-Air	LV12HC-1*****	Reach-in	12.06	1.47
Beverage-Air	LV17HC-1-***	Reach-in	18.49	1.84
Beverage-Air	LV19HC-1*****	Reach-in	17.87	1.98
Beverage-Air	LV23HC-1*****	Reach-in	23.10	2.18
Beverage-Air	LV27HC-1*****	Reach-in	25.88	2.06
Beverage-Air	LV35HC-1*****	Reach-in	35.40	2.60
Beverage-Air	LV45HC-1*****	Reach-in	44.00	3.38
Beverage-Air	LV49HC-1*****	Reach-in	46.15	3.21
Beverage-Air	LV66HC-1*****	Reach-in	64.40	4.42
Beverage-Air	LV72HC-1*****	Reach-in	68.93	3.92
Beverage-Air	MMR12HC*****	Reach-in	12.06	1.57
Beverage-Air	MMR19HC-1*****	Reach-in	17.87	1.98
Beverage-Air	MMR23HC-1*****	Reach-in	23.10	2.04
Beverage-Air	MMR27HC-1*****	Reach-in	25.88	2.05
Beverage-Air	MMR35HC-1*****	Reach-in	35.40	2.60
Beverage-Air	MMR45HC-1*****	Reach-in	44.00	3.38
Beverage-Air	MMR49HC-1*****	Reach-in	46.15	3.21
Beverage-Air	MMR66HC-1*****	Reach-in	64.40	4.42
Beverage-Air	MMR72HC-1*****	Reach-in	68.93	3.92
Beverage-Air	MT08-1*****	Reach-in	7.69	1.15
Beverage-Air	MT08-1[*]	Reach-in	7.69	1.15
Beverage-Air	MT10-1*****	Reach-in	9.43	1.24
Beverage-Air	MT10-1[*]	Reach-in	9.43	1.24
Beverage-Air	MT12-1*****	Reach-in	11.50	1.46
Beverage-Air	MT12-1[*]	Reach-in	11.50	1.46
Beverage-Air	MT21-1*****	Reach-in	16.80	1.92
Beverage-Air	MT23-1*****	Reach-in	19.20	1.81
Beverage-Air	MT23-1[*]	Reach-in	19.20	1.80
Beverage-Air	MT34-1	Reach-in	26.12	2.26
Beverage-Air	MT34-1*****	Reach-in	26.12	2.25
Beverage-Air	MT41-48-1-SD*****	Reach-in	13.44	1.62
Beverage-Air	MT41-54-1-SD*****	Reach-in	17.10	1.70
Beverage-Air	MT49-1*****	Reach-in	37.42	3.12
Beverage-Air	MT49-1-SD*****	Reach-in	39.03	2.94
Beverage-Air	MT49-1-SD[*]	Reach-in	39.03	3.00
Beverage-Air	MT49-1[*]	Reach-in	37.42	3.12
Beverage-Air	MT53-1*****	Reach-in	41.66	3.24
Beverage-Air	MT53-1-SD[*]	Reach-in	41.66	3.31

Qualified Glass Door Refrigerators

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
Beverage-Air	MT53-1[*]	Reach-in	41.66	3.29
Beverage-Air	MT72-1B*****	Reach-in	66.30	5.06
Beverage-Air	MT72-1W*****	Reach-in	66.30	5.06
Beverage-Air	RB19HC-1*C*****	Reach-in	17.87	1.98
Beverage-Air	RB23HC-1*C*****	Reach-in	23.10	2.18
Beverage-Air	RB27HC-1*C*****	Reach-in	25.88	2.06
Beverage-Air	RB49HC-1*C*****	Reach-in	46.15	3.65
Beverage-Air	RB72HC-1*C*****	Reach-in	68.93	5.49
Beverage-Air	UCR32AHC-25*****	Undercounter	7.22	1.06
Beverage-Air	UCR60AHC-25*****	Undercounter	14.75	1.70
Beverage-Air	WTR32AHC-25*****	Work-Top Table	7.22	1.06
Beverage-Air	WTR60AHC-25*****	Work-Top Table	14.75	1.70
Continental Refrigerator	1RENGD	Reach-in	21.40	2.06
Continental Refrigerator	1RENGDHD	Reach-in	21.20	2.13
Continental Refrigerator	1RENGDPT	Pass-Through	24.50	2.27
Continental Refrigerator	1RENGDPTHD	Pass-Through	24.00	2.32
Continental Refrigerator	1RESNGD	Reach-in	18.80	1.84
Continental Refrigerator	1RESNGDHD	Reach-in	18.90	2.01
Continental Refrigerator	1RNGD	Reach-in	18.97	1.84
Continental Refrigerator	1RNGDHD	Reach-in	18.60	1.66
Continental Refrigerator	1RNGDPT	Pass-Through	22.10	2.22
Continental Refrigerator	1RSENGD	Reach-in	13.80	1.55
Continental Refrigerator	1RSENGDHD	Reach-in	13.60	1.58
Continental Refrigerator	1RSENGD	Reach-in	11.30	1.42
Continental Refrigerator	1RSNGD	Reach-in	14.70	1.60
Continental Refrigerator	1RSNGDHD	Reach-in	14.40	1.63
Continental Refrigerator	1RXNGD	Reach-in	28.70	2.29
Continental Refrigerator	1RXNGDHD	Reach-in	28.40	2.46
Continental Refrigerator	1RXNGDPT	Pass-Through	33.20	2.68
Continental Refrigerator	1RXNGDPTHD	Pass-Through	32.60	2.76
Continental Refrigerator	1RXSNGD	Reach-in	23.00	2.20
Continental Refrigerator	1RXSNGDHD	Reach-in	22.70	2.21
Continental Refrigerator	2RENGD	Reach-in	48.80	3.34
Continental Refrigerator	2RENGDHD	Reach-in	48.30	3.45
Continental Refrigerator	2RESNGD	Reach-in	40.80	3.05
Continental Refrigerator	2RESNGDHD	Reach-in	40.30	3.11
Continental Refrigerator	2RNGD	Reach-in	43.70	2.78
Continental Refrigerator	2RNGDHD	Reach-in	42.60	3.21
Continental Refrigerator	2RSNGD	Reach-in	36.50	2.82
Continental Refrigerator	2RSNGDHD	Reach-in	36.00	2.88
Continental Refrigerator	3R-GD-HD-R	Reach-in	67.60	5.25
Continental Refrigerator	3R-GD-R	Reach-in	68.40	5.22
Continental Refrigerator	3RE-GD-HD-R	Reach-in	75.70	5.48
Continental Refrigerator	3RE-GD-R	Reach-in	77.00	5.45
Continental Refrigerator	3RENGD	Reach-in	77.00	6.25
Continental Refrigerator	3RENGDHD	Reach-in	75.70	6.56
Continental Refrigerator	3RENGDPT	Pass-Through	84.00	6.80
Continental Refrigerator	3RNGD	Reach-in	68.40	6.00
Continental Refrigerator	3RNGDPTHD	Pass-Through	74.00	6.20
Continental Refrigerator	D1RENGD	Reach-in	21.80	1.87
Continental Refrigerator	D1RENGDHD	Reach-in	21.50	2.10
Continental Refrigerator	D1RENGDPT	Pass-Through	24.50	2.27
Continental Refrigerator	D1RENGDPTHD	Pass-Through	24.00	2.32
Continental Refrigerator	D1RESNGD	Reach-in	18.80	1.84
Continental Refrigerator	D1RESNGDHD	Reach-in	18.90	2.01
Continental Refrigerator	D1RINGD	Reach-in	32.00	2.61
Continental Refrigerator	D1RNGD	Reach-in	19.30	1.99
Continental Refrigerator	D1RNGDHD	Reach-in	19.30	2.01

Qualified Glass Door Refrigerators

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
Continental Refrigerator	D1RNGDPT	Pass-Through	22.10	2.22
Continental Refrigerator	D1RSENGD	Reach-in	13.80	1.50
Continental Refrigerator	D1RSENGDHD	Reach-in	13.60	1.63
Continental Refrigerator	D1RSESNGD	Reach-in	11.30	1.48
Continental Refrigerator	D1RSNGD	Reach-in	14.70	1.60
Continental Refrigerator	D1RSNGDHD	Reach-in	14.40	1.63
Continental Refrigerator	D1RXNGD	Reach-in	29.20	2.52
Continental Refrigerator	D1RXNGDHD	Reach-in	28.90	2.55
Continental Refrigerator	D1RXNGDPT	Pass-Through	33.20	2.68
Continental Refrigerator	D1RXNGDPTHD	Pass-Through	32.60	2.76
Continental Refrigerator	D1RXSNGD	Reach-in	23.00	2.20
Continental Refrigerator	D1RXSNGDHD	Reach-in	22.70	2.21
Continental Refrigerator	D2RESNGD	Reach-in	40.80	3.05
Continental Refrigerator	D2RESNGDHD	Reach-in	40.30	3.11
Continental Refrigerator	D2RINGD	Reach-in	62.94	4.65
Continental Refrigerator	D2RINGDRT	Roll-Through	67.34	4.98
Continental Refrigerator	D2RSNGD	Reach-in	36.50	2.82
Continental Refrigerator	D2RSNGDHD	Reach-in	36.00	2.88
Continental Refrigerator	D3RENGD	Reach-in	77.00	5.74
Continental Refrigerator	D3RENGDHD	Reach-in	75.70	5.76
Continental Refrigerator	D3RENGDPT	Pass-Through	84.00	6.80
Continental Refrigerator	D3RNGD	Reach-in	69.20	5.50
Continental Refrigerator	D3RNGDHD	Reach-in	68.40	5.52
Continental Refrigerator	D3RNGDPTHD	Pass-Through	74.00	6.20
Continental Refrigerator	SW48NGD	Work-Top Table	11.60	1.49
Continental Refrigerator	SW60NGD	Work-Top Table	14.50	1.53
Continental Refrigerator	SW72NGD	Work-Top Table	18.50	2.02
Delfield	6025XL-G	Reach-in	18.90	1.60
Delfield	6025XL-GH	Reach-in	18.86	1.70
Delfield	6051XL-G	Reach-in	41.45	2.63
Delfield	6051XL-GH	Reach-in	41.45	2.89
Delfield	CSR2NP-G	Reach-in	39.76	2.39
Delfield	CSR2NP-GH	Reach-in	39.53	2.37
Delfield	CSRPT1P-G	Pass-Through	23.63	2.21
Delfield	CSRPT2P-G	Pass-Through	49.93	3.20
Delfield	CSRPT2P-GH	Pass-Through	49.38	3.67
Delfield	CSRR1IP-G	Roll-In	37.66	2.97
Delfield	CSRR2P-GS	Roll-Through	80.06	5.35
Delfield	GAR1NP-GH*****	Reach-in	17.87	1.98
Delfield	GAR1P-GH*****	Reach-in	21.46	2.04
Delfield	GAR2NP-G*****	Reach-in	39.76	2.66
Delfield	GAR2NP-GH*****	Reach-in	39.53	2.37
Delfield	GAR2P-G*****	Reach-in	45.85	2.86
Delfield	GAR2P-GH*****	Reach-in	45.58	2.86
Delfield	GAR3P-C*****	Reach-in	71.22	5.58
Delfield	GAR3P-GH*****	Reach-in	70.81	5.05
Delfield	GARPT1P-C*****	Pass-Through	23.63	2.20
Delfield	GARPT2P-C*****	Pass-Through	49.93	3.68
Delfield	GARPT2P-G*****	Pass-Through	49.93	3.54
Delfield	GARPT2P-GH*****	Pass-Through	49.38	3.67
Delfield	GARPT2P-GH*****	Pass-Through	49.38	3.67
Delfield	GARR1IP-G*****	Roll-In	37.66	2.74
Delfield	GARR1IP-G*****	Roll-In	37.66	2.50
Delfield	GARRI2P-C*****	Roll-In	76.34	5.18
Delfield	GARRI2P-G*****	Roll-In	76.34	4.35
Delfield	GARRT1P-C*****	Roll-Through	39.00	2.75
Delfield	GARRT1P-C*****	Roll-Through	39.00	3.24
Delfield	GARRT2P-C*****	Roll-Through	80.06	5.23

Qualified Glass Door Refrigerators

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
Delfield	GARRT2P-GS*****	Roll-Through	80.06	5.83
Delfield	GCR1P-GH	Reach-in	21.46	2.04
Delfield	GCR2P-G	Reach-in	45.85	3.69
Delfield	GCR2P-GH	Reach-in	45.58	2.86
Delfield	GCR3P-G	Reach-in	71.22	5.58
Delfield	GCR3P-GH	Reach-in	70.81	5.05
Desmon SPA	PGM07G-A	Other	19.42	1.34
Desmon SPA	PGM07G-C-A	Other	19.42	1.34
Desmon SPA	PGM14G-A	Other	42.32	3.12
Desmon SPA	PGM14G-C-A	Other	42.32	3.12
Desmon SPA	PGM21G-A	Other	71.57	3.50
Display Source Alliance	Dula30	Reach-in	12.78	1.37
Display Source Alliance	Dula36s	Reach-in	13.32	1.60
Display Source Alliance	Dula48	Reach-in	16.09	1.76
Display Source Alliance	Lina24S	Reach-in	7.20	0.80
Display Source Alliance	Santi22	Reach-in	3.92	0.78
Economy Series	EUR27A	Reach-in	6.33	0.86
Economy Series	EUR48A	Reach-in	12.09	1.22
Everest Refrigeration	EMGR24	Reach-in	25.02	2.34
Everest Refrigeration	EMGR24B	Reach-in	25.02	2.34
Everest Refrigeration	EMGR24C	Reach-in	25.02	2.34
Fogel	HR24-GL	Reach-in	3.90	0.65
Fogel	V-513	Reach-in	15.62	1.79
Fogel	VR-10-HC	Reach-in	8.74	1.10
Fogel	VR-12-HC	Reach-in	10.68	1.27
Fogel	VR-17-RE	Reach-in	15.46	1.75
Fogel	VR-26-HC	Reach-in	21.34	1.81
Fogel	VR-9-HC-US	Reach-in	7.23	1.10
Haier	SC-258H	Reach-in	8.50	1.15
Haier	SC-328H	Reach-in	10.70	1.41
Hoshizaki	BB80-G*	Undercounter	28.73	2.44
Hoshizaki	BB95-G*	Undercounter	32.53	2.64
Hoshizaki	HR24C	Reach-in	3.87	0.64
Hoshizaki	R3A-FG***	Reach-in	79.03	6.50
Hoshizaki	R3A-HC***	Reach-in	79.03	6.50
Hoshizaki	RM-10-HC	Reach-in	8.74	1.10
Hoshizaki	RM-26-HC	Reach-in	21.34	1.81
Hoshizaki	UR48B-CLP01	Undercounter	12.00	1.46
Husmann Corporation	DD5X5FRW	Reach-in	251.91	23.39
Husmann Corporation	RM3W	Reach-in	106.70	9.21
Husmann Corporation	RM4W	Reach-in	141.80	11.03
Husmann Corporation	RM5W	Reach-in	177.00	13.56
Husmann Corporation	RMN4W	Reach-in	124.30	11.03
Husmann Corporation	RMN5W	Reach-in	155.20	13.56
IDW	G-10SI-N-3-3-4-B-5	Other	9.30	1.20
IDW	G-12SI-N-3-3-4-B-5	Other	11.40	1.32
IDW	G-2.5SI-N-2-3-4-B-5	Other	2.60	0.65
IDW	G-26SI-C-3-3-4-B-5	Other	22.60	1.86
IDW	G-37SI-N-3-3-5-B-5	Other	33.80	2.66
IDW	G-3SI-N-2-3-4-B-5	Other	3.30	0.65
IDW	G-45SI-C-3-3-5-B-5	Other	38.20	2.75
IDW	G-45SI-N-3-3-5-B-5	Other	38.20	2.75
IDW	G-49SI-C-3-3-5-B-5	Other	40.70	3.33
IDW	G-49SI-N-3-3-5-B-5	Other	40.70	3.33
IDW	G-4SI-N-2-3-4-B-5	Other	4.30	0.85
IDW	G-5SI-N-2-3-4-B-5	Other	5.40	0.89
IDW	G-7SI-N-3-3-4-B-5	Other	5.50	0.81
IDW	G-9SI-N-3-3-4-B-5	Other	7.20	1.04

Qualified Glass Door Refrigerators

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).

NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
IDW	G41-48SI-N335B	Other	14.20	1.45
IDW	G41-54SI-N335B	Other	16.90	1.50
IDW	G41-60SI-N335B	Other	19.30	1.68
IDW	GV-10SI-N-3-3-4-B-5	Other	9.30	1.20
IDW	GV-12SI-N-3-3-4-B-5	Other	11.40	1.32
IDW	GV-2.5SI-N-2-3-4-B-5	Other	2.60	0.65
IDW	GV-26SI-C-3-3-4-B-5	Other	22.60	1.86
IDW	GV-37SI-N-3-3-5-B-5	Other	33.80	2.66
IDW	GV-3SI-N-2-3-4-B-5	Other	3.30	0.65
IDW	GV-45SI-C-3-3-5-B-5	Other	38.20	2.75
IDW	GV-49SI-C-3-3-5-B-5	Other	40.70	3.33
IDW	GV-49SI-N-3-3-5-B-5	Other	40.70	3.33
IDW	GV-4SI-N-2-3-4-B-5	Other	4.30	0.85
IDW	GV-5SI-N-2-3-4-B-5	Other	5.40	0.89
IDW	GV-7SI-N-3-3-4-B-5	Other	5.50	0.81
IDW	GV-9.5+-N-3-3-4-B-5	Other	11.20	1.18
IDW	GV-9.5+SI-N-3-3-4-B-5	Other	11.20	1.18
IDW	GV-9SI-N-3-3-4-B-5	Other	7.20	1.04
Imbera	EVC04 R6	Reach-in	3.92	0.78
Imbera	EVC12 HC	Reach-in	12.78	1.37
Imbera	EVC14 HC	Reach-in	13.32	1.60
Imbera	EVC19 HC	Reach-in	16.09	1.76
Imbera	EVC19 R2	Reach-in	16.09	1.76
Imbera	EVC7.5 HC	Reach-in	7.20	0.80
Imbera	G319 R2 KM	Reach-in	19.18	1.85
Imbera	G319 R2 SZ	Reach-in	19.20	2.02
Imbera	G326 R2	Reach-in	26.12	2.26
Imbera	G372 HC	Reach-in	66.30	5.09
Imbera	VR06 R6	Reach-in	5.10	0.91
Imbera	VR08 R6	Reach-in	7.69	1.15
Imbera	VR09 CC R2	Reach-in	10.31	1.36
Imbera	VR10 R2	Reach-in	9.43	1.24
Imbera	VR10 R6	Reach-in	9.43	1.31
Imbera	VR10-58 R2	Reach-in	10.14	1.33
Imbera	VR13 CZ R6	Reach-in	11.72	1.53
Imbera	VRD21 R2	Reach-in	16.77	1.83
Imbera	VRD26 HC	Reach-in	25.69	2.37
Imbera	VRD35 R2	Reach-in	32.12	2.56
Imbera	VRD37 R2	Reach-in	37.42	3.12
Imbera	VRD37 SD R2	Reach-in	39.03	3.00
Imbera	VRD41 SD 48HC	Reach-in	13.44	1.62
Imbera	VRD41 SD 54HC	Reach-in	17.10	1.71
Imbera	VRD43 R2	Reach-in	41.66	3.29
Imbera	VRD43 SD R2	Reach-in	41.66	3.31
Imbera	VRD44 HC CZ	Reach-in	40.26	2.92
Imbera	VRD50 HC CZ	Reach-in	45.16	3.04
Imbera	VR511 HC	Reach-in	4.00	0.79
Kelvinator COMMERCIAL	KCHBB60G	Reach-in	16.60	1.88
Kelvinator COMMERCIAL	KCHBB72G	Reach-in	20.80	2.04
Kelvinator COMMERCIAL	KCHGM26R	Reach-in	21.60	1.73
Kelvinator COMMERCIAL	KCHGM48R	Reach-in	43.40	3.16
Kelvinator COMMERCIAL	KCHGM72R	Reach-in	67.60	4.05
Kelvinator COMMERCIAL	KCHRI25R1GDR	Reach-in	19.00	2.04
Kelvinator COMMERCIAL	KCHRI25R1GDR	Reach-in	19.00	2.04
Kelvinator COMMERCIAL	KCHRI27R1GDR	Reach-in	19.00	1.54
Kelvinator COMMERCIAL	KCHRI27R2HGDR	Reach-in	19.00	1.54
Kelvinator COMMERCIAL	KCHRI54R2GDR	Reach-in	43.90	2.56
Kelvinator COMMERCIAL	KCHRI54R4HGDR	Reach-in	43.90	2.56

Qualified Glass Door Refrigerators

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
Kelvinator COMMERCIAL	KCHRI81R3GDR	Reach-in	68.80	3.91
Kelvinator COMMERCIAL	KCHSGM48R	Reach-in	40.10	3.37
Kelvinator COMMERCIAL	KCHSGM72R	Reach-in	63.60	4.69
KERONG	BC-89	Reach-in	3.13	0.65
KERONG	KWS-34F	Reach-in	3.13	0.65
KUTANO	KUTG DM 1**	Reach-in	20.31	1.80
KUTANO	KUTG DM 2**	Reach-in	47.17	3.44
Liebherr	BCDv 4613	Reach-in	16.30	1.84
Magic Chef	MCCM21ST	Other	2.12	0.64
Magic Chef	MCCM31ST	Other	3.14	0.74
Master-Bilt	MPR80*SSG/OX	Reach-in	82.95	6.72
METALFRIO	NG10CHC	Reach-in	9.20	1.00
METALFRIO	NG11CHC	Reach-in	9.50	1.14
METALFRIO	NG12CHC	Reach-in	11.29	1.17
METALFRIO	NG13CHC	Reach-in	11.60	1.26
METALFRIO	NG26CHC	Reach-in	22.20	2.00
METALFRIO	NG27CHC	Reach-in	24.50	2.28
METALFRIO	NG27CHN	Reach-in	22.70	1.63
METALFRIO	NG42CHC	Reach-in	33.70	2.89
METALFRIO	NG43CHC	Reach-in	39.14	3.27
METALFRIO	NG43CHCSD	Reach-in	37.47	3.02
METALFRIO	NG44CHC	Reach-in	41.18	3.34
METALFRIO	NG49CHC	Reach-in	46.26	3.43
METALFRIO	NG4CHC	Reach-in	4.66	0.87
METALFRIO	NG4CHS	Reach-in	4.27	0.81
METALFRIO	NG50CHC	Reach-in	48.64	3.54
METALFRIO	NG5CHC	Reach-in	5.82	0.99
METALFRIO	NG6CHC	Reach-in	6.47	0.98
METALFRIO	NG9CHC	Reach-in	8.00	1.11
Migali	C-23RM-HC	Reach-in	19.10	1.72
Migali	C-49RM-HC	Reach-in	43.80	3.60
Migali	C-BB72SG-HC	Undercounter	20.40	1.99
Minus Forty	10-USGR-00-1C00*-*****	Reach-in	9.15	1.19
Minus Forty	10-USGR-X1-1C00*-*****	Reach-in	9.15	1.19
Minus Forty	13-USGR-00-1C00*-*****	Reach-in	11.24	1.37
Minus Forty	13-USGR-L2-1C00*-*****	Reach-in	11.24	1.37
Minus Forty	13-USGR-X1-1C00*-*****	Reach-in	11.24	1.37
Minus Forty	19-USGR-00-1C00*-*****	Reach-in	18.39	1.72
Minus Forty	19-USGR-L2-1C00*-*****	Reach-in	18.39	1.72
Minus Forty	19-USGR-X1-1C00*-*****	Reach-in	18.39	1.72
Minus Forty	22-USGR-00-1C00*-*****	Reach-in	21.50	1.85
Minus Forty	22-USGR-F1-1C00*-*****	Reach-in	21.83	2.06
Minus Forty	22-USGR-F2-1C00*-*****	Reach-in	21.83	2.06
Minus Forty	22-USGR-L2-1C00*-*****	Reach-in	21.50	1.85
Minus Forty	22-USGR-X1-1C00*-*****	Reach-in	21.50	1.85
Minus Forty	43-UDGR-00-1C00*-*****	Reach-in	35.43	2.81
Minus Forty	43-UDGR-L1-1C00*-*****	Reach-in	35.43	2.81
Minus Forty	43-UDGR-X1-1C00*-*****	Reach-in	35.43	2.81
Norlake	NR803**G/OX	Reach-in	79.85	5.98
Norlake	NR806**G/OX	Reach-in	79.52	5.90
Norlake	NR806SSG/0	Reach-in	79.52	7.20
Norlake	PR80*SSG/OX	Reach-in	82.95	6.72
Perlick	CC24B-2-***	Reach-in	13.00	1.60
Perlick	CC24W-2-***	Reach-in	13.00	1.60
Perlick	CC30B-2-***	Reach-in	16.93	1.80
Perlick	CC30D-2-***	Reach-in	16.92	1.90
Perlick	CC30W-2-***	Reach-in	16.93	1.80
Perlick	HC24RS4T-**-*****	Undercounter	5.22	0.86

Qualified Glass Door Refrigerators

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
Perlick	HC24WS4T-**-*****	Undercounter	5.22	0.86
Polarman	PLM-27RGS	Reach-in	18.10	0.90
Polarman	PLM-54RGS	Reach-in	41.60	1.24
Pro-Kold	G372 HC	Reach-in	66.30	5.09
Pro-Kold	VC-12-H2-G1	Reach-in	11.50	1.46
Pro-Kold	VC-23-H2-G1	Reach-in	19.20	1.80
Pro-Kold	VC-43-H2-G2	Reach-in	37.42	3.12
Pro-Kold	VC-49-H2-G2	Reach-in	41.66	3.29
Pro-Kold	VRD26 HC	Reach-in	25.69	2.37
Pro-Kold	VRD44 HC CZ	Reach-in	40.26	2.92
Pro-Kold	VRD50 HC CZ	Reach-in	45.16	3.04
QBD	CD10-58-HC	Reach-in	10.55	1.33
QBD	CD10-HC	Reach-in	9.65	1.27
QBD	CD12-HC	Reach-in	11.62	1.36
QBD	CD26-HC	Reach-in	23.67	2.28
QBD	CD26FDE-HC	Reach-in	24.21	2.27
QBD	CD47FD-HC	Reach-in	44.48	3.60
QBD	CD72-HC	Reach-in	64.80	5.52
QBD	PC8-HC	Reach-in	9.67	1.30
Royal Vendors	RVCF-027	Reach-in	25.44	2.39
Royal Vendors	RVCFH-027	Reach-in	25.44	2.39
Summit Commercial	ACR1818***	Reach-in	16.26	1.47
Summit Commercial	ACR261***	Reach-in	21.34	1.81
Summit Commercial	ADA72G	Other	5.43	0.94
Summit Commercial	ADA72GB***	Other	5.50	0.94
Summit Commercial	ADA72GLH	Other	5.43	0.94
Summit Commercial	BAR14***	Undercounter	2.20	0.64
Summit Commercial	BAR141S***	Undercounter	2.20	0.64
Summit Commercial	BAR19	Reach-in	3.13	0.65
Summit Commercial	BAR191S	Reach-in	3.13	0.65
Summit Commercial	BAR72G	Other	5.43	0.94
Summit Commercial	BAR72GB***	Other	5.50	0.94
Summit Commercial	BAR72GLH	Other	5.43	0.94
Summit Commercial	BC14***	Undercounter	2.20	0.64
Summit Commercial	BC143S***	Undercounter	2.20	0.64
Summit Commercial	BC193S	Reach-in	3.13	0.65
Summit Commercial	BC89	Reach-in	3.13	0.65
Summit Commercial	SBC56****	Undercounter	5.43	0.94
Summit Commercial	SBC56BG****	Other	5.50	0.94
Summit Commercial	SCLP73BC***	Other	5.50	0.94
Summit Commercial	SCLP74WC***	Other	5.50	0.94
Summit Commercial	SCOM73BC****	Other	5.50	0.94
Summit Commercial	SCOM74WG***	Other	5.50	0.94
Summit Commercial	SCR1400W	Reach-in	15.20	1.88
Summit Commercial	SCR1802G***	Reach-in	16.26	1.47
Summit Commercial	SCR1931	Reach-in	3.13	0.65
Summit Commercial	SCR23SSG**	Reach-in	19.53	1.74
Summit Commercial	SCR23SSSGLH**	Reach-in	19.53	1.74
Summit Commercial	SCR314L	Reach-in	2.15	0.64
Summit Commercial	SCR450*/SCR500*	Reach-in	4.10	0.80
Summit Commercial	SCR489OS	Reach-in	3.21	0.60
Summit Commercial	SCR49SSG**	Reach-in	42.24	3.15
Summit Commercial	SCR49SSSGLH**	Reach-in	42.24	3.16
Summit Commercial	SCR600*GL**	Other	5.43	0.94
Summit Commercial	SCR600B*GL**	Other	5.43	0.94
Summit Commercial	SCR600B*GL**	Other	5.43	0.94
Summit Commercial	SCR610BL	Reach-in	5.07	0.84
Summit Commercial	SCR72SSG**	Reach-in	60.84	4.18

Qualified Glass Door Refrigerators

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
Summit Commercial	SCR72SSGLH**	Reach-in	60.84	4.18
Summit Commercial	SCRR261G***	Reach-in	21.34	1.81
Summit Commercial	SPR314LOS***	Undercounter	2.15	0.64
Summit Commercial	SPR489OS	Reach-in	3.13	0.65
Traulsen	CLUC-27R-GD	Undercounter	6.80	1.04
Traulsen	CLUC-36R-GD	Undercounter	9.30	1.26
Traulsen	CLUC-48R-GD	Undercounter	12.80	1.58
Traulsen	CLUC-60R-GD	Undercounter	16.40	1.84
Traulsen	CLUC-72R-GD	Undercounter	20.30	2.03
True	FLM-27~TSL01	Reach-in	19.54	1.86
True	FLM-81~TSL01	Reach-in	67.30	5.73
True	GDM-05-HC-LD	Reach-in	5.43	0.87
True	GDM-05-HC~FGD01	Reach-in	5.43	0.87
True	GDM-05-HC~TSL01	Reach-in	5.43	0.87
True	GDM-05-S-HC-LD	Reach-in	5.43	0.87
True	GDM-05-S-HC~FGD01	Reach-in	5.43	0.87
True	GDM-05PT-HC~FGD01	Pass-Through	5.05	0.86
True	GDM-05PT-S-HC~FGD01	Pass-Through	5.05	0.86
True	GDM-06-34-HC~FGD01	Reach-in	5.05	0.86
True	GDM-06-34-HC~TSL01	Reach-in	5.35	0.86
True	GDM-06-34-HC~TSL01-EXT TOP	Reach-in	5.05	0.86
True	GDM-07-HC~FGD01	Reach-in	6.69	1.01
True	GDM-07-HC~TSL01	Reach-in	6.69	1.01
True	GDM-07-S-HC~TSL01	Reach-in	6.69	1.01
True	GDM-08-HC~TSL01	Reach-in	6.66	1.05
True	GDM-10-58-HC~TSL01	Reach-in	10.31	1.39
True	GDM-10-HC~FGD01	Reach-in	9.20	1.18
True	GDM-10-HC~TSL01	Pass-Through	9.20	1.18
True	GDM-12-HC~FGD01	Reach-in	11.31	1.27
True	GDM-12-HC~TSL01	Pass-Through	11.31	1.27
True	GDM-12FC-HC-LD	Reach-in	11.31	1.27
True	GDM-12FC-HC~TSL01	Reach-in	11.31	1.27
True	GDM-14RF-HC-LD	Reach-in	15.09	1.18
True	GDM-19T-HC~FGD01	Reach-in	16.45	1.91
True	GDM-19T-HC~TSL01	Reach-in	16.45	1.91
True	GDM-23-2-HC-LD	Reach-in	20.41	1.84
True	GDM-23-HC~FGD01	Reach-in	20.55	1.95
True	GDM-23-HC~TSL01	Reach-in	20.55	1.95
True	GDM-23-HST-HC~FGD01	Reach-in	20.55	1.95
True	GDM-23-HST-HC~TSL01	Reach-in	20.55	1.95
True	GDM-23FC-HC~FGD01	Reach-in	20.55	1.95
True	GDM-23FC-HC~TSL01	Reach-in	20.55	1.95
True	GDM-23W-HC~FGD01	Reach-in	20.55	1.95
True	GDM-23W-HC~TSL01	Reach-in	20.55	1.95
True	GDM-26-HC~FGD01	Reach-in	23.21	1.92
True	GDM-26-HC~TSL01	Reach-in	23.21	1.92
True	GDM-26-HST-HC~FGD01	Reach-in	23.21	1.92
True	GDM-26-HST-HC~TSL01	Reach-in	23.21	1.92
True	GDM-33-HC-LD	Reach-in	28.67	2.40
True	GDM-35-HC~FGD01	Reach-in	29.30	2.50
True	GDM-35-HC~TSL01	Reach-in	29.30	2.50
True	GDM-35SL-RF-HC-LD	Reach-in	15.50	1.72
True	GDM-37-HC-LD	Reach-in	32.11	2.72
True	GDM-41-HC-LD	Reach-in	35.24	2.92
True	GDM-41C-48-HC-LD	Reach-in	14.48	1.57
True	GDM-41SL-54-HC-LD	Reach-in	14.10	1.74
True	GDM-41SL-60-HC-LD	Reach-in	16.50	1.85

Qualified Glass Door Refrigerators

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
True	GDM-43-HC~FGD01	Reach-in	37.71	2.68
True	GDM-43-HC~TSL01	Reach-in	37.71	2.68
True	GDM-45-HC-LD	Reach-in	38.68	3.23
True	GDM-47-HC-LD	Reach-in	41.35	3.48
True	GDM-49-HC~FGD01	Reach-in	44.34	3.60
True	GDM-49-HC~TSL01	Reach-in	44.34	3.60
True	GDM-49FC-HC~FGD01	Reach-in	44.34	3.60
True	GDM-49FC-HC~TSL01	Reach-in	44.34	3.60
True	GDM-69-HC-LD	Reach-in	61.62	4.89
True	GDM-72-HC~FGD01	Reach-in	65.68	4.90
True	GDM-72-HC~TSL01	Reach-in	65.68	4.90
True	GDM-72FC-HC~FGD01	Reach-in	65.68	4.90
True	GDM-72FC-HC~TSL01	Reach-in	65.68	4.90
True	STA1R-1G	Reach-in	22.86	2.21
True	STA1R-1G-HC	Reach-in	22.86	1.74
True	STA1R-1HG/1HS	Reach-in	22.33	2.11
True	STA1RPT-1G-1G-HC	Pass-Through	25.07	2.37
True	STA1RRI-1G	Roll-In	36.98	3.06
True	STA2R-2G-HC	Reach-in	48.40	3.01
True	STA2R-4HG-HC	Reach-in	48.01	3.41
True	STA2RPT-2G-2G-HC	Pass-Through	52.79	3.41
True	STA2RPT-2G-2S-HC	Pass-Through	51.25	3.41
True	STA2RPT-2HG/2HS-2G-HC	Pass-Through	52.10	3.41
True	STA2RPT-2S-2G-HC	Pass-Through	51.25	3.41
True	STA2RPT-4HG-2G-HC	Pass-Through	52.40	3.41
True	STA2RPT-4HG-2S-HC	Pass-Through	50.85	3.41
True	STA2RPT-4HG-4HG-HC	Pass-Through	52.01	3.41
True	STA2RPT-4HS-2G-HC	Pass-Through	51.08	3.41
True	STG1R-1G	Reach-in	22.86	2.21
True	STG1R-1G-HC	Reach-in	22.86	1.74
True	STG1R-1HG/1HS	Reach-in	22.33	2.11
True	STG1RPT-1G-1G-HC	Pass-Through	25.07	2.37
True	STG1RRI-1G	Roll-In	36.98	3.06
True	STG2R-2G-HC	Reach-in	48.40	3.01
True	STG2R-4HG-HC	Reach-in	48.01	3.41
True	STG2RPT-2G-2G-HC	Pass-Through	52.79	3.41
True	STG2RPT-2G-2S-HC	Pass-Through	51.25	3.41
True	STG2RPT-2HG/2HS-2G-HC	Pass-Through	52.10	3.41
True	STG2RPT-2S-2G-HC	Pass-Through	51.25	3.41
True	STG2RPT-4HG-2G-HC	Pass-Through	52.40	3.41
True	STG2RPT-4HG-2S-HC	Pass-Through	50.85	3.41
True	STG2RPT-4HG-4HG-HC	Pass-Through	52.01	3.41
True	STG2RPT-4HS-2G-HC	Pass-Through	51.08	3.41
True	STR1R-1G	Reach-in	22.86	2.21
True	STR1R-1G-HC	Reach-in	22.86	1.74
True	STR1R-1HG/1HS	Reach-in	22.33	2.11
True	STR1RPT-1G-1G-HC	Pass-Through	25.07	2.37
True	STR1RRI-1G	Roll-In	36.98	3.06
True	STR2R-2G-HC	Reach-in	48.40	3.01
True	STR2R-4HG-HC	Reach-in	48.01	3.41
True	STR2RPT-2G-2G-HC	Pass-Through	52.79	3.41
True	STR2RPT-2G-2S-HC	Pass-Through	51.25	3.41
True	STR2RPT-2HG/2HS-2G-HC	Pass-Through	52.10	3.41
True	STR2RPT-2S-2G-HC	Pass-Through	51.25	3.41
True	STR2RPT-4HG-2G-HC	Pass-Through	52.40	3.41
True	STR2RPT-4HG-2S-HC	Pass-Through	50.85	3.41
True	STR2RPT-4HG-4HG-HC	Pass-Through	52.01	3.41
True	STR2RPT-4HS-2G-HC	Pass-Through	51.08	3.41

Qualified Glass Door Refrigerators

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
True	T-12G-HC~FGD01	Reach-in	11.33	1.17
True	T-15-1-G-1-HC-LD	Reach-in	12.76	1.12
True	T-19G-HC~FGD01	Reach-in	15.29	1.40
True	T-23G-2-HC~FGD01	Reach-in	19.68	1.41
True	T-23G-HC~FGD01	Reach-in	20.25	1.49
True	T-23G-PT-HC~FGD01	Pass-Through	20.92	1.41
True	T-23G-PT-HC~FGD01 MCD1	Pass-Through	20.96	1.51
True	T-49-2-G-2-HC~FGD01	Reach-in	43.41	3.20
True	T-49G-4-HC~FGD01	Reach-in	43.41	3.20
True	T-49G-HC~FGD01	Reach-in	43.41	3.20
True	TBB-24-48G-HC-LD	Undercounter	13.21	1.47
True	TBB-24-48G-S-HC-LD	Undercounter	13.21	1.47
True	TBB-24-60G-HC-LD	Undercounter	17.61	1.66
True	TBB-24-60G-S-HC-LD	Undercounter	17.61	1.66
True	TBB-24GAL-48G-HC-LD	Undercounter	13.21	1.47
True	TBB-24GAL-48G-S-HC-LD	Undercounter	13.21	1.47
True	TBB-24GAL-60G-HC-LD	Undercounter	17.61	1.66
True	TBB-24GAL-60G-S-HC-LD	Undercounter	17.61	1.66
True	TBB-2G-HC-LD	Undercounter	20.34	1.43
True	TBB-2G-S-HC-LD	Undercounter	20.34	1.43
True	TBB-3G-HC-LD	Undercounter	24.42	1.74
True	TBB-3G-S-HC-LD	Undercounter	24.42	1.74
True	TBB-4G-HC-LD	Undercounter	28.57	2.35
True	TBB-4G-S-HC-LD	Undercounter	28.57	2.35
True	TBR48-RISZ1-L-B-11-1	Undercounter	11.29	1.00
True	TBR48-RISZ1-L-B-GG-1	Undercounter	11.73	0.86
True	TBR48-RISZ1-L-S-11-1	Undercounter	11.29	1.00
True	TBR48-RISZ1-L-S-GG-1	Undercounter	11.73	0.86
True	TBR52-RISZ1-L-B-11-1	Undercounter	12.68	1.00
True	TBR52-RISZ1-L-B-GG-1	Undercounter	13.19	0.88
True	TBR52-RISZ1-L-S-11-1	Undercounter	12.68	1.00
True	TBR52-RISZ1-L-S-GG-1	Undercounter	13.19	0.88
True	TBR60-RISZ1-L-B-11-1	Undercounter	15.46	1.29
True	TBR60-RISZ1-L-B-GG-1	Undercounter	16.11	1.17
True	TBR60-RISZ1-L-S-11-1	Undercounter	15.46	1.29
True	TBR60-RISZ1-L-S-GG-1	Undercounter	16.11	1.17
True	TBR72-RISZ1-L-B-111-1	Undercounter	19.55	1.52
True	TBR72-RISZ1-L-B-GGG-1	Undercounter	20.28	1.31
True	TBR72-RISZ1-L-B-SGG-1	Undercounter	20.16	1.31
True	TBR72-RISZ1-L-S-111-1	Undercounter	19.55	1.52
True	TBR72-RISZ1-L-S-GGG-1	Undercounter	20.28	1.31
True	TBR72-RISZ1-L-S-SGG-1	Undercounter	20.16	1.31
True	TDB-24-48-1-G-1-HC-LD	Undercounter	13.21	1.47
True	TDB-24-48G-HC-LD	Undercounter	13.21	1.47
True	TDR48-RISZ1-L-B-11-1	Undercounter	11.29	1.00
True	TDR48-RISZ1-L-B-GG-1	Undercounter	11.73	0.86
True	TDR48-RISZ1-L-S-11-1	Undercounter	11.29	1.00
True	TDR48-RISZ1-L-S-GG-1	Undercounter	11.73	0.86
True	TDR52-RISZ1-L-B-11-1	Undercounter	12.68	1.00
True	TDR52-RISZ1-L-B-GG-1	Undercounter	13.19	0.88
True	TDR52-RISZ1-L-S-11-1	Undercounter	12.68	1.00
True	TDR52-RISZ1-L-S-GG-1	Undercounter	13.19	0.88
True	TDR60-RISZ1-L-B-11-1	Undercounter	15.46	1.29
True	TDR60-RISZ1-L-B-GG-1	Undercounter	16.11	1.17
True	TDR60-RISZ1-L-S-11-1	Undercounter	15.46	1.29
True	TDR60-RISZ1-L-S-GG-1	Undercounter	16.11	1.17
True	TDR72-RISZ1-L-B-111-1	Undercounter	19.55	1.52
True	TDR72-RISZ1-L-B-GGG-1	Undercounter	20.28	1.31

Qualified Glass Door Refrigerators

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).

NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
True	TDR72-RISZ1-L-B-SGG-1	Undercounter	20.16	1.31
True	TDR72-RISZ1-L-S-111-1	Undercounter	19.55	1.52
True	TDR72-RISZ1-L-S-GGG-1	Undercounter	20.28	1.31
True	TDR72-RISZ1-L-S-SGG-1	Undercounter	20.16	1.31
TRUE	TRM2M-***_***_*****_**_*	Reach-in	77.89	4.74
TRUE	TRM3M-***_***_*****_**_*	Reach-in	116.15	6.85
TRUE	TRM4M-***_***_*****_**_*	Reach-in	154.41	8.45
True	TS-23G-2-HC~FGD01	Reach-in	19.68	1.41
True	TS-23G-HC~FGD01	Reach-in	20.25	1.49
True	TS-23G-PT-HC~FGD01	Pass-Through	20.92	1.41
True	TS-49-2-G-2-HC~FGD01	Reach-in	43.41	3.20
True	TS-49G-4-HC~FGD01	Reach-in	43.41	3.20
True	TS-49G-HC~FGD01	Reach-in	43.41	3.20
True	TSD-47G-HC-LD	Reach-in	42.05	3.50
True	TUC-24G-HC~FGD01	Undercounter	5.42	0.85
True	TUC-27G-ADA-HC~FGD01	Undercounter	7.37	1.01
True	TUC-27G-ADA-HC~SPEC3	Undercounter	7.37	1.01
True	TUC-27G-HC~FGD01	Undercounter	7.37	1.01
True	TUC-27G-HC~SPEC3	Undercounter	7.37	1.01
True	TUC-27G-LP-HC~FGD01	Undercounter	7.37	1.01
True	TUC-27G-LP-HC~SPEC3	Undercounter	7.37	1.01
True	TUC-48G-ADA-HC~FGD01	Undercounter	13.78	1.47
True	TUC-48G-ADA-HC~SPEC3	Undercounter	13.78	1.47
True	TUC-48G-HC~FGD01	Undercounter	13.78	1.47
True	TUC-48G-HC~SPEC3	Undercounter	13.78	1.47
True	TUC-48G-LP-HC~FGD01	Undercounter	13.78	1.47
True	TUC-48G-LP-HC~SPEC3	Undercounter	13.78	1.47
Turbo Air	JUR-48-G-N	Reach-in	10.66	1.44
Turbo Air	JUR-60-G-N	Reach-in	14.58	1.78
Turbo Air	JUR-72-G-N	Reach-in	18.74	1.97
Turbo Air	MSR-72G-3	Reach-in	67.02	5.43
Turbo Air	TBB-24-60SG-N	Reach-in	16.46	1.78
Turbo Air	TBB-24-60SGD-N	Reach-in	16.46	1.83
Turbo Air	TBB-24-60SGSD-N	Reach-in	16.46	1.83
Turbo Air	TBB-24-72SGD-N	Reach-in	20.62	2.04
Turbo Air	TBB-2SG-N	Reach-in	19.00	1.82
Turbo Air	TBB-2SGD-N	Reach-in	19.00	2.01
Turbo Air	TBB-2SGSD-N	Reach-in	19.00	2.01
Turbo Air	TBB-3SG-N	Reach-in	23.00	1.95
Turbo Air	TBB-3SGD-N	Reach-in	23.00	1.92
Turbo Air	TBB-4SG-N	Reach-in	36.47	2.84
Turbo Air	TBB-4SGD-N	Reach-in	37.00	2.85
Turbo Air	TGM-10SD*-N6	Reach-in	8.12	1.12
Turbo Air	TGM-12SDB-N6	Reach-in	10.19	1.31
Turbo Air	TGM-12SDV-N6	Reach-in	10.19	1.31
Turbo Air	TGM-12SDW-N6	Reach-in	10.19	1.31
Turbo Air	TGM-15SD*-N6	Reach-in	14.43	1.64
Turbo Air	TGM-15SDHB-N	Reach-in	14.70	1.42
Turbo Air	TGM-15SDHB-N6	Reach-in	14.70	1.42
Turbo Air	TGM-15SDHV-N	Reach-in	14.70	1.42
Turbo Air	TGM-15SDHV-N6	Reach-in	14.70	1.42
Turbo Air	TGM-15SDHW-N	Reach-in	14.70	1.42
Turbo Air	TGM-15SDHW-N6	Reach-in	14.70	1.42
Turbo Air	TGM-23SD*-N6	Reach-in	19.40	1.85
Turbo Air	TGM-23SDB-N6-L	Reach-in	19.40	1.85
Turbo Air	TGM-23SDHB-N6	Reach-in	19.02	1.88
Turbo Air	TGM-23SDHB-N6-L	Reach-in	19.02	1.88
Turbo Air	TGM-23SDHV-N6	Reach-in	19.02	1.88

Qualified Glass Door Refrigerators

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
Turbo Air	TGM-23SDHV-N6-L	Reach-in	19.02	1.88
Turbo Air	TGM-23SDHW-N6	Reach-in	19.02	1.88
Turbo Air	TGM-23SDHW-N6-L	Reach-in	19.02	1.88
Turbo Air	TGM-23SDV-N6-L	Reach-in	19.40	1.85
Turbo Air	TGM-23SDW-N6-L	Reach-in	19.40	1.85
Turbo Air	TGM-35SDHB-N	Reach-in	31.70	2.26
Turbo Air	TGM-35SDHV-N	Reach-in	31.70	2.26
Turbo Air	TGM-35SDHW-N	Reach-in	31.70	2.26
Turbo Air	TGM-47SD*-N	Reach-in	41.71	3.30
Turbo Air	TGM-47SDHB-N	Reach-in	44.22	2.80
Turbo Air	TGM-47SDHV-N	Reach-in	44.22	2.80
Turbo Air	TGM-47SDHW-N	Reach-in	44.22	2.80
Turbo Air	TGM-5.1R-N6	Reach-in	2.44	0.51
Turbo Air	TGM-50RS-N	Reach-in	45.97	3.15
Turbo Air	TGM-50RSB-N	Reach-in	45.97	3.15
Turbo Air	TGM-5R-N6	Reach-in	4.16	0.60
Turbo Air	TGM-5SD*-N6	Reach-in	4.45	0.80
Turbo Air	TGM-72SDB-N	Reach-in	67.98	5.75
Turbo Air	TGM-72SDHB-N	Reach-in	70.44	5.14
Turbo Air	TGM-72SDHV-N	Reach-in	70.44	5.14
Turbo Air	TGM-72SDHW-N	Reach-in	70.44	5.14
Turbo Air	TGM-72SDV-N	Reach-in	67.98	5.75
Turbo Air	TGM-72SDW-N	Reach-in	67.98	5.75
Turbo Air	TGM-7SDB-N6	Reach-in	6.20	0.92
Turbo Air	TGM-7SDV-N6	Reach-in	6.20	0.92
Turbo Air	TGM-7SDW-N6	Reach-in	6.20	0.92
Turbo Air	TJMR-30SDAB-N	Reach-in	32.04	2.31
Turbo Air	TJMR-30SDB-N	Reach-in	32.04	2.31
Turbo Air	TJMR-30SDW-N	Reach-in	32.04	2.31
Turbo Air	TJMR-55SDAB-N	Reach-in	62.05	4.40
Turbo Air	TJMR-55SDB-N	Reach-in	62.05	4.40
Turbo Air	TJMR-55SDW-N	Reach-in	62.05	4.40
Turbo Air	TJMR-85SDAB-N	Reach-in	97.08	7.41
Turbo Air	TJMR-85SDB-N	Reach-in	97.08	7.41
Turbo Air	TJMR-85SDW-N	Reach-in	97.08	7.41
Turbo Air	TSR-23GSD-N6	Reach-in	20.00	1.64
Turbo Air	TSR-35GSD-N	Reach-in	27.50	2.37
Turbo Air	TSR-49GSD-N	Reach-in	44.14	2.99
Turbo Air	TSR-72GSD-N	Reach-in	67.02	5.23
U-Line	UCRE515-SG32A	Reach-in	3.70	0.72
U-Line	UCRE515-SG33A	Reach-in	3.70	0.72
U-Line	UCRE518-SG32A	Reach-in	3.70	0.75
U-Line	UCRE518-SG33A	Reach-in	3.70	0.75
U-Line	UCRE524-SG32A	Reach-in	5.20	0.90
U-Line	UCRE524-SG33A	Reach-in	5.20	0.90
U-Line	UCRE524-SG33B	Reach-in	5.20	0.90
U-Line	UCRE527-SG41A	Other	19.42	1.34
U-Line	UCRE553-SG71A	Reach-in	42.72	3.50
U-Line	UCRE553-SG71A	Other	42.32	3.12
U-Line	UCWC515-SG32A	Reach-in	3.70	0.72
U-Line	UCWC515-SG33A	Reach-in	3.70	0.72
U-Line	UCWC518-SG32A	Reach-in	3.70	0.75
U-Line	UCWC518-SG33A	Reach-in	3.70	0.75
U-Line	UCWC524-SG32A	Reach-in	5.20	0.90
U-Line	UCWC524-SG33A	Reach-in	5.20	0.90
Victory	LSR23*HC*1*****	Reach-in	23.10	2.12
Victory	LSR27*HC*1*****	Reach-in	26.17	2.21
Victory	LSR72*HC*1*****	Reach-in	68.94	5.49

Qualified Glass Door Refrigerators

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).

NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
Victory	VERS-2D-GD-HC*****	Reach-in	46.88	3.55
Victory	VERS-2D-HG-HC*****	Reach-in	46.88	3.55
Victory	VERS-3D-GD-HC*****	Reach-in	71.52	6.26
Victory	VERS-3D-HG-HC*****	Reach-in	71.52	6.26
Victory	VERSA-2D-GD-HC*****	Reach-in	46.88	3.55
Victory	VERSA-2D-HG-HC*****	Reach-in	46.88	3.55
Victory	VERSA-3D-GD-HC*****	Reach-in	71.52	6.26
Victory	VERSA-3D-HG-HC*****	Reach-in	71.52	6.26

Qualified Solid Door Refrigerators

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
Atosa	MBF8011GR	Reach-in	41.92	2.06
Atosa	MGF24RGR	Undercounter	4.30	0.75
Atosa	MGF36RGR	Undercounter	9.50	0.61
Atosa	MGF36RWGR	Undercounter	9.50	0.61
Avantco	178A23RHC	Reach-in	20.60	1.37
Avantco	178A49RHC	Reach-in	41.32	2.21
Avantco	178AU27R	Undercounter	6.10	0.80
Avantco	178AWT27R	Work-Top Table	6.10	0.80
Avantco	178SS1RHC	Reach-in	20.60	1.37
Avantco	178SS2RHC	Reach-in	41.32	2.21
Avantco	178SSUC36RHC	Undercounter	8.20	0.82
Avantco	178SSWT36RHC	Work-Top Table	8.20	0.82
Avantco	178UBB378*	Milk or Beverage Cabinet	28.00	1.58
Avantco	178UDD378*	Milk or Beverage Cabinet	28.00	1.68
Avantco	178Z**27R***	Undercounter	5.60	0.77
Avantco	178Z1R2A	Reach-in	21.14	1.40
Avantco	178Z1RHC	Reach-in	21.26	1.48
Avantco	178Z1RN	Reach-in	10.60	0.97
Avantco	178Z1RNWMS	Reach-in	10.60	0.97
Avantco	178Z2R4K	Reach-in	42.34	1.88
Avantco	178Z2RHC	Reach-in	42.59	1.81
Avantco	178ZUC27RHC	Undercounter	5.55	0.78
Avantco	178ZUC60RHC	Undercounter	13.90	1.12
Avantco	178ZWT27RHC	Work-Top Table	5.55	0.78
Avantco	178ZWT60RHC	Work-Top Table	13.90	1.12
Avantco	447AP23R	Reach-in	20.16	1.00
Avantco	447AP49R	Reach-in	44.85	1.84
Avantco	CFD-1RR	Reach-in	20.60	1.20
Avantco	CFD-2RR	Reach-in	41.40	2.00
Beverage-Air	HBR12HC-1*****	Reach-in	12.06	0.82
Beverage-Air	HBR19HC-1*S*****	Reach-in	17.87	1.20
Beverage-Air	HBR23HC*****	Reach-in	23.10	1.30
Beverage-Air	HBR27HC-1*****	Reach-in	25.88	1.40
Beverage-Air	HBR35HC-1*S*****	Reach-in	35.40	1.68
Beverage-Air	HBR44HC-1*****	Reach-in	40.20	1.93
Beverage-Air	HBR49HC-1*****	Reach-in	46.15	2.11
Beverage-Air	HBR72HC-1*****	Reach-in	68.93	2.38
Beverage-Air	HR2HC-1HS*****	Reach-in	45.20	2.51
Beverage-Air	HR2HC-1S*****	Reach-in	45.20	2.51
Beverage-Air	HR3HC-1HS*****	Reach-in	71.52	2.60
Beverage-Air	HR3HC-1S*****	Reach-in	71.52	2.60
Beverage-Air	HRP2HC-1HS*****	Reach-in	45.20	2.51
Beverage-Air	HRP2HC-1S*****	Reach-in	45.20	2.51
Beverage-Air	HRP3HC-1HS*****	Reach-in	71.52	2.60
Beverage-Air	HRP3HC-1S*****	Reach-in	71.52	2.60
Beverage-Air	HRPS2HC-1HS*****	Reach-in	45.20	2.51
Beverage-Air	HRPS2HC-1S*****	Reach-in	45.20	2.51
Beverage-Air	HRPS3HC-1HS*****	Reach-in	71.52	2.60
Beverage-Air	HRPS3HC-1S*****	Reach-in	71.52	2.60
Beverage-Air	HRS2HC-1HS*****	Reach-in	45.20	2.51
Beverage-Air	HRS2HC-1S*****	Reach-in	45.20	2.51
Beverage-Air	HRS3HC-1HS*****	Reach-in	71.52	2.60
Beverage-Air	HRS3HC-1S*****	Reach-in	71.52	2.60
Beverage-Air	RB19HC-1*S*****	Reach-in	17.87	1.20

Qualified Solid Door Refrigerators

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
Beverage-Air	RB23HC-1*S*****	Reach-in	23.10	1.30
Beverage-Air	RB27HC-1*S*****	Reach-in	25.88	1.40
Beverage-Air	RB44HC-1*S*****	Reach-in	40.20	1.93
Beverage-Air	RB49HC-1*S*****	Reach-in	46.15	2.14
Beverage-Air	RB72HC-1*S*****	Reach-in	68.93	2.68
Beverage-Air	SM34HC_*****	Milk or Beverage Cabinet	12.73	0.87
Beverage-Air	SM49HC_*****	Milk or Beverage Cabinet	20.32	0.98
Beverage-Air	SM58HC_*****	Milk or Beverage Cabinet	22.63	1.08
Beverage-Air	UCR20HC-*****	Undercounter	2.25	0.67
Beverage-Air	UCR32AHC-*****	Undercounter	7.22	0.79
Beverage-Air	UCR34HC*****	Undercounter	4.21	0.64
Beverage-Air	UCR46AHC-*****	Undercounter	10.80	0.81
Beverage-Air	UCR48AHC-*****	Undercounter	11.82	0.91
Beverage-Air	UCR60AHC-*****	Undercounter	14.75	0.93
Beverage-Air	UCR67AHC-*****	Undercounter	18.97	1.16
Beverage-Air	WTR20HC-*****	Work-Top Table	2.25	0.67
Beverage-Air	WTR32AHC-*****	Work-Top Table	7.22	0.79
Beverage-Air	WTR46AHC-*****	Work-Top Table	10.80	0.81
Beverage-Air	WTR48AHC-*****	Work-Top Table	11.82	0.91
Beverage-Air	WTR60AHC-*****	Work-Top Table	14.75	0.93
Beverage-Air	WTR67AHC-*****	Work-Top Table	18.97	1.16
Blue Air	BSR23-HC	Reach-in	18.89	0.85
Blue Air	BSR23T-HC	Reach-in	19.04	1.06
Blue Air	BSR49-HC	Reach-in	42.69	2.58
Blue Air	BSR49-HC_VI	Reach-in	42.70	2.05
Blue Air	BSR49T-HC	Reach-in	42.85	1.65
Blue Air	BSR49T-HC_VI	Reach-in	42.85	2.21
Blue Air	BSR72-HC	Reach-in	66.52	2.94
Blueline	BR-600V	Other	18.01	1.08
Chumart	CM-27R	Reach-in	18.11	0.90
Chumart	CM-54R	Reach-in	41.61	1.24
Chumart	CM-81R	Reach-in	66.01	1.65
Chumart	CM-BC4	Undercounter	29.10	1.60
Continental Refrigerator	1REN	Reach-in	21.38	1.40
Continental Refrigerator	1RENHD	Reach-in	21.11	1.46
Continental Refrigerator	1RESN	Reach-in	18.79	1.27
Continental Refrigerator	1RN	Reach-in	18.97	1.28
Continental Refrigerator	1RNPT	Pass-Through	22.03	1.54
Continental Refrigerator	1RXN	Reach-in	28.66	1.71
Continental Refrigerator	1RXNHD	Reach-in	28.36	1.74
Continental Refrigerator	1RXNPT	Pass-Through	33.16	1.90
Continental Refrigerator	1RXNPTHD	Pass-Through	32.70	1.96
Continental Refrigerator	1RXSN	Reach-in	22.63	1.50
Continental Refrigerator	1RXSNHD	Reach-in	22.06	1.47
Continental Refrigerator	2REN	Reach-in	48.64	2.06
Continental Refrigerator	2RENHD	Reach-in	48.33	2.25
Continental Refrigerator	2RENPT	Pass-Through	53.34	2.70
Continental Refrigerator	2RENPTHD	Pass-Through	53.00	2.88
Continental Refrigerator	2RESN	Reach-in	40.75	2.11
Continental Refrigerator	2RESNHD	Reach-in	40.42	2.22
Continental Refrigerator	2RN	Reach-in	43.45	2.13
Continental Refrigerator	2RNHD	Reach-in	43.03	2.15

Qualified Solid Door Refrigerators

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
Continental Refrigerator	2RNPT	Pass-Through	47.20	2.61
Continental Refrigerator	2RNPTH	Pass-Through	46.30	2.70
Continental Refrigerator	2RSEN	Reach-in	28.38	1.86
Continental Refrigerator	2RSN	Reach-in	36.45	1.88
Continental Refrigerator	2RSNHD	Reach-in	36.02	1.96
Continental Refrigerator	3REN	Reach-in	77.00	3.04
Continental Refrigerator	3RENHD	Reach-in	75.70	3.13
Continental Refrigerator	3RN	Reach-in	68.40	2.98
Continental Refrigerator	3RNHD	Reach-in	67.60	3.10
Continental Refrigerator	3RSN	Reach-in	55.60	2.97
Continental Refrigerator	BB79N	Milk or Beverage Cabinet	25.88	1.55
Continental Refrigerator	DIREN	Reach-in	21.80	1.21
Continental Refrigerator	DIRESN	Reach-in	19.19	1.36
Continental Refrigerator	D1RIN	Roll-In	32.00	2.03
Continental Refrigerator	D1RN	Reach-in	19.30	1.39
Continental Refrigerator	D1RNHD	Reach-in	19.25	1.24
Continental Refrigerator	D1RNPT	Pass-Through	22.03	1.54
Continental Refrigerator	D1RXN	Reach-in	29.17	1.75
Continental Refrigerator	D1RXNHD	Reach-in	28.87	1.80
Continental Refrigerator	D1RXNPT	Pass-Through	33.16	1.90
Continental Refrigerator	D1RXNPTH	Pass-Through	32.70	1.96
Continental Refrigerator	D1RXSN	Reach-in	22.36	1.43
Continental Refrigerator	D1RXSNHD	Reach-in	22.06	1.47
Continental Refrigerator	D2REN	Reach-in	49.10	2.42
Continental Refrigerator	D2RENHD	Reach-in	48.70	2.51
Continental Refrigerator	D2RENPT	Pass-Through	53.34	2.70
Continental Refrigerator	D2RENPTH	Pass-Through	53.80	2.88
Continental Refrigerator	D2RESN	Reach-in	41.10	2.14
Continental Refrigerator	D2RESNHD	Reach-in	40.70	2.23
Continental Refrigerator	D2RIN	Roll-In	62.94	3.22
Continental Refrigerator	D2RN	Reach-in	44.10	2.16
Continental Refrigerator	D2RNHD	Reach-in	43.70	2.23
Continental Refrigerator	D2RNPT	Pass-Through	47.20	2.61
Continental Refrigerator	D2RNPTH	Pass-Through	46.30	2.70
Continental Refrigerator	D2RSN	Reach-in	37.10	2.05
Continental Refrigerator	D2RSNHD	Reach-in	36.70	2.08
Continental Refrigerator	KC79N	Milk or Beverage Cabinet	25.88	1.55
Continental Refrigerator	MC4NSCW	Milk or Beverage Cabinet	18.20	0.88
Continental Refrigerator	MC5NSCW	Milk or Beverage Cabinet	23.60	1.17
Continental Refrigerator	RA118N	Reach-in	43.00	1.91
Continental Refrigerator	RA43N	Reach-in	12.20	1.05
Continental Refrigerator	RA60N	Reach-in	19.20	1.29
Continental Refrigerator	RA68N	Reach-in	22.90	1.53
Continental Refrigerator	RA93N	Reach-in	33.30	1.70
Continental Refrigerator	SW27N	Work-Top Table	6.66	0.86
Continental Refrigerator	SW32N	Work-Top Table	7.76	0.90
Continental Refrigerator	SW36N	Work-Top Table	8.27	0.91
Continental Refrigerator	SW48N	Work-Top Table	11.60	0.97
Continental Refrigerator	SW60N	Work-Top Table	14.50	1.04
Continental Refrigerator	SW72N	Work-Top Table	18.50	1.24

Qualified Solid Door Refrigerators

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
COTLIN	WX-49CR	Reach-in	43.50	1.48
Delfield	18648BSTMP*****	Work-Top Table	10.25	1.07
Delfield	18648BUCMP*****	Work-Top Table	10.25	1.07
Delfield	18660BSTMP*****	Work-Top Table	15.09	1.13
Delfield	18660BUCMP*****	Work-Top Table	15.09	1.13
Delfield	18672BSTMP*****	Work-Top Table	18.04	1.30
Delfield	18672BUCMP*****	Work-Top Table	18.04	1.30
Delfield	406P*****	Work-Top Table	5.70	0.81
Delfield	4424NP	Work-Top Table	6.35	0.76
Delfield	4427NP	Work-Top Table	7.35	0.82
Delfield	4432NP	Work-Top Table	9.01	0.92
Delfield	4448NP	Undercounter	14.23	0.97
Delfield	4460NP	Work-Top Table	18.32	1.31
Delfield	4464NP	Work-Top Table	19.55	1.19
Delfield	4472NP	Work-Top Table	22.11	1.23
Delfield	6025XL-S	Reach-in	18.90	1.18
Delfield	6025XL-SH	Reach-in	18.70	1.32
Delfield	6051XL-S	Reach-in	41.44	1.91
Delfield	6051XL-SH	Reach-in	41.37	2.20
Delfield	CSR2NP-S	Reach-in	39.76	2.08
Delfield	CSR2NP-SH	Reach-in	39.53	2.09
Delfield	CSRPT2P-SH	Pass-Through	49.38	2.48
Delfield	CSRR1IP-S	Reach-in	37.66	2.27
Delfield	D4424NP	Undercounter	6.35	0.76
Delfield	D4427NP	Undercounter	7.35	0.82
Delfield	D4432NP	Undercounter	9.01	0.92
Delfield	D4448NP	Undercounter	14.23	0.97
Delfield	D4460NP	Undercounter	18.32	1.31
Delfield	D4464NP*****	Work-Top Table	19.55	1.19
Delfield	D4472NP	Undercounter	22.11	1.23
Delfield	F17C52P*****	Work-Top Table	7.26	0.83
Delfield	F17C60P*****	Work-Top Table	9.08	0.93
Delfield	F17C62P*****	Work-Top Table	9.08	0.93
Delfield	F17C73P*****	Work-Top Table	12.03	1.10
Delfield	F17C75P*****	Work-Top Table	12.03	1.10
Delfield	F18WC44P*****	Work-Top Table	9.14	0.99
Delfield	F18WC48P*****	Work-Top Table	10.25	1.07
Delfield	F18WC60P*****	Work-Top Table	15.09	1.13
Delfield	F18WC68P*****	Work-Top Table	18.04	1.30
Delfield	F18WC72P*****	Work-Top Table	18.04	1.30
Delfield	F2952CP*****	Work-Top Table	7.26	0.83
Delfield	F2952P*****	Work-Top Table	7.26	0.83
Delfield	F2956CP*****	Work-Top Table	7.26	0.83
Delfield	F2956P*****	Work-Top Table	7.26	0.83
Delfield	F2960CP*****	Work-Top Table	9.08	0.93
Delfield	F2960P*****	Work-Top Table	9.08	0.93
Delfield	F2962CP*****	Work-Top Table	9.08	0.93
Delfield	F2962P*****	Work-Top Table	9.08	0.93
Delfield	F2973CP*****	Work-Top Table	12.03	1.10
Delfield	F2973P*****	Work-Top Table	12.03	1.10
Delfield	F2975CP*****	Work-Top Table	12.03	1.10
Delfield	F2975P*****	Work-Top Table	12.03	1.10
Delfield	GAR2NP-S*****	Reach-in	39.76	2.13
Delfield	GAR2NP-SH*****	Reach-in	39.53	2.09
Delfield	GAR2P-SH*****	Reach-in	45.58	2.48
Delfield	GARPT1P-S*****	Pass-Through	23.63	1.55
Delfield	GARPT2P-SH*****	Pass-Through	49.38	2.48
Delfield	GARPT2P-SH*****	Pass-Through	49.38	2.49

Qualified Solid Door Refrigerators

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
Delfield	GARRIIP-S*****	Reach-in	37.66	2.32
Delfield	GCR2P-SH	Reach-in	45.58	2.48
Delfield	ST4424NP	Work-Top Table	6.35	0.76
Delfield	ST4427NP	Work-Top Table	7.35	0.82
Delfield	ST4432NP	Work-Top Table	9.01	0.92
Delfield	ST4448NP	Work-Top Table	14.23	0.97
Delfield	ST4460NP	Work-Top Table	18.32	1.31
Delfield	ST4464NP*****	Work-Top Table	19.55	1.19
Delfield	ST4472NP	Work-Top Table	22.11	1.23
Delfield	STD4424NP	Undercounter	6.35	0.76
Delfield	STD4427NP	Undercounter	7.35	0.82
Delfield	STD4432NP	Undercounter	9.01	0.92
Delfield	STD4448NP	Work-Top Table	14.23	0.97
Delfield	STD4460NP	Undercounter	18.32	1.31
Delfield	STD4464NP*****	Work-Top Table	19.55	1.19
Delfield	STD4472NP	Undercounter	22.11	1.23
Desmon SPA	PGM07C-A	Other	19.42	1.34
Desmon SPA	PGM07C-C-A	Other	19.42	1.34
Desmon SPA	PGM14C-A	Other	42.32	1.58
Desmon SPA	PGM14C-C-A	Other	42.32	1.59
Desmon SPA	TGM2ETL	Reach-in	9.47	0.97
Desmon SPA	TGM3ETL	Other	14.85	1.10
Desmon SPA	TGM4ETL	Other	20.28	1.41
Dowell	R-60	Wedge Case	2.12	0.66
Duke	RUFP-48	Reach-in	13.98	1.16
Duke	SUB-RUFP-48	Reach-in	13.98	1.16
ECEVT	ST54BR	Reach-in	43.40	1.86
Everest Refrigeration	EBB48-24	Reach-in	12.71	1.03
Everest Refrigeration	EBSR2	Reach-in	40.03	2.41
Everest Refrigeration	ECB52-60D2	Reach-in	10.06	1.00
Everest Refrigeration	ESR1	Reach-in	21.24	1.37
Everest Refrigeration	ETBR1	Undercounter	7.47	0.54
Everest Refrigeration	ETBR2	Undercounter	13.70	1.11
Everest Refrigeration	ETBR2-D4	Undercounter	11.85	1.11
FERUEO	ST54BR	Reach-in	43.40	1.86
Fogel	HR15A	Reach-in	2.55	0.76
Fogel	MTR-27	Undercounter	6.33	0.86
Freezlabs	ST54BR	Reach-in	43.40	1.86
Fresh Town Co Ltd	FBC-95B	Undercounter	28.31	1.68
Fresh Town Co Ltd	FRB-23RS	Reach-in	18.22	1.25
Fresh Town Co Ltd	FRB-49RS	Reach-in	40.93	2.14
FWE	PTST-0911-56-1520-16HR	Reach-in	23.60	1.41
FWE	R-30	Reach-in	17.20	1.27
FWE	R-60	Reach-in	38.52	1.94
FWE	RBQ-96	Reach-in	29.14	1.41
FWE	SR-30	Reach-in	17.20	1.27
FWE	SR-30P	Reach-in	17.20	1.27
FWE	UHRS-0912-1216-48	Reach-in	19.13	1.27
FWE	UHRS-10	Reach-in	19.01	1.27
FWE	UHRS-10P	Reach-in	19.13	1.27
FWE	URS-10	Reach-in	19.71	1.27
FWE	URS-10-GN	Reach-in	20.75	1.27
FWE	URS-10-GND	Reach-in	20.75	1.27
FWE	URS-10-GNP	Reach-in	20.75	1.27
FWE	URS-10-GNS	Reach-in	20.75	1.27
FWE	URS-10D	Reach-in	19.71	1.27
FWE	URS-10P	Reach-in	19.71	1.27
FWE	URS-10S	Reach-in	19.71	1.27

Qualified Solid Door Refrigerators

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).

NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
FWE	URS-16	Reach-in	31.88	1.94
FWE	URS-16-GN	Reach-in	31.88	1.94
FWE	URS-20	Reach-in	38.70	1.94
FWE	URS-20-GN	Reach-in	38.70	1.94
Galaxy	177GRI18RW	Reach-in	18.01	1.08
Hoshizaki	DD24*	Other	7.46	0.84
Hoshizaki	HR15A	Reach-in	2.54	0.76
Hoshizaki	PT1A-FS-FS	Pass-Through	24.20	1.31
Hoshizaki	PT1A-HS-HS	Pass-Through	24.20	1.31
Hoshizaki	R1A-FS***	Reach-in	23.11	1.25
Hoshizaki	R1A-HS***	Reach-in	23.11	1.25
Hoshizaki	ULR46B-***	Undercounter	11.78	0.92
Hoshizaki	ULR60B-***	Undercounter	17.22	1.15
Hoshizaki	ULR60B-****	Undercounter	17.22	1.26
Hoshizaki	ULR67B-***	Undercounter	19.97	1.14
Hoshizaki	ULR67B-****	Undercounter	19.97	1.33
Hoshizaki	ULR93B-****	Undercounter	30.17	1.87
Hoshizaki	UR27B-***	Undercounter	6.21	0.65
Hoshizaki	UR27B-****	Undercounter	6.21	0.65
Hoshizaki	UR36B-***	Undercounter	8.64	0.69
Hoshizaki	UR36B-****	Undercounter	8.64	0.69
Hoshizaki	UR48B-***	Undercounter	12.00	1.05
Hoshizaki	UR48B-****	Undercounter	12.00	1.05
Hoshizaki	UR60B-***	Undercounter	15.10	0.94
Hoshizaki	UR60B-****	Undercounter	15.10	0.94
Hoshizaki	UR72B-***	Undercounter	18.27	1.12
Hoshizaki	UR72B-****	Undercounter	18.27	1.12
Hoshizaki	WLR46B-***	Work-Top Table	11.78	0.92
Hoshizaki	WLR60B-***	Work-Top Table	17.22	1.15
Hoshizaki	WLR60B-****	Work-Top Table	17.22	1.26
Hoshizaki	WLR67B-***	Work-Top Table	19.97	1.14
Hoshizaki	WLR67B-****	Work-Top Table	19.97	1.33
Hoshizaki	WLR93B-****	Work-Top Table	30.17	1.87
Hoshizaki	WR27B-***	Work-Top Table	6.21	0.65
Hoshizaki	WR27B-****	Work-Top Table	6.21	0.65
Hoshizaki	WR36B-***	Work-Top Table	8.64	0.69
Hoshizaki	WR36B-****	Work-Top Table	8.64	0.69
Hoshizaki	WR48B-***	Work-Top Table	12.00	1.05
Hoshizaki	WR48B-****	Work-Top Table	12.00	1.05
Hoshizaki	WR60B-***	Work-Top Table	15.10	0.94
Hoshizaki	WR60B-****	Work-Top Table	15.10	0.94
Hoshizaki	WR72B-***	Work-Top Table	18.27	1.12
Hoshizaki	WR72B-****	Work-Top Table	18.27	1.12
IM2	EVC1.5 R6	Reach-in	1.62	0.45
Imbera	RIB23-HC-B1	Reach-in	23.40	1.34
Imbera	VC31-H2S2	Reach-in	47.60	2.51
JonesZylon	JZHR-40-HC	Reach-in	23.60	1.41
JonesZylon	JZR-10UBT	Reach-in	19.34	1.27
JonesZylon	JZR-10UBTD	Reach-in	19.34	1.27
JonesZylon	JZR-168	Reach-in	27.42	1.41
JonesZylon	JZR-168-XL	Reach-in	28.18	1.41
JonesZylon	JZR-192-XL	Reach-in	31.88	1.90
JonesZylon	JZRR-120	Reach-in	28.52	1.41
JonesZylon	JZRR-120HD	Reach-in	28.52	1.41
JonesZylon	JZRR-144	Reach-in	38.70	1.94
JonesZylon	JZRR-144-RH	Reach-in	38.70	1.94
JonesZylon	JZRR-144HD	Reach-in	38.70	1.94
JonesZylon	JZRR-144HD-RH	Reach-in	38.70	1.94

Qualified Solid Door Refrigerators

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
Kegco	SLK-15BBR	Undercounter	2.86	0.50
Kegco	SLK-15BSR	Undercounter	2.86	0.50
Kelvinator COMMERCIAL	KCHMC34	Milk or Beverage Cabinet	12.40	0.81
Kelvinator COMMERCIAL	KCHMC49	Milk or Beverage Cabinet	18.40	1.09
Kelvinator COMMERCIAL	KCHMC58	Milk or Beverage Cabinet	22.10	1.14
Kelvinator COMMERCIAL	KCHRI25R1DRE	Reach-in	18.20	1.11
Kelvinator COMMERCIAL	KCHRI25R1DRE	Reach-in	18.20	1.11
Kelvinator COMMERCIAL	KCHRI27R1DRE	Reach-in	18.10	0.90
Kelvinator COMMERCIAL	KCHRI27R2HDR	Reach-in	18.10	0.90
Kelvinator COMMERCIAL	KCHRI54R2DRE	Reach-in	41.60	1.36
Kelvinator COMMERCIAL	KCHRI54R4HDR	Reach-in	41.60	1.36
Kelvinator COMMERCIAL	KCHRI81R3DR	Reach-in	66.00	2.03
Kelvinator COMMERCIAL	KCHUC27.2DR-32	Undercounter	5.40	0.77
Kelvinator COMMERCIAL	KCHUC27R-32	Undercounter	5.40	0.77
Kelvinator COMMERCIAL	KCHUC36R-32	Undercounter	7.50	0.74
Kelvinator COMMERCIAL	KCHUC48R-32	Undercounter	10.10	0.92
Kelvinator COMMERCIAL	KCHUC60R-32	Undercounter	13.20	1.09
Kelvinator COMMERCIAL	KCHUCWT36R	Undercounter	7.50	0.74
KERONG	BC-136CT	Reach-in	4.80	0.58
KERONG	BC-89F	Reach-in	3.13	0.53
KUTANO	KUTR1SS**	Reach-in	20.08	1.04
KUTANO	KUTR2SS**	Reach-in	45.40	1.84
LCEKY	ST54BR	Reach-in	43.40	1.86
Main Street	829BMR23R	Reach-in	20.60	1.28
Main Street	829BMR49R	Reach-in	41.33	2.36
Master-Bilt	MBR23-SH	Reach-in	19.44	1.37
Master-Bilt	R23-SH	Reach-in	19.44	1.37
Migali	C-1R-HC	Reach-in	21.40	1.27
Migali	C-2R-HC	Reach-in	42.18	2.06
Migali	C-3R-HC	Reach-in	64.88	2.40
Migali	C-DD23-1-HC	Other	7.80	1.00
Migali	C-HBC65-HC	Undercounter	17.50	1.09
Migali	C-U27R-HC	Undercounter	7.15	0.83
Migali	C-U48R-HC	Undercounter	13.38	1.01
Migali	C-U60R-HC	Undercounter	17.20	1.19
Migali	C-U72R-HC	Undercounter	21.13	1.26
Norlake	AR124***/O-A	Milk or Beverage Cabinet	17.82	1.16
Norlake	AR162***/O-A	Milk or Beverage Cabinet	23.50	1.25
Norlake	AR164***/O-A	Milk or Beverage Cabinet	23.50	1.32
Norlake	NLR23-SH	Reach-in	19.44	1.37
Norlake	NR522**S/OX	Reach-in	51.45	2.98
Norlake	NR803**S/OX	Reach-in	79.85	3.51
Norlake	NR806**S/OX	Reach-in	79.52	3.36
Norlake	R23-SH	Reach-in	19.44	1.37
OMCAN INC	BB-CN-0017-HC	Reach-in	17.50	1.08
OMCAN INC	RE-CN-0006-HC	Undercounter	5.50	0.53

Qualified Solid Door Refrigerators

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
OMCAN INC	RE-CN-0021-HC	Reach-in	20.60	1.17
Perlick	BBR24-RO-*	Reach-in	6.74	0.89
Perlick	HB24BS4S-**-*****	Undercounter	4.81	0.83
Perlick	HB24RS4S-**-*****	Undercounter	4.81	0.83
Perlick	HB24WS4S-**-*****	Undercounter	4.81	0.83
Perlick	HC24RS4S-**-*****	Undercounter	5.22	0.76
Perlick	HC24WS4S-**-*****	Undercounter	5.22	0.76
Perlick	HD24RS4S-**-*****	Undercounter	3.20	0.68
Perlick	HD24WS4S-**-*****	Undercounter	3.20	0.68
Polarman	PLM-19RS	Reach-in	13.92	0.90
Polarman	PLM-27RS	Reach-in	18.12	0.90
Polarman	PLM-35RS	Reach-in	28.71	1.13
Polarman	PLM-54RS	Reach-in	41.61	1.24
Polarman	PLM-81R	Reach-in	66.01	1.65
Polarman	PLM-BC4	Undercounter	29.11	1.60
Primoris	FB49R	Reach-in	43.40	2.34
Pro-Kold	VC31-H2S2	Reach-in	47.60	2.51
QBD	RUC27-HC	Undercounter	5.55	0.69
RefrigerationX	XBD-1SB-N6	Reach-in	10.81	1.08
RefrigerationX	XR19-1-N6	Reach-in	18.46	0.94
RefrigerationX	XR24-1-N6	Reach-in	21.94	1.08
RefrigerationX	XR47-2-N6	Reach-in	42.27	1.61
RefrigerationX	XUR-28-N6	Undercounter	7.11	0.69
RefrigerationX	XUR-36-N6	Undercounter	9.74	0.86
RefrigerationX	XUR-48-N6	Undercounter	13.24	1.10
RefrigerationX	XUR-60-N6	Undercounter	16.86	1.20
Silver King	SK2SB	Other	4.30	0.74
Silver King	SKDL18-ED***	Undercounter	3.87	0.50
Silver King	SKMAJ2	Milk or Beverage Cabinet	4.01	0.33
Silver King	SKR24A-ES***	Reach-in	4.50	0.78
Silver King	SKSD	Other	3.86	0.43
Summit Commercial	ACRR432L***	Reach-in	38.61	2.10
Summit Commercial	ADA2DOS	Reach-in	4.80	0.58
Summit Commercial	ADRD24	Reach-in	4.80	0.58
Summit Commercial	ADRD25OS	Reach-in	4.80	0.58
Summit Commercial	BAR197	Reach-in	3.13	0.53
Summit Commercial	BAR198S	Reach-in	3.13	0.53
Summit Commercial	BCR199	Reach-in	3.13	0.53
Summit Commercial	BCR19S	Reach-in	3.13	0.53
Summit Commercial	FF19S	Reach-in	3.13	0.53
Summit Commercial	FFAR25L*7*	Other	1.70	0.66
Summit Commercial	LADA2D24	Reach-in	4.80	0.58
Summit Commercial	R17FF*	Reach-in	16.50	1.20
Summit Commercial	SBC635M*7*	Undercounter	5.60	0.85
Summit Commercial	SBC695OS*	Undercounter	6.05	0.85
Summit Commercial	SBC696OS*	Undercounter	6.05	0.85
Summit Commercial	SCRR231	Reach-in	20.60	1.01
Summit Commercial	SCRR232**	Reach-in	19.53	1.03
Summit Commercial	SCRR232LH**	Reach-in	19.53	1.03
Summit Commercial	SCRR432***	Reach-in	38.61	2.10
Summit Commercial	SCRR491	Reach-in	41.30	2.07
Summit Commercial	SCRR492**	Reach-in	42.24	1.83
Summit Commercial	SCRR492LH**	Reach-in	42.24	1.83
Summit Commercial	SCRR722**	Reach-in	60.84	2.44
Summit Commercial	SCRR722LH**	Reach-in	60.84	2.44
Summit Commercial	SP6DS24ADA	Reach-in	4.80	0.58

Qualified Solid Door Refrigerators

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
Summit Commercial	SPR196OS	Reach-in	3.13	0.53
Summit Commercial	SPR2DOSADA	Reach-in	4.80	0.58
Traulsen	AHT232WUT-FHS-eS	Reach-in	50.53	2.95
Traulsen	AHT232WUT-HHS-eS	Reach-in	50.40	2.94
Traulsen	AHT332WUT-FHS-eS	Reach-in	77.45	3.56
Traulsen	AHT332WUT-HHS-eS	Reach-in	77.26	3.56
Traulsen	G30000	Reach-in	69.15	3.37
Traulsen	G30000-032	Reach-in	69.15	3.37
Traulsen	G30001	Reach-in	69.15	3.37
Traulsen	G30001-032	Reach-in	69.15	3.37
Traulsen	G30002	Reach-in	69.15	3.37
Traulsen	G30002-032	Reach-in	69.15	3.37
Traulsen	G30003	Reach-in	69.15	3.37
Traulsen	G30003-032	Reach-in	69.15	3.37
Traulsen	G30010	Reach-in	69.35	3.38
Traulsen	G30010-032	Reach-in	69.35	3.38
Traulsen	G30011	Reach-in	69.35	3.38
Traulsen	G30011-032	Reach-in	69.35	3.38
Traulsen	G30012	Reach-in	69.35	3.38
Traulsen	G30012-032	Reach-in	69.35	3.38
Traulsen	G30013	Reach-in	69.35	3.38
Traulsen	G30013-032	Reach-in	69.35	3.38
Traulsen	RHT232WUT-FHS-eS	Reach-in	50.53	2.95
Traulsen	RHT232WUT-HHS-eS	Reach-in	50.40	2.94
Traulsen	RHT332WUT-FHS-eS	Reach-in	77.45	3.56
Traulsen	RHT332WUT-HHS-eS	Reach-in	77.26	3.56
True	STA1R-1S-HC	Reach-in	23.35	1.34
True	STA1R-2HS-HC	Reach-in	22.00	1.34
True	STA1RPT-2HS-2HS-HC	Pass-Through	23.35	1.34
True	STA2R-2S-HC	Reach-in	46.86	2.23
True	STG1R-1S-HC	Reach-in	23.35	1.34
True	STG1R-2HS-HC	Reach-in	22.00	1.34
True	STG1RPT-2HS-2HS-HC	Pass-Through	23.35	1.34
True	STG2R-2S-HC	Reach-in	46.86	2.23
True	STR1R-1S-HC	Reach-in	23.35	1.34
True	STR1R-2HS-HC	Reach-in	22.00	1.34
True	STR1RPT-2HS-2HS-HC	Pass-Through	23.35	1.34
True	STR2R-2S-HC	Reach-in	46.86	2.23
True	T-12-HC	Reach-in	11.22	0.76
True	T-15-2-HC	Reach-in	12.46	0.81
True	T-19-HC	Reach-in	14.79	0.92
True	T-23-2-HC	Reach-in	20.13	1.36
True	T-23-HC	Reach-in	20.26	1.20
True	T-23PT-HC	Pass-Through	21.23	1.02
True	T-49-HC	Reach-in	43.26	2.57
True	TBB-1-HC	Undercounter	7.86	0.93
True	TBB-1-S-HC	Undercounter	7.86	0.93
True	TBB-2-HC	Undercounter	19.51	1.30
True	TBB-2-S-HC	Undercounter	19.51	1.30
True	TBB-3-HC	Undercounter	23.54	1.42
True	TBB-3-S-HC	Undercounter	23.54	1.42
True	TBR48-RISZ1-L-B-SG-1	Undercounter	11.65	0.86
True	TBR48-RISZ1-L-B-SS-1	Undercounter	11.65	0.71
True	TBR48-RISZ1-L-S-SG-1	Undercounter	11.65	0.86
True	TBR48-RISZ1-L-S-SS-1	Undercounter	11.65	0.71
True	TBR52-RISZ1-L-B-SG-1	Undercounter	13.11	0.88
True	TBR52-RISZ1-L-B-SS-1	Undercounter	13.11	0.82
True	TBR52-RISZ1-L-S-SG-1	Undercounter	13.11	0.88

Qualified Solid Door Refrigerators

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
True	TBR52-RISZ1-L-S-SS-1	Undercounter	13.11	0.82
True	TBR60-RISZ1-L-B-SG-1	Undercounter	16.01	1.17
True	TBR60-RISZ1-L-B-SS-1	Undercounter	16.01	1.02
True	TBR60-RISZ1-L-S-SG-1	Undercounter	16.01	1.17
True	TBR60-RISZ1-L-S-SS-1	Undercounter	16.01	1.02
True	TBR72-RISZ1-L-B-SSG-1	Undercounter	20.16	1.31
True	TBR72-RISZ1-L-B-SSS-1	Undercounter	20.16	1.03
True	TBR72-RISZ1-L-S-SSG-1	Undercounter	20.16	1.31
True	TBR72-RISZ1-L-S-SSS-1	Undercounter	20.16	1.03
True	TDD-1-HC	Other	7.86	0.93
True	TDD-1-S-HC	Other	7.86	0.93
True	TDD-2-HC	Other	19.51	1.30
True	TDD-2-S-HC	Other	19.51	1.30
True	TDD-2CT-HC	Other	19.51	1.30
True	TDD-2CT-S-HC	Other	19.51	1.30
True	TDD-3-HC	Reach-in	23.54	1.42
True	TDD-3-S-HC	Reach-in	23.54	1.42
True	TDD-3CT-HC	Reach-in	23.54	1.42
True	TDD-3CT-S-HC	Reach-in	23.54	1.42
True	TDR48-RISZ1-L-B-SG-1	Undercounter	11.65	0.86
True	TDR48-RISZ1-L-B-SS-1	Undercounter	11.65	0.71
True	TDR48-RISZ1-L-S-SG-1	Undercounter	11.65	0.86
True	TDR48-RISZ1-L-S-SS-1	Undercounter	11.65	0.71
True	TDR52-RISZ1-L-B-SG-1	Undercounter	13.11	0.88
True	TDR52-RISZ1-L-B-SS-1	Undercounter	13.11	0.82
True	TDR52-RISZ1-L-S-SG-1	Undercounter	13.11	0.88
True	TDR52-RISZ1-L-S-SS-1	Undercounter	13.11	0.82
True	TDR60-RISZ1-L-B-SG-1	Undercounter	16.01	1.17
True	TDR60-RISZ1-L-B-SS-1	Undercounter	16.01	1.02
True	TDR60-RISZ1-L-S-SG-1	Undercounter	16.01	1.17
True	TDR60-RISZ1-L-S-SS-1	Undercounter	16.01	1.02
True	TDR72-RISZ1-L-B-SSG-1	Undercounter	20.16	1.31
True	TDR72-RISZ1-L-B-SSS-1	Undercounter	20.16	1.03
True	TDR72-RISZ1-L-S-SSG-1	Undercounter	20.16	1.31
True	TDR72-RISZ1-L-S-SSS-1	Undercounter	20.16	1.03
True	TG1R-1S-HC	Reach-in	27.33	1.28
True	TG2R-2S-HC	Reach-in	50.59	2.65
True	TMC-34-DS-HC	Milk or Beverage Cabinet	11.70	0.72
True	TMC-34-DS-S-HC	Milk or Beverage Cabinet	11.70	0.72
True	TMC-34-DS-S-SS-HC	Milk or Beverage Cabinet	11.70	0.72
True	TMC-34-DS-SS-HC	Milk or Beverage Cabinet	11.70	0.72
True	TMC-34-HC	Milk or Beverage Cabinet	11.06	0.69
True	TMC-34-S-HC	Milk or Beverage Cabinet	11.06	0.69
True	TMC-34-S-SS-HC	Milk or Beverage Cabinet	11.06	0.69

Qualified Solid Door Refrigerators

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
True	TMC-34-SS-HC	Milk or Beverage Cabinet	11.06	0.69
True	TMC-49-DS-HC	Milk or Beverage Cabinet	17.24	0.96
True	TMC-49-DS-S-HC	Milk or Beverage Cabinet	17.24	0.96
True	TMC-49-DS-S-SS-HC	Milk or Beverage Cabinet	17.24	0.96
True	TMC-49-DS-SS-HC	Milk or Beverage Cabinet	17.24	0.96
True	TMC-49-HC	Milk or Beverage Cabinet	16.61	1.06
True	TMC-49-S-HC	Milk or Beverage Cabinet	16.61	1.05
True	TMC-49-S-SS-HC	Milk or Beverage Cabinet	16.61	1.05
True	TMC-49-SS-HC	Milk or Beverage Cabinet	16.61	1.05
True	TMC-58-DS-HC	Milk or Beverage Cabinet	21.11	0.97
True	TMC-58-DS-S-HC	Milk or Beverage Cabinet	21.11	0.97
True	TMC-58-DS-S-SS-HC	Milk or Beverage Cabinet	21.11	0.97
True	TMC-58-DS-SS-HC	Milk or Beverage Cabinet	21.11	0.97
True	TMC-58-HC	Milk or Beverage Cabinet	19.94	1.25
True	TMC-58-S-HC	Milk or Beverage Cabinet	19.94	1.25
True	TMC-58-S-SS-HC	Milk or Beverage Cabinet	19.94	1.25
True	TMC-58-SS-HC	Milk or Beverage Cabinet	19.94	1.25
True	TS-23-2-HC	Reach-in	20.13	1.36
True	TS-23-HC	Reach-in	20.26	1.20
True	TS-23PT-HC	Pass-Through	21.23	1.02
True	TS-49-HC	Reach-in	43.26	2.57
True	TUC-24-HC	Undercounter	4.97	0.59
True	TUC-24-HC~SPEC3	Undercounter	4.93	0.59
True	TUC-27-ADA-HC	Undercounter	7.07	0.93

Qualified Solid Door Refrigerators

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
True	TUC-27-ADA-HC~SPEC3	Undercounter	7.07	0.93
True	TUC-27-HC	Undercounter	7.07	0.93
True	TUC-27-HC~SPEC3	Undercounter	7.07	0.93
True	TUC-27-LP-HC	Undercounter	7.07	0.93
True	TUC-27-LP-HC~SPEC3	Undercounter	7.07	0.93
True	TUC-27-LP-K-HC	Undercounter	6.74	0.87
True	TUC-48-ADA-HC	Undercounter	13.35	1.12
True	TUC-48-ADA-HC~SPEC3	Undercounter	13.35	1.12
True	TUC-48-HC	Undercounter	13.35	1.12
True	TUC-48-HC~SPEC3	Undercounter	13.35	1.12
True	TUC-48-LP-HC	Undercounter	13.35	1.12
True	TUC-48-LP-HC~SPEC3	Undercounter	13.35	1.12
True	TUC-48-LP-K-HC	Undercounter	12.76	0.99
True	TUC-93-HC	Undercounter	31.34	1.86
True	TUC-93-HC~SPEC3	Undercounter	31.34	1.86
True	TUC-93-LP-HC	Undercounter	31.34	1.86
True	TUC-93-LP-HC~SPEC3	Undercounter	31.34	1.86
True	TWT-27-ADA-HC	Work-Top Table	7.07	0.93
True	TWT-27-ADA-HC~SPEC3	Work-Top Table	7.07	0.93
True	TWT-27-HC	Work-Top Table	7.07	0.93
True	TWT-27-HC~SPEC3	Work-Top Table	7.07	0.93
True	TWT-48-ADA-HC	Work-Top Table	13.35	1.12
True	TWT-48-ADA-HC~SPEC3	Work-Top Table	13.35	1.12
True	TWT-48-HC	Work-Top Table	13.35	1.12
True	TWT-48-HC~SPEC3	Work-Top Table	13.35	1.12
True	TWT-93-HC	Work-Top Table	31.34	1.86
True	TWT-93-HC~SPEC3	Work-Top Table	31.34	1.86
Turbo Air	ER19-1-N6-V	Reach-in	18.46	0.94
Turbo Air	ER24-1-N6-V	Reach-in	21.94	1.08
Turbo Air	ER47-2-N	Reach-in	42.10	2.42
Turbo Air	ER47-2-N6-V	Reach-in	42.27	1.61
Turbo Air	ER47-4-N	Reach-in	42.10	2.42
Turbo Air	EUR-28-N6	Reach-in	6.76	0.75
Turbo Air	EUR-28-N6-V	Undercounter	7.11	0.69
Turbo Air	EUR-36-N6-V	Undercounter	9.74	0.86
Turbo Air	EUR-48-N6	Reach-in	12.18	0.93
Turbo Air	EUR-48-N6-V	Undercounter	13.24	1.10
Turbo Air	EUR-60-N6	Reach-in	17.22	1.11
Turbo Air	EUR-60-N6-V	Undercounter	16.86	1.20
Turbo Air	JUR-36-N6	Reach-in	6.37	0.73
Turbo Air	JUR-36N	Reach-in	5.66	0.80
Turbo Air	JUR-36S-N6	Reach-in	5.66	0.63
Turbo Air	JUR-48-N6	Reach-in	9.93	0.98
Turbo Air	JUR-48N	Reach-in	9.04	0.98
Turbo Air	JUR-48S-N6	Reach-in	8.27	0.74
Turbo Air	JUR-60S-N6	Reach-in	11.31	1.04
Turbo Air	JUR-72-N6	Reach-in	17.20	1.13
Turbo Air	JUR-72S-N6	Reach-in	15.17	1.01
Turbo Air	M3R24-1-N	Reach-in	21.70	0.94
Turbo Air	M3R24-2-N	Reach-in	21.70	0.94
Turbo Air	M3R47-2-N	Reach-in	42.10	1.65
Turbo Air	M3R47-4-N	Reach-in	42.10	1.65
Turbo Air	M3R72-3-N	Reach-in	65.88	2.35
Turbo Air	M3R72-6-N	Reach-in	65.88	2.35
Turbo Air	MUR-20S-N6	Reach-in	2.30	0.82
Turbo Air	MUR-28	Reach-in	6.80	0.84
Turbo Air	MUR-28L	Reach-in	6.80	0.84
Turbo Air	MUR-28L-N6	Reach-in	6.18	0.75

Qualified Solid Door Refrigerators

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
Turbo Air	MUR-36-N6	Reach-in	9.00	0.91
Turbo Air	MUR-36L-N6	Reach-in	8.36	0.91
Turbo Air	MWR-20S-N6	Reach-in	2.30	0.82
Turbo Air	PRO-26-2R-N	Reach-in	25.40	1.58
Turbo Air	PRO-26R-N	Reach-in	25.40	1.58
Turbo Air	PRO-26R-RI-N	Reach-in	39.91	1.83
Turbo Air	PRO-50-4R-N	Reach-in	48.70	2.43
Turbo Air	PRO-50R-N	Reach-in	48.70	2.43
Turbo Air	PRO-77-6R-N	Reach-in	75.04	2.99
Turbo Air	PRO-77R-N	Reach-in	75.04	2.99
Turbo Air	TBB-24-48SBD-N6	Reach-in	12.20	1.05
Turbo Air	TBB-24-48SSD-N6	Reach-in	12.20	1.05
Turbo Air	TBB-24-60SBD-N6	Reach-in	16.46	1.20
Turbo Air	TBB-24-60SSD-N6	Reach-in	16.46	1.20
Turbo Air	TBB-24-72SBD-N6	Reach-in	20.62	1.39
Turbo Air	TBB-2SBD-N6	Reach-in	19.00	1.28
Turbo Air	TBB-2SSD-N6	Reach-in	19.00	1.28
Turbo Air	TBB-3SB-N6	Reach-in	23.00	1.59
Turbo Air	TBB-3SBD-N6	Reach-in	23.00	1.36
Turbo Air	TBB-4SBD-N	Reach-in	36.47	1.84
Turbo Air	TBD-2SB	Reach-in	20.90	1.40
Turbo Air	TBD-2SB-N6	Reach-in	17.12	1.15
Turbo Air	TBD-2SBD-N6	Reach-in	17.12	1.25
Turbo Air	TBD-2SD	Reach-in	20.90	1.40
Turbo Air	TBD-2SD-N6	Reach-in	17.12	1.15
Turbo Air	TBD-2SDD-N6	Reach-in	17.12	1.25
Turbo Air	TBD-3S*D-N6	Reach-in	21.19	1.34
Turbo Air	TBD-3SBD-N	Reach-in	21.19	1.50
Turbo Air	TBD-3SDD-N	Reach-in	21.19	1.50
Turbo Air	TBD-4SB-N	Reach-in	29.64	1.76
Turbo Air	TBD-4SBD-N	Reach-in	29.64	1.81
Turbo Air	TBD-4SD-N	Reach-in	29.64	1.76
Turbo Air	TBD-4SDD-N	Reach-in	29.64	1.81
Turbo Air	TCB-2SB-N6	Reach-in	20.90	1.33
Turbo Air	TCB-2SBD-N6	Reach-in	20.90	1.23
Turbo Air	TCB-2SD-N6	Reach-in	20.90	1.33
Turbo Air	TCB-2SDD-N6	Reach-in	20.90	1.23
Turbo Air	TCB-3SB-N6	Reach-in	25.40	1.13
Turbo Air	TCB-3SBD-N6	Reach-in	25.40	1.24
Turbo Air	TCB-3SD-N6	Reach-in	25.40	1.13
Turbo Air	TCB-3SDD-N6	Reach-in	25.40	1.24
Turbo Air	TCB-4SB-N	Reach-in	36.47	1.53
Turbo Air	TCB-4SBD-N	Reach-in	36.47	1.68
Turbo Air	TCB-4SD-N	Reach-in	36.47	1.53
Turbo Air	TCB-4SDD-N	Reach-in	36.47	1.68
Turbo Air	TMKC-34-2-SS-N6	Milk or Beverage Cabinet	12.21	0.73
Turbo Air	TMKC-34-2-WS-N6	Milk or Beverage Cabinet	12.21	0.73
Turbo Air	TMKC-49-2-SS-N6	Milk or Beverage Cabinet	18.30	0.87
Turbo Air	TMKC-49-2-WS-N6	Milk or Beverage Cabinet	18.30	0.87

Qualified Solid Door Refrigerators

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
Turbo Air	TMKC-58-2-SS-N6	Milk or Beverage Cabinet	21.98	1.07
Turbo Air	TMKC-58-2-WS-N6	Milk or Beverage Cabinet	21.98	1.07
Turbo Air	TSR-23SD-N6	Reach-in	19.30	0.79
Turbo Air	TSR-23SD-N6-L	Reach-in	19.30	0.79
Turbo Air	TSR-35SD-N	Reach-in	29.00	1.66
Turbo Air	TSR-35SD-N6	Reach-in	29.19	1.45
Turbo Air	TSR-49SD	Reach-in	41.10	2.45
Turbo Air	TSR-49SD-N6	Reach-in	42.69	1.37
Turbo Air	TSR-72SD-N	Reach-in	64.10	2.33
Turbo Air	TUR-36SD-N6	Reach-in	9.00	0.91
Turbo Air	TWR-36SD-N6	Reach-in	9.00	0.91
Turbo Air	XBD-1SB-N6	Reach-in	10.81	1.08
Turbo Air	XBR24-1-N6	Reach-in	21.94	1.08
Turbo Air	XBR47-2-N6	Reach-in	42.27	1.61
Turbo Air	XR19-1-N6	Reach-in	18.46	0.94
Turbo Air	XR24-1-N6	Reach-in	21.94	1.08
Turbo Air	XR47-2-N6	Reach-in	42.27	1.61
Turbo Air	XUR-28-N6	Undercounter	7.11	0.69
Turbo Air	XUR-36-N6	Undercounter	9.74	0.86
Turbo Air	XUR-48-N6	Undercounter	13.24	1.10
Turbo Air	XUR-60-N6	Undercounter	16.86	1.20
U-Line	UCFZ553-SS71A	Other	42.32	1.59
U-Line	UCRE515-SS32A	Reach-in	3.70	0.75
U-Line	UCRE515-SS33A	Reach-in	3.70	0.75
U-Line	UCRE518-SS32A	Reach-in	3.70	0.75
U-Line	UCRE518-SS33A	Reach-in	3.70	0.75
U-Line	UCRE524-SS32A	Reach-in	5.20	0.90
U-Line	UCRE524-SS33A	Reach-in	5.20	0.90
U-Line	UCWC515-SS32A	Reach-in	3.70	0.75
U-Line	UCWC515-SS33A	Reach-in	3.70	0.75
U-Line	UCWC518-SS32A	Reach-in	3.70	0.75
U-Line	UCWC518-SS33A	Reach-in	3.70	0.75
U-Line	UCWC524-SS32A	Reach-in	5.20	0.90
U-Line	UCWC524-SS33A	Reach-in	5.20	0.90
US Refrigeration	USBV-48R	Reach-in	43.46	2.34
US Refrigeration	USTV-48R	Reach-in	41.99	2.34
US Refrigeration	USUV-28	Undercounter	7.15	0.90
US Refrigeration	USWT-28	Work-Top Table	7.15	0.90
Utility Refrigerator	R-30-SS-1S-N-C	Reach-in	19.45	1.41
Valiance by Hoshizaki	VR1A-FS	Reach-in	19.10	0.96
Valiance by Hoshizaki	VR2A-FS	Reach-in	43.00	1.48
Valiance by Hoshizaki	VUR27A	Reach-in	7.00	0.85
Valiance by Hoshizaki	VUR48A	Reach-in	12.00	0.75
Victory	VERS-2D-HD-HC*****	Reach-in	45.20	2.57
Victory	VERS-2D-SD-HC*****	Reach-in	45.20	2.57
Victory	VERSA-2D-HD-HC*****	Reach-in	45.20	2.57
Victory	VERSA-2D-SD-HC*****	Reach-in	45.20	2.57
Victory	VMCF49-1-S-HC*****	Milk or Beverage Cabinet	18.26	1.16
Victory	VMCF58-1-S-HC*****	Milk or Beverage Cabinet	24.00	1.33
Victory	VUR32HC*****	Undercounter	7.22	0.95

Qualified Solid Door Refrigerators

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).

NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
Victory	VURD32HC*****	Undercounter	7.22	0.95
Victory	VURD48HC*****	Undercounter	11.82	0.85
Victory	VWR32HC*****	Work-Top Table	7.22	0.95
Victory	VWRD32HC*****	Work-Top Table	7.22	0.95
Victory	VWRD48HC*****	Work-Top Table	11.82	0.85
Whynter	BEF-286SB	Reach-in	2.86	0.50
Whynter	BOR-53024-SSW	Undercounter	5.30	0.72
Whynter	TBR-182RS	Reach-in	1.80	0.58
Whynter	TBR-185SR	Reach-in	1.80	0.58
Zhejiang Meisda Refrigeration Technology Co.,Ltd.	SC68	Reach-in	2.30	0.69

Qualified Glass Door Freezers

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
ACCUCOLD	SPF5*	Reach-in	3.20	1.99
AHT	KINLEY XL 210 NAM2	Reach-in	26.08	8.38
AHT	KINLEY XL 250 NAM2	Reach-in	31.36	9.52
Beverage-Air	CF3HC-1-W	Reach-in	2.90	2.61
Beverage-Air	CTIHC-1*G*****	Reach-in	22.37	7.50
Beverage-Air	UCF20HC-25-*****	Undercounter	2.27	2.48
Beverage-Air	UCF24AHC-25*****	Undercounter	4.90	2.71
Beverage-Air	UCF27AHC-25*****	Undercounter	6.15	3.73
Beverage-Air	UCF32AHC-25*****	Undercounter	7.22	3.38
Beverage-Air	WTF20HC-25-*****	Work-Top Table	2.27	2.48
Beverage-Air	WTF24AHC-25*****	Work-Top Table	4.90	2.71
Beverage-Air	WTF27AHC-25*****	Work-Top Table	6.15	3.73
Beverage-Air	WTF32AHC-25*****	Work-Top Table	7.22	3.38
Continental Refrigerator	1FENG	Reach-in	21.38	7.06
Continental Refrigerator	1FENG	Reach-in	21.11	7.11
Continental Refrigerator	1FESNG	Reach-in	18.79	6.50
Continental Refrigerator	1FESNG	Reach-in	18.52	6.55
Continental Refrigerator	1FNG	Reach-in	18.83	6.69
Continental Refrigerator	1FNG	Reach-in	18.60	6.62
Continental Refrigerator	1FXNG	Reach-in	28.66	6.51
Continental Refrigerator	1FXNG	Reach-in	28.36	6.53
Continental Refrigerator	1FXNG	Reach-in	33.16	8.74
Continental Refrigerator	1FXNG	Reach-in	22.36	6.43
Continental Refrigerator	1FXNG	Reach-in	22.06	6.46
Continental Refrigerator	D1FESNG	Reach-in	18.79	6.50
Continental Refrigerator	D1FESNG	Reach-in	18.52	6.55
Continental Refrigerator	D1FXNG	Pass-Through	33.16	8.74
Continental Refrigerator	D2FENG	Reach-in	49.07	11.90
Continental Refrigerator	D2FENG	Reach-in	48.65	12.04
Continental Refrigerator	D2FNG	Reach-in	44.14	11.19
Continental Refrigerator	D2FNG	Reach-in	43.72	11.32
Desmon SPA	PGB07G-A	Reach-in	19.38	6.09
Desmon SPA	PGB14G-A	Reach-in	42.36	11.59
Desmon SPA	PGB21G-A	Reach-in	71.57	16.72
Hoshizaki	UF27A-GLP01	Undercounter	6.22	3.13
Husmann Corporation	MD4060DA	Reach-in	16.80	2.18
Husmann Corporation	RM2W	Reach-in	71.50	5.51
Husmann Corporation	VRL1B1A	Reach-in	22.80	6.30
Husmann Corporation	VRL2B1A	Reach-in	44.50	10.71
Husmann Corporation	VRL3B1A	Reach-in	66.10	14.60
Imbera	EVC09 HC	Reach-in	7.17	1.05
Imbera	LTF23 HC	Reach-in	22.43	7.19
Imbera	LTF23 R2	Reach-in	22.43	7.19
Imbera	VFS12 HC	Reach-in	9.80	4.09
Imbera	VR11 CZ HC	Reach-in	10.20	1.34
Imbera	VR13 CZ HC	Reach-in	11.70	1.49
Imbera	VR27 CZ HC	Reach-in	27.80	2.45
Kelvinator COMMERCIAL	KCHGICM23FB	Reach-in	19.20	6.54
Kelvinator COMMERCIAL	KCHGICM49FB	Reach-in	43.80	10.57
Kelvinator COMMERCIAL	KCHGM48F	Reach-in	43.80	10.57
METALFRIO	NG5CHC	Reach-in	5.37	2.26
METALFRIO	VN20MX	Reach-in	6.22	2.88
METALFRIO	VN22MX	Reach-in	7.63	3.25
Migali	C-2FBG-Hce	Reach-in	43.80	12.14
Minus Forty	07-CSGF-00-1C00*-*****	Reach-in	6.43	3.57
Minus Forty	07-CSGF-01-1C00*-*****	Reach-in	6.43	3.57
Minus Forty	09-USGF-00-1C00*-*****	Reach-in	7.88	3.06
Minus Forty	09-USGF-X1-1C00*-*****	Reach-in	7.88	3.06

Qualified Glass Door Freezers

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
ACCUCOLD	SPF5*	Reach-in	3.20	1.99
Minus Forty	09M-USGF-00-1C00*_*****	Reach-in	6.60	3.30
Minus Forty	09M-USGF-X1-1C00*_*****	Reach-in	6.60	3.30
Minus Forty	10-USGF-00-1C00*_*****	Reach-in	9.15	3.47
Minus Forty	10-USGF-X1-1C00*_*****	Reach-in	9.15	3.47
Minus Forty	11-CSGF-00-1C00*_*****	Reach-in	12.53	5.16
Minus Forty	13-USGF-00-1C00*_*****	Reach-in	11.24	4.41
Minus Forty	13-USGF-L2-1C00*_*****	Reach-in	11.24	4.41
Minus Forty	13-USGF-X1-1C00*_*****	Reach-in	11.24	4.41
Minus Forty	19-USGF-00-1C00*_*****	Reach-in	18.39	5.41
Minus Forty	19-USGF-L2-1C00*_*****	Reach-in	18.39	5.41
Minus Forty	19-USGF-X1-1C00*_*****	Reach-in	18.39	5.41
Minus Forty	22-USGF-00-1C00*_*****	Reach-in	21.50	5.78
Minus Forty	22-USGF-F1-1C00*_*****	Reach-in	21.83	6.39
Minus Forty	22-USGF-F2-1C00*_*****	Reach-in	21.83	6.39
Minus Forty	22-USGF-L2-1C00*_*****	Reach-in	21.50	5.78
Minus Forty	22-USGF-X1-1C00*_*****	Reach-in	21.50	5.78
Minus Forty	43-UDGF-00-1C010	Reach-in	35.45	10.46
Minus Forty	43-UDGF-L1-1C010	Reach-in	35.45	10.46
Minus Forty	43-UDGF-X1-1C010	Reach-in	35.45	10.46
Minus Forty	72-UTGF-00-1C000	Reach-in	62.00	16.32
OMCAN INC	FR-CN-0045-HC	Reach-in	42.50	11.19
OMCAN INC	FR-CN-1473	Reach-in	17.65	2.27
Pro-Kold	EVC09 HC	Reach-in	7.17	1.05
Pro-Kold	VFS12 HC	Reach-in	9.80	4.09
Pro-Kold	VR11 CZ HC	Reach-in	10.20	1.34
Pro-Kold	VR13 CZ HC	Reach-in	11.70	1.49
Pro-Kold	VR27 CZ HC	Reach-in	27.80	2.45
Summit Commercial	FS20L*GL*	Other	1.60	1.35
Summit Commercial	FS22L*GL*	Other	1.20	1.35
Summit Commercial	FS24L*GL*	Other	1.40	1.35
Summit Commercial	SCFU386*	Reach-in	1.77	2.20
True	FLM-54F~TSL01	Reach-in	43.61	10.54
True	FLM-81F~TSL01	Reach-in	67.30	17.73
True	GDIM-26NT-HC~TSL01	Reach-in	22.53	7.13
True	GDIM-49NT-HC~TSL01	Reach-in	41.03	9.02
True	GDM-07F-HC~FGD01	Reach-in	6.52	3.84
True	GDM-07F-HC~TSL01	Reach-in	6.52	3.84
True	GDM-10F-HC~FGD01	Reach-in	8.48	3.98
True	GDM-10F-HC~TSL01	Reach-in	8.48	3.98
True	GDM-12F-HC~FGD01	Reach-in	10.50	3.67
True	GDM-12F-HC~TSL01	Reach-in	10.50	3.67
True	GDM-19T-F-HC~FGD01	Reach-in	15.34	4.82
True	GDM-19T-F-HC~TSL01	Reach-in	15.34	4.82
True	GDM-23F-HC~FGD01	Reach-in	19.11	4.57
True	GDM-23F-HC~TSL01	Reach-in	19.11	4.57
True	GDM-26F-HC~FGD01	Reach-in	21.83	5.03
True	GDM-26F-HC~TSL01	Reach-in	21.83	5.03
True	GDM-35F-HC~FGD01	Reach-in	29.30	7.71
True	GDM-35F-HC~TSL01	Reach-in	29.30	7.71
True	GDM-43F-HC~FGD01	Reach-in	35.79	8.11
True	GDM-43F-HC~TSL01	Reach-in	35.79	8.11
True	GDM-49F-HC~FGD01	Reach-in	41.71	9.74
True	GDM-49F-HC~TSL01	Reach-in	41.71	9.74
True	GDM-72F-HC~FGD01	Reach-in	61.93	14.40
True	GDM-72F-HC~TSL01	Reach-in	61.93	14.40
True	T-12FG-HC~FGD01	Reach-in	10.43	4.59
True	T-23FG-HC~FGD01	Reach-in	18.40	5.73

Qualified Glass Door Freezers

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).

NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
ACCUCOLD	SPF5*	Reach-in	3.20	1.99
TRUE	TRM2L-***_***_*****_**_*	Reach-in	77.89	19.59
TRUE	TRM3L-***_***_*****_**_*	Reach-in	116.15	27.30
TRUE	TRM4L-***_***_*****_**_*	Reach-in	154.41	36.24
True	TS-23FG-HC~FGD01	Reach-in	18.40	5.73
True	TUC-60G-ADA-HC~SPEC3	Undercounter	17.50	2.51
Turbo Air	TGF-10SD*-N	Reach-in	7.92	4.07
Turbo Air	TGF-23F-N	Reach-in	17.70	5.61
Turbo Air	TGF-23F-S-N	Reach-in	17.70	5.61
Turbo Air	TGF-23FAB-N	Reach-in	17.70	5.61
Turbo Air	TGF-23FB-N	Reach-in	17.70	5.61
Turbo Air	TGF-23FB-S-N	Reach-in	17.70	5.61
Turbo Air	TGF-23SD*-N	Reach-in	17.99	6.08
Turbo Air	TGF-23SDB-N-L	Reach-in	17.99	6.08
Turbo Air	TGF-23SDHB-N	Reach-in	19.94	6.36
Turbo Air	TGF-23SDHB-N-L	Reach-in	17.94	6.36
Turbo Air	TGF-23SDHV-N	Reach-in	17.94	6.36
Turbo Air	TGF-23SDHV-N-L	Reach-in	17.94	6.36
Turbo Air	TGF-23SDHW-N	Reach-in	17.94	6.36
Turbo Air	TGF-23SDHW-N-L	Reach-in	17.94	6.36
Turbo Air	TGF-23SDV-N-L	Reach-in	17.09	6.08
Turbo Air	TGF-23SDW-N-L	Reach-in	17.99	6.08
Turbo Air	TGF-35SD*-N	Reach-in	28.44	8.27
Turbo Air	TGF-35SDHB-N	Reach-in	30.94	9.44
Turbo Air	TGF-35SDHV-N	Reach-in	30.94	9.44
Turbo Air	TGF-35SDHW-N	Reach-in	30.94	9.44
Turbo Air	TGF-47SDB-N	Reach-in	39.00	11.35
Turbo Air	TGF-47SDB-N-LT	Reach-in	39.00	10.90
Turbo Air	TGF-47SDHB-N	Reach-in	42.12	11.36
Turbo Air	TGF-47SDHV-N	Reach-in	42.12	11.36
Turbo Air	TGF-47SDHW-N	Reach-in	42.12	11.36
Turbo Air	TGF-47SDS-N-LT	Reach-in	39.00	10.90
Turbo Air	TGF-47SDSB-N-LT	Reach-in	39.00	10.90
Turbo Air	TGF-47SDSW-N-LT	Reach-in	39.00	10.90
Turbo Air	TGF-47SDV-N	Reach-in	39.00	11.35
Turbo Air	TGF-47SDW-N	Reach-in	39.00	11.35
Turbo Air	TGF-47SDW-N-LT	Reach-in	39.00	10.90
Turbo Air	TGF-49F-N	Reach-in	39.88	11.26
Turbo Air	TGF-49F-S-N	Reach-in	39.88	11.26
Turbo Air	TGF-49FAB-N	Reach-in	39.88	11.26
Turbo Air	TGF-49FB-N	Reach-in	39.88	11.26
Turbo Air	TGF-49FB-S-N	Reach-in	39.88	11.26
Turbo Air	TGIM-23B-N	Reach-in	17.70	5.50
Turbo Air	TGIM-23HB-N	Reach-in	17.30	5.26
Turbo Air	TGIM-23HB-N-L	Reach-in	17.30	5.26
Turbo Air	TGIM-23HW-N	Reach-in	17.30	5.26
Turbo Air	TGIM-23HW-N-L	Reach-in	17.30	5.26
Turbo Air	TGIM-23W-N	Reach-in	17.70	5.50
Turbo Air	TJMF-30SDAB-N	Reach-in	32.04	9.42
Turbo Air	TJMF-30SDB-N	Reach-in	32.04	9.42
Turbo Air	TJMF-30SDW-N	Reach-in	32.04	9.42
Turbo Air	TJMF-55SDAB-N	Reach-in	60.04	13.42
Turbo Air	TJMF-55SDB-N	Reach-in	60.04	13.42
Turbo Air	TJMF-55SDW-N	Reach-in	60.04	13.42
Turbo Air	TJMF-85SDAB-N	Reach-in	93.80	22.64
Turbo Air	TJMF-85SDB-N	Reach-in	93.80	22.64
Turbo Air	TJMF-85SDW-N	Reach-in	93.80	22.64
Turbo Air	TJMI-30SDAB-N	Reach-in	32.04	9.02

Qualified Glass Door Freezers

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).

NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
ACCUCOLD	SPF5*	Reach-in	3.20	1.99
Turbo Air	TJMI-30SDB-N	Reach-in	32.04	9.02
Turbo Air	TJMI-30SDW-N	Reach-in	32.04	9.02
Turbo Air	TJMI-55SDAB-N	Reach-in	60.04	13.42
Turbo Air	TJMI-55SDB-N	Reach-in	60.04	13.42
Turbo Air	TJMI-55SDW-N	Reach-in	60.04	13.42
Turbo Air	TSF-23GSD-N	Reach-in	19.13	5.26
Victory	FS-2D-ST**G*HC*****	Reach-in	44.60	12.10
Victory	FSA-2D-ST**G*HC*****	Reach-in	44.60	12.10

Qualified Glass Door Freezers

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).

NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
ACCUCOLD	SPF5*	Reach-in	3.20	1.99

Qualified Solid Door Freezers

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
ACCUCOLD	ACF332D*	Undercounter	2.50	1.36
ACCUCOLD	ALF62*	Undercounter	3.50	1.37
ACCUCOLD	FS24L*	Other	2.10	1.14
ACCUCOLD	FS407*/FS408*	Reach-in	2.80	0.90
Atosa	MBF8001GR	Reach-in	21.40	3.45
Atosa	MBF8007GR	Reach-in	21.20	4.20
Atosa	MBF8008GR	Reach-in	41.92	7.31
Atosa	MBF8501GR	Reach-in	20.00	4.33
Avantco	178A23FHC	Reach-in	20.60	3.76
Avantco	178A49FHC	Reach-in	41.32	7.12
Avantco	178AU27F	Undercounter	6.10	2.12
Avantco	178AU60FHC	Undercounter	14.19	3.53
Avantco	178AWT27F	Work-Top Table	6.10	2.12
Avantco	178AWT60FHC	Work-Top Table	14.19	3.53
Avantco	178SS1FHC	Reach-in	20.60	3.76
Avantco	178SS2FHC	Reach-in	41.32	7.12
Avantco	178Z**36F***	Undercounter	8.30	1.06
Avantco	178Z**48F***	Undercounter	10.30	2.90
Avantco	178Z**60F***	Undercounter	13.40	3.40
Avantco	178Z1FHC	Reach-in	21.26	4.44
Avantco	178Z2F4K	Reach-in	42.34	7.52
Avantco	178Z2FHC	Reach-in	42.59	7.19
Avantco	178ZUC48FHC	Undercounter	10.29	2.92
Avantco	178ZUC60FHC	Undercounter	13.39	3.41
Avantco	178ZWT48FHC	Work-Top Table	10.29	2.92
Avantco	178ZWT60FHC	Work-Top Table	13.39	3.41
Avantco	447AP23F	Reach-in	20.16	4.32
Avantco	447AP49F	Reach-in	44.85	8.18
Avantco	CFD-1FF	Reach-in	20.60	4.70
Avanti	MCCF5F0W	Reach-in	5.00	0.60
Avanti	MCCF7F0W	Reach-in	7.00	0.70
Beverage-Air	FB35HC-1*S*****	Reach-in	36.87	6.83
Beverage-Air	FB44HC-1*S*****	Reach-in	44.00	7.69
Beverage-Air	FB49HC-1*S*****	Reach-in	46.10	8.20
Beverage-Air	HBF35HC-1*S*****	Reach-in	36.87	6.83
Beverage-Air	HBF44HC-1*****	Reach-in	44.00	7.69
Beverage-Air	HBF49HC-1*****	Reach-in	46.10	8.20
Beverage-Air	HFIHC-1HS*****	Reach-in	21.66	4.59
Beverage-Air	HFIHC-1S*****	Reach-in	21.66	4.59
Beverage-Air	HFIWHC-1HS*****	Reach-in	30.37	5.37
Beverage-Air	HFIWHC-1S*****	Reach-in	30.37	5.37
Beverage-Air	HF2HC-1HS*****	Reach-in	45.20	6.66
Beverage-Air	HF2HC-1S*****	Reach-in	45.20	6.66
Beverage-Air	HF3HC-1HS*****	Reach-in	69.10	11.76
Beverage-Air	HF3HC-1S*****	Reach-in	69.10	11.76
Beverage-Air	HFP1HC-1HS*****	Reach-in	21.66	4.59
Beverage-Air	HFP1HC-1S*****	Reach-in	21.66	4.59
Beverage-Air	HFP1WHC-1HS*****	Reach-in	30.37	5.37
Beverage-Air	HFP1WHC-1S*****	Reach-in	30.37	5.37
Beverage-Air	HFP2HC-1HS*****	Reach-in	45.20	6.66
Beverage-Air	HFP2HC-1S*****	Reach-in	45.20	6.66
Beverage-Air	HFP3HC-1HS*****	Reach-in	69.10	11.76
Beverage-Air	HFP3HC-1S*****	Reach-in	69.10	11.76
Beverage-Air	HFPS1HC-1HS*****	Reach-in	21.66	4.59
Beverage-Air	HFPS1HC-1S*****	Reach-in	21.66	4.59
Beverage-Air	HFPS1WHC-1HS*****	Reach-in	30.37	5.37
Beverage-Air	HFPS1WHC-1S*****	Reach-in	30.37	5.37
Beverage-Air	HFPS2HC-1HS*****	Reach-in	45.20	6.66

Qualified Solid Door Freezers

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
Beverage-Air	HFPS2HC-1S*****	Reach-in	45.20	6.66
Beverage-Air	HFPS3HC-1HS*****	Reach-in	69.10	11.76
Beverage-Air	HFPS3HC-1S*****	Reach-in	69.10	11.76
Beverage-Air	HFS1HC-1HS*****	Reach-in	21.66	4.59
Beverage-Air	HFS1HC-1S*****	Reach-in	21.66	4.59
Beverage-Air	HFS1WHC-1HS*****	Reach-in	30.37	5.37
Beverage-Air	HFS1WHC-1S*****	Reach-in	30.37	5.37
Beverage-Air	HFS2HC-1HS*****	Reach-in	45.20	6.66
Beverage-Air	HFS2HC-1S*****	Reach-in	45.20	6.66
Beverage-Air	HFS3HC-1HS*****	Reach-in	69.10	11.76
Beverage-Air	HFS3HC-1S*****	Reach-in	69.10	11.76
Beverage-Air	UCF20HC-*****	Undercounter	2.27	1.35
Beverage-Air	UCF24HC-*****	Undercounter	4.53	1.79
Beverage-Air	UCF27AHC-*****	Undercounter	5.87	2.01
Beverage-Air	UCF27HC-*****	Undercounter	5.24	1.89
Beverage-Air	UCF32AHC-*****	Undercounter	7.22	2.17
Beverage-Air	UCF36AHC-*****	Undercounter	8.69	2.09
Beverage-Air	UCF60AHC-*****	Undercounter	14.39	3.56
Beverage-Air	UCF67AHC-*****	Undercounter	20.08	4.13
Beverage-Air	WTF20HC-*****	Work-Top Table	2.27	1.35
Beverage-Air	WTF24HC-*****	Work-Top Table	4.53	1.79
Beverage-Air	WTF27AHC-*****	Work-Top Table	5.87	2.01
Beverage-Air	WTF27HC-*****	Work-Top Table	5.24	1.89
Beverage-Air	WTF32AHC-*****	Work-Top Table	7.22	2.17
Beverage-Air	WTF36AHC-*****	Work-Top Table	8.69	2.09
Beverage-Air	WTF60AHC-*****	Work-Top Table	14.39	3.56
Beverage-Air	WTF67AHC-*****	Work-Top Table	20.08	4.13
Beverage-Air	WTFD27AHC-*****	Work-Top Table	5.87	2.09
Blue Air	BSF23-HC	Reach-in	18.62	4.44
Blue Air	BSF23T-HC	Reach-in	19.04	4.40
Blue Air	BSF49-HC	Reach-in	41.83	7.73
Blue Air	BSF49T-HC	Reach-in	42.52	7.25
Blue Air	BSF72-HC	Reach-in	65.20	11.41
Blueline	BF-600V	Other	18.01	3.38
Continental Refrigerator	1F-HD-R	Reach-in	18.97	4.47
Continental Refrigerator	1F-R	Reach-in	18.83	4.46
Continental Refrigerator	1FE-R	Reach-in	21.38	4.75
Continental Refrigerator	1FEN	Reach-in	21.38	4.60
Continental Refrigerator	1FENHD	Reach-in	21.11	4.65
Continental Refrigerator	1FES-HD-R	Reach-in	18.52	4.30
Continental Refrigerator	1FES-R	Reach-in	18.79	4.31
Continental Refrigerator	1FESN	Reach-in	18.79	4.35
Continental Refrigerator	1FESNHD	Reach-in	18.52	4.34
Continental Refrigerator	1FN	Reach-in	18.97	4.45
Continental Refrigerator	1FX-HD-R	Reach-in	28.36	5.01
Continental Refrigerator	1FX-R	Reach-in	28.66	4.73
Continental Refrigerator	1FXN	Reach-in	28.66	4.80
Continental Refrigerator	1FXNHD	Reach-in	28.36	4.83
Continental Refrigerator	1FXS-HD-R	Reach-in	22.06	4.70
Continental Refrigerator	1FXS-R	Reach-in	22.36	4.43
Continental Refrigerator	1FXSN	Reach-in	22.36	4.58
Continental Refrigerator	1FXSNHD	Reach-in	22.06	4.72
Continental Refrigerator	2F	Reach-in	43.45	7.28
Continental Refrigerator	2F-CW	Reach-in	44.58	9.20
Continental Refrigerator	2F-HD	Reach-in	43.03	7.47
Continental Refrigerator	2F-PT-R	Pass-Through	47.18	10.11
Continental Refrigerator	2F-R	Reach-in	43.45	9.29
Continental Refrigerator	2FE	Reach-in	48.75	7.35

Qualified Solid Door Freezers

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
Continental Refrigerator	2FE-HD	Reach-in	48.33	7.53
Continental Refrigerator	2FE-HD-R	Reach-in	48.33	8.94
Continental Refrigerator	2FE-PT-R	Pass-Through	53.79	11.28
Continental Refrigerator	2FE-R	Reach-in	48.75	9.01
Continental Refrigerator	2FEN	Reach-in	48.75	9.45
Continental Refrigerator	2FENHD	Reach-in	48.33	9.82
Continental Refrigerator	2FENPT	Pass-Through	53.80	10.27
Continental Refrigerator	2FENPTHD	Pass-Through	53.00	10.97
Continental Refrigerator	2FES	Reach-in	40.75	7.17
Continental Refrigerator	2FES-HD	Reach-in	40.33	7.49
Continental Refrigerator	2FN	Reach-in	43.45	8.85
Continental Refrigerator	2FNHD	Reach-in	43.03	9.17
Continental Refrigerator	2FNPT	Pass-Through	47.20	9.79
Continental Refrigerator	D1FESN	Reach-in	18.79	4.35
Continental Refrigerator	D1FESNHD	Reach-in	18.52	4.34
Continental Refrigerator	D1FXSN	Reach-in	22.36	4.58
Continental Refrigerator	D1FXSNHD	Reach-in	22.06	4.72
Continental Refrigerator	D2FEN	Reach-in	49.07	8.03
Continental Refrigerator	D2FENHD	Reach-in	48.65	8.42
Continental Refrigerator	D2FENPT	Pass-Through	53.79	10.27
Continental Refrigerator	D2FENPTHD	Pass-Through	52.95	10.97
Continental Refrigerator	D2FN	Reach-in	44.14	7.67
Continental Refrigerator	D2FNHD	Reach-in	43.72	8.01
Continental Refrigerator	D2FNPT	Pass-Through	47.18	9.79
Continental Refrigerator	DL1F-HD-R	Reach-in	19.25	4.26
Continental Refrigerator	DL1F-R	Reach-in	19.34	4.13
Continental Refrigerator	DL1FE-HD-R	Reach-in	21.51	4.45
Continental Refrigerator	DL1FE-R	Reach-in	21.78	4.30
Continental Refrigerator	DL2F-PT-R	Pass-Through	47.18	10.11
Continental Refrigerator	DL2F-R	Reach-in	44.14	9.27
Continental Refrigerator	DL2FE-HD-R	Reach-in	48.65	9.91
Continental Refrigerator	DL2FE-PT-R	Pass-Through	53.79	11.28
Continental Refrigerator	DL2FE-R	Reach-in	49.07	9.71
Danby	DH016A1*	Reach-in	1.60	0.60
Danby	DH032A1*	Reach-in	3.20	0.80
Delfield	18FC43V	Work-Top Table	8.32	2.39
Delfield	18FC62V	Work-Top Table	13.86	3.14
Delfield	407P-ES*****	Undercounter	5.70	2.04
Delfield	4524NP	Work-Top Table	6.14	1.68
Delfield	4527NP	Work-Top Table	7.14	1.94
Delfield	4532NP	Work-Top Table	8.80	1.76
Delfield	4548NP	Undercounter	14.02	2.72
Delfield	4560NP	Work-Top Table	17.40	3.21
Delfield	4564NP	Work-Top Table	18.73	3.61
Delfield	4572NP	Work-Top Table	21.29	4.22
Delfield	6125XL-S	Reach-in	18.90	4.04
Delfield	6125XL-SH	Reach-in	18.70	4.13
Delfield	6151XL-S	Reach-in	41.44	7.74
Delfield	6151XL-SH	Reach-in	41.45	7.96
Delfield	CSFPT2P-SH	Reach-in	49.38	10.23
Delfield	D4524NP	Work-Top Table	6.28	1.98
Delfield	F17C88CP	Other	14.07	3.81
Delfield	F18FC43V	Work-Top Table	8.32	2.39
Delfield	F18FC47P*****	Work-Top Table	8.07	2.08
Delfield	F18FC62P*****	Work-Top Table	13.61	3.11
Delfield	F18FC62V	Work-Top Table	13.86	3.14
Delfield	F18FC88P*****	Work-Top Table	23.21	3.77
Delfield	F2688*P****	Other	14.07	3.81

Qualified Solid Door Freezers

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
Delfield	F2694*P****	Other	14.07	3.81
Delfield	GAF2P-G	Reach-in	46.82	10.03
Delfield	GAF2P-SH*****	Reach-in	45.58	9.62
Delfield	GAF3P-S*****	Reach-in	71.22	12.54
Delfield	GAF3P-SH*****	Reach-in	70.81	12.72
Delfield	GAFPT1P-S*****	Pass-Through	23.63	4.82
Delfield	GAFPT2P-S*****	Pass-Through	49.93	8.23
Delfield	GAFPT2P-SH*****	Pass-Through	49.38	10.21
Delfield	GAFR11P-S*****	Roll-In	37.66	7.61
Delfield	GAFR12P-S*****	Roll-In	76.34	14.34
Delfield	GARI2P-S*****	Roll-In	76.34	4.21
Delfield	GUF32P-D****	Undercounter	7.53	2.46
Delfield	GUF32P-S****	Undercounter	7.53	2.17
Delfield	GUF60P-S****	Undercounter	15.09	4.02
Delfield	ST4524NP*****	Work-Top Table	6.14	1.68
Delfield	ST4527NP	Work-Top Table	7.14	1.94
Delfield	ST4532NP	Work-Top Table	8.80	1.76
Delfield	ST4548NP	Work-Top Table	14.02	2.72
Delfield	ST4560NP	Work-Top Table	17.40	3.21
Delfield	ST4572NP*****	Work-Top Table	21.29	4.22
Delfield	STD4524NP	Work-Top Table	6.28	1.98
Desmon SPA	PBB14C-A	Other	45.79	8.31
Desmon SPA	PGB07C-A	Other	19.42	4.49
Desmon SPA	PGB14C-A	Other	42.32	7.47
Desmon SPA	PGB21C-A	Other	71.57	13.69
ECEVT	ST54BF	Reach-in	43.40	8.34
FERUEO	ST54BF	Reach-in	43.40	8.34
Fogel	MTF-48	Undercounter	12.09	3.17
Freezlabs	ST54BF	Reach-in	43.40	8.34
Fresh Town Co Ltd	FRB-23FS	Reach-in	18.22	3.73
Fresh Town Co Ltd	FRB-23FSL	Reach-in	18.22	3.29
Fresh Town Co Ltd	FRB-49FS	Reach-in	40.93	6.06
Fresh Town Co Ltd	FRB-72FS	Reach-in	63.75	9.66
Galaxy	177CF10HC	Other	9.60	1.07
Galaxy	177CF13HC	Other	12.60	1.12
Galaxy	177GRI18FW	Reach-in	18.01	3.33
Galaxy	177GRI20FW	Reach-in	19.31	4.53
Hoshizaki	DT1A-HS	Reach-in	20.38	4.49
Hoshizaki	DT2A-FS	Reach-in	46.22	8.43
Hoshizaki	DT2A-HS	Reach-in	46.22	8.43
Hoshizaki	UF60B-***	Undercounter	15.10	3.95
Hoshizaki	UF60B-****	Undercounter	15.10	3.95
Hoshizaki	ULF46B-****	Undercounter	11.78	3.36
Hoshizaki	ULF67B-****	Undercounter	19.97	4.49
Hoshizaki	WF60B-***	Work-Top Table	15.10	3.95
Hoshizaki	WF60B-****	Work-Top Table	15.10	3.95
Hoshizaki	WLF46B-****	Work-Top Table	11.78	3.36
Hoshizaki	WLF67B-****	Work-Top Table	19.97	4.49
Imbera	SSF-20-1S	Reach-in	21.70	4.71
Imbera	SSF-45-2S	Reach-in	46.30	9.66
Imbera	VRF-24-1DS	Reach-in	22.90	4.89
Kelvinator COMMERCIAL	KCCF140WH	Reach-in	14.20	1.20
Kelvinator COMMERCIAL	KCCF140WH	Other	14.20	1.20
Kelvinator COMMERCIAL	KCCF170WH	Reach-in	17.30	1.20
Kelvinator COMMERCIAL	KCCF170WH	Other	17.30	1.20
Kelvinator COMMERCIAL	KCCF210WH	Reach-in	20.90	1.58
Kelvinator COMMERCIAL	KCCF210WH	Other	20.90	1.62
Kelvinator COMMERCIAL	KCHRI27RIDFE	Reach-in	17.80	2.90

Qualified Solid Door Freezers

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
Kelvinator COMMERCIAL	KCHRI27R2HDF	Reach-in	17.80	2.90
Kelvinator COMMERCIAL	KCHRI54R2DFE	Reach-in	42.00	4.97
Kelvinator COMMERCIAL	KCHRI81R3DF	Reach-in	66.00	7.71
Kelvinator COMMERCIAL	KCHUC48F	Undercounter	10.10	2.92
Kelvinator COMMERCIAL	KCHUC48F-32	Undercounter	10.10	2.91
Kelvinator COMMERCIAL	KCHUCWT48F	Undercounter	10.10	2.92
KERONG	BD-100CT	Other	3.46	1.46
KUTANO	KUTFISS	Reach-in	20.10	4.36
KUTANO	KUTF2SS**	Reach-in	44.85	8.24
LCEKY	ST54BF	Reach-in	43.40	8.34
Main Street	829BMR23F	Reach-in	20.60	4.57
Migali	C-1F-HC	Reach-in	21.40	3.68
Migali	C-2F-HC	Reach-in	42.18	6.23
Minus Forty	22-USSF-00-1C00*-*****	Reach-in	21.31	4.63
Minus Forty	22-USSF-X1-1C00*-*****	Reach-in	21.31	4.63
Pro-Kold	SSF-20-1S	Reach-in	21.70	4.71
Pro-Kold	SSF-45-2S	Reach-in	46.30	9.66
Pro-Kold	VRF-24-1DS	Reach-in	22.90	4.89
Randell	9404-32-290	Undercounter	10.80	3.06
Randell	9404-32-290*	Undercounter	10.80	3.06
RefrigerationX	XF19-1-N	Reach-in	18.46	3.77
RefrigerationX	XF24-1-N	Reach-in	21.94	3.92
RefrigerationX	XF47-2-N	Reach-in	42.27	6.74
Silver King	SKF27A-ED***	Reach-in	7.85	2.31
Summit Commercial	ADFD2D24	Other	3.46	1.46
Summit Commercial	ADFD2D24OS	Other	3.46	1.46
Summit Commercial	AFM19W**	Reach-in	18.30	3.30
Summit Commercial	CCF8	Other	8.10	1.00
Summit Commercial	FS20L*	Reach-in	1.60	1.04
Summit Commercial	FS21L*	Other	1.40	1.00
Summit Commercial	FS22L*	Reach-in	1.42	1.04
Summit Commercial	SCFF237**	Reach-in	19.53	4.29
Summit Commercial	SCFF237LH**	Reach-in	19.53	4.29
Summit Commercial	SCFF2D24	Other	3.46	1.46
Summit Commercial	SCFF497**	Reach-in	42.24	7.10
Summit Commercial	SCFF497LH**	Reach-in	42.24	7.10
Summit Commercial	SCFF727**	Reach-in	60.84	10.65
Summit Commercial	SCFF727LH**	Reach-in	60.84	10.65
Summit Commercial	SCFM83	Other	8.10	1.00
Summit Commercial	SCUF18*	Reach-in	16.80	3.10
Summit Commercial	SCUF20*	Reach-in	20.50	3.65
Summit Commercial	SPFF2D24OS	Other	3.46	1.46
Summit Commercial	VT65M*	Reach-in	3.50	1.45
Traulsen	AL232N-X0031	Reach-in	46.02	9.69
Traulsen	AL232W-X0029	Reach-in	50.40	10.57
Traulsen	ALT232WUT-FHS-eS	Reach-in	50.53	11.04
Traulsen	ALT232WUT-HHS-eS	Reach-in	50.40	11.02
Traulsen	ALT332WUT-FHS-eS	Reach-in	77.45	14.67
Traulsen	ALT332WUT-HHS-eS	Reach-in	77.26	14.65
Traulsen	G12000-ES	Reach-in	23.37	4.80
Traulsen	G12001-ES	Reach-in	23.37	4.80
Traulsen	G12010-ES	Reach-in	23.43	4.81
Traulsen	G12011-ES	Reach-in	23.43	4.81
Traulsen	G22000R	Reach-in	45.89	9.67
Traulsen	G22001R	Reach-in	45.89	9.67
Traulsen	G22002R	Reach-in	45.89	9.67
Traulsen	G22003R	Reach-in	45.89	9.67
Traulsen	G22010	Reach-in	46.02	9.89

Qualified Solid Door Freezers

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).
NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
Traulsen	G22010R	Reach-in	46.02	9.69
Traulsen	G22011	Reach-in	46.02	9.89
Traulsen	G22011R	Reach-in	46.02	9.69
Traulsen	G22012	Reach-in	46.02	9.89
Traulsen	G22012R	Reach-in	46.02	9.69
Traulsen	G22013	Reach-in	46.02	9.89
Traulsen	G22013R	Reach-in	46.02	9.69
Traulsen	G31000-032	Reach-in	69.15	13.55
Traulsen	G31001-032	Reach-in	69.15	13.55
Traulsen	G31002-032	Reach-in	69.15	13.55
Traulsen	G31003-032	Reach-in	69.15	13.55
Traulsen	G31010-032	Reach-in	69.35	13.58
Traulsen	G31011-032	Reach-in	69.35	13.58
Traulsen	G31012-032	Reach-in	69.35	13.58
Traulsen	G31013-032	Reach-in	69.35	13.58
Traulsen	RL232W-X0091	Reach-in	50.53	10.59
Traulsen	RLT232WUT-FHS-eS	Reach-in	50.53	11.04
Traulsen	RLT232WUT-HHS-eS	Reach-in	50.40	11.02
Traulsen	RLT332WUT-FHS-eS	Reach-in	77.45	14.67
Traulsen	RLT332WUT-HHS-eS	Reach-in	77.26	14.65
True	STA3F-3S-HC	Reach-in	70.33	13.81
True	STG3F-3S-HC	Reach-in	70.33	13.81
True	STR3F-3S-HC	Reach-in	70.33	13.81
True	T-19F-HC	Reach-in	14.79	3.89
True	T-19FZ-HC	Reach-in	14.79	3.89
True	T-23F-HC	Reach-in	18.54	4.27
True	T-49F-HC	Reach-in	41.47	8.57
True	TS-23F-HC	Reach-in	18.54	4.27
True	TS-49F-HC	Reach-in	41.47	8.57
True	TUC-27F-ADA-HC	Undercounter	7.07	2.22
True	TUC-27F-ADA-HC~SPEC3	Undercounter	7.07	2.22
True	TUC-27F-HC	Undercounter	7.07	2.22
True	TUC-27F-HC~SPEC3	Undercounter	7.07	2.22
True	TUC-27F-LP-HC	Undercounter	7.07	2.22
True	TUC-27F-LP-HC~SPEC3	Undercounter	7.07	2.22
True	TUC-44F-HC	Undercounter	11.14	3.23
True	TUC-44F-HC~SPEC3	Undercounter	11.14	3.23
True	TUC-48F-ADA-HC	Undercounter	12.85	3.56
True	TUC-48F-ADA-HC~SPEC3	Undercounter	12.85	3.56
True	TUC-48F-HC	Undercounter	12.85	3.56
True	TUC-48F-HC~SPEC3	Undercounter	12.85	3.56
True	TUC-48F-LP-HC	Undercounter	12.85	3.56
True	TUC-48F-LP-HC~SPEC3	Undercounter	12.85	3.56
True	TWT-27F-HC	Work-Top Table	7.07	2.22
True	TWT-27F-HC~SPEC3	Work-Top Table	7.07	2.22
True	TWT-44F-HC	Work-Top Table	11.14	3.23
True	TWT-44F-HC~SPEC3	Work-Top Table	11.14	3.23
True	TWT-48F-HC	Work-Top Table	12.85	3.56
True	TWT-48F-HC~SPEC3	Work-Top Table	12.85	3.56
Turbo Air	EF19-1-N	Reach-in	18.44	4.37
Turbo Air	EF19-1-N-V	Reach-in	18.46	3.77
Turbo Air	EF19-2-N	Reach-in	18.44	4.37
Turbo Air	EF24-1-N	Reach-in	21.70	4.77
Turbo Air	EF24-1-N-V	Reach-in	21.94	3.92
Turbo Air	EF24-2-N	Reach-in	21.70	4.77
Turbo Air	EF47-2-N	Reach-in	42.10	5.27
Turbo Air	EF47-2-N-V	Reach-in	42.27	6.74
Turbo Air	EF47-4-N	Reach-in	42.10	5.27

Qualified Solid Door Freezers

V-07-2025

Qualifying models must meet ENERGY STAR® Version 5.0 specifications and must be listed in the California Energy Commission database. Refrigeration system must be built-in (packaged).

NOTE: Program criteria are subject to change.

Company	Model Number	Style Type	Total Volume (cu. ft.)	Daily Energy Use (kWh)
Turbo Air	JRF-45	Reach-in	35.97	5.89
Turbo Air	JRF-65	Reach-in	61.84	8.29
Turbo Air	JUF-36-N	Reach-in	6.37	2.11
Turbo Air	JUF-60-N	Reach-in	13.58	3.71
Turbo Air	JURF-72-N	Reach-in	17.76	4.22
Turbo Air	M3F19-1-N	Reach-in	18.44	4.37
Turbo Air	M3F19-2-N	Reach-in	18.44	4.37
Turbo Air	M3F24-1-N	Reach-in	21.70	4.05
Turbo Air	M3F24-2-N	Reach-in	21.70	4.05
Turbo Air	M3F47-2-N	Reach-in	42.10	6.66
Turbo Air	M3F47-4-N	Reach-in	42.10	6.66
Turbo Air	M3F72-3-N	Reach-in	65.88	10.19
Turbo Air	M3F72-6-N	Reach-in	65.88	10.19
Turbo Air	M3RF19-2-N	Reach-in	16.28	3.77
Turbo Air	M3RF45-2	Reach-in	35.97	5.89
Turbo Air	M3RF45-2-N	Reach-in	35.97	5.25
Turbo Air	MUF-28-71I	Reach-in	6.97	1.96
Turbo Air	PRO-50-4F-N	Reach-in	48.70	9.18
Turbo Air	PRO-50F-N	Reach-in	48.70	9.18
Turbo Air	TSF-23SD-N	Reach-in	19.03	3.44
Turbo Air	TSF-23SD-N-L	Reach-in	19.03	3.44
Turbo Air	TSF-35SD-N	Reach-in	29.00	5.45
Turbo Air	TSF-35SDN-N	Reach-in	29.19	4.18
Turbo Air	TSF-49SD	Reach-in	39.90	7.66
Turbo Air	TSF-49SD-N	Reach-in	39.90	5.30
Turbo Air	TSF-72SD	Reach-in	63.80	11.57
Turbo Air	TSF-72SD-N	Reach-in	63.80	7.59
Turbo Air	XBF24-1-N	Reach-in	21.94	3.92
Turbo Air	XBF47-2-N	Reach-in	42.27	6.74
Turbo Air	XF19-1-N	Reach-in	18.46	3.77
Turbo Air	XF24-1-N	Reach-in	21.94	3.92
Turbo Air	XF47-2-N	Reach-in	42.27	6.74
U-Line	UCFZ585-SS71A	Other	71.57	13.68
U-Line	UCRE527-SS31A	Other	19.42	4.49
U-Line	UCRE553-SS71A	Other	42.32	7.46
US Refrigeration	USBV-70F	Reach-in	67.99	10.70
US Refrigeration	USTV-70F	Reach-in	64.88	10.70
Valiance by Hoshizaki	VF1A-FS	Reach-in	20.00	3.89
Valiance by Hoshizaki	VF2A-FS	Reach-in	43.00	6.94
Valiance by Hoshizaki	VUF27A	Reach-in	7.00	1.92
Valiance by Hoshizaki	VUF48A	Reach-in	12.00	3.17
Victory	VEFS-2D-HD-HC*****	Reach-in	45.20	7.93
Victory	VEFS-2D-SD-HC*****	Reach-in	45.20	7.93
Victory	VEFS-3D-HD-HC*****	Reach-in	69.10	11.76
Victory	VEFS-3D-SD-HC*****	Reach-in	69.10	11.76
Victory	VEFSA-2D-HD-HC*****	Reach-in	45.20	7.93
Victory	VEFSA-2D-SD-HC*****	Reach-in	45.20	7.93
Victory	VEFSA-3D-HD-HC*****	Reach-in	69.10	11.76
Victory	VEFSA-3D-SD-HC*****	Reach-in	69.10	11.76
Zero Zone, Inc.	1RVZC30****	Reach-in	32.86	6.39
Zero Zone, Inc.	2RVZC30****	Reach-in	64.49	10.80
Zero Zone, Inc.	3RVZC30****	Reach-in	96.12	15.21
Zero Zone, Inc.	4RVZC30****	Reach-in	127.74	19.62
Zero Zone, Inc.	5RVZC30****	Reach-in	159.37	24.03

Qualified Door-Type Dishwashers

V-07-2025

Qualifying high temperature sanitizing door-type dishwashers must have an idle energy rate ≤ 0.55 kW, a washing energy ≤ 0.35 kWh/rack, and a water consumption ≤ 0.76 gallons/rack.

NOTE: Program criteria are subject to change.

Company	Model Number	Type	Sanitation Method	Idle Energy Rate (kW)	Washing Energy Rate (kWh/rack)	Water Consumption (gal/rack)
Auto-Chlor	A6	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.42	0.24	0.73
Auto-Chlor	A6V	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.42	0.24	0.73
Champion	DH6000 STD	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.40	0.22	0.76
Champion	DH6000T STD	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.40	0.22	0.76
Ecolab	E-HT	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.32	0.24	0.48
Ecolab	E-HT-V	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.41	0.22	0.48
Ecolab	XL-HT	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.44	0.25	0.71
Ecolab	XL-HT VV	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.32	0.24	0.48
Fagor	COP-144W	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.44	0.31	0.68
Fagor	COP-144W-HRS	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.36	0.27	0.66
Fagor	COP-174W	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.31	0.34	0.67
Fagor	COP-174W HRS	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.41	0.31	0.64
Hobart	AM16ASR-*	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.31	0.32	0.67
Hobart	AM16BAS-**	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.31	0.32	0.67
Hobart	AM16BASX-**	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.31	0.32	0.67
Hobart	AM16SVL-*	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.31	0.2	0.67
Hobart	AM16SVLT-*	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.31	0.2	0.67
Hobart	AM16TASR-*	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.31	0.32	0.67
Hobart	AM16TBAS-**	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.31	0.32	0.67
Hobart	AM16VLADV-*	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.31	0.2	0.67
Hobart	AM16VLBAS-*	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.31	0.2	0.67
Hobart	AM16VLBASX-**	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.31	0.2	0.67
Hobart	AM16VLTADV-*	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.31	0.2	0.67
Hobart	AM16VLTBAS-*	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.31	0.2	0.67
Hobart	AM16VLTBASX-*	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.31	0.2	0.67
Hobart	CDH	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.42	0.28	0.73
Insinger	CX20	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.50	0.28	0.67
Jackson	Dynastar	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.34	0.3	0.7
Jackson	Dynastar HH-E	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.32	0.33	0.72
Jackson	Dynastar HH-E-VER	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.36	0.2	0.72
Jackson	Dynastar HH/NB-E	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.32	0.33	0.72
Jackson	Dynastar NB	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.34	0.3	0.7
Jackson	Dynastar VER	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.35	0.2	0.7
Jackson	Tempstar HH-E	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.49	0.32	0.72
Jackson	Tempstar HH/NB-E	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.49	0.32	0.72
Jackson	WareForce HT180HH-E	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.49	0.32	0.72
Jackson	WareForce HT180HH/NB-E	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.49	0.32	0.72
Lamber	L21EKDPS	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.49	0.28	0.33
Lamber	L21EKS	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.49	0.28	0.33
Mainstreet	541HTDT401	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.44	0.31	0.68
Mainstreet	541HTDT403	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.44	0.31	0.68
Meiko	DV 80.2	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.25	0.23	0.76
Meiko	M004DWHIT0M1-20	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.25	0.26	0.75
Meiko	M004DWHIT0M1-20 Heat Recovery	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.30	0.17	0.76
Noble	495HTDT51	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.42	0.28	0.73
Noble	495HTDT513	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.42	0.28	0.73
Noble	495NODTVL1	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.36	0.27	0.66
Noble	495NODTVL3	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.36	0.27	0.66
Noble	WareForce HT-180HH/NB-E	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.49	0.32	0.72
Noble	WareForce HT180HH-E	Single Tank Door-Type	Hot Water Sanitizing (High Temp) Machine	0.49	0.32	0.72

Qualified Hand Wrap Machines

V-07-2025

Only countertop and standalone machines are eligible. The handwrapper must be an on-demand machine replacing an always-on hand wrap machine to be eligible. The handwrapper must utilize a mechanical or optical sensor to activate the largest heating element.

NOTE: Program criteria are subject to change.

Company	Model Number
HeatSeal	104ES
HeatSeal	107ES
HeatSeal	200ES
HeatSeal	625ES
HeatSeal	700ES
HeatSeal	700ES Mini
HeatSeal	725ES
HeatSeal	ESCKR-8
HeatSeal	SM20ES